

OCaml library

October 14, 2003

Contents

1	Module Arg : Parsing of command line arguments.	3
2	Module Array : Array operations.	6
3	Module ArrayLabels : Array operations.	9
4	Module Buffer : Extensible string buffers.	12
5	Module Callback : Registering Caml values with the C runtime.	13
6	Module Camlinternal00 : Run-time support for objects and classes.	14
7	Module Char : Character operations.	15
8	Module Complex : Complex numbers.	16
9	Module Digest : MD5 message digest.	17
10	Module Filename : Operations on file names.	18
11	Module Format : Pretty printing.	20
12	Module Gc : Memory management control and statistics; finalised values.	30
13	Module Genlex : A generic lexical analyzer.	35
14	Module Hashtbl : Hash tables and hash functions.	36
14.1	Module type Hashtbl.HashedType : The input signature of the functor Hashtbl.Make[14.3].	37
14.2	Module type Hashtbl.S : The output signature of the functor Hashtbl.Make[14.3].	38
14.3	Module Hashtbl.Make : Functor building an implementation of the hashtable structure.	38
15	Module Int32 : 32-bit integers.	39
16	Module Int64 : 64-bit integers.	41
17	Module Lazy : Deferred computations.	44

18 Module Lexing :	The run-time library for lexers generated by ocamllex.	45
19 Module List :	List operations.	47
20 Module ListLabels :	List operations.	51
21 Module Map :	Association tables over ordered types.	56
21.1	Module type Map.OrderedType : Input signature of the functor Map.Make[21.3]. . . .	56
21.2	Module type Map.S : Output signature of the functor Map.Make[21.3].	56
21.3	Module Map.Make : Functor building an implementation of the map structure given a totally ordered type.	57
22 Module Marshal :	Marshaling of data structures.	58
23 Module MoreLabels :	Extra labeled libraries.	60
23.1	Module MoreLabels.Hashtbl	60
23.1.1	Module type MoreLabels.Hashtbl.HashedType	61
23.1.2	Module type MoreLabels.Hashtbl.S	61
23.1.3	Module MoreLabels.Hashtbl.Make	61
23.2	Module MoreLabels.Map	61
23.2.1	Module type MoreLabels.Map.OrderedType	62
23.2.2	Module type MoreLabels.Map.S	62
23.2.3	Module MoreLabels.Map.Make	62
23.3	Module MoreLabels.Set	63
23.3.1	Module type MoreLabels.Set.OrderedType	63
23.3.2	Module type MoreLabels.Set.S	63
23.3.3	Module MoreLabels.Set.Make	64
24 Module Nativeint :	Processor-native integers.	64
25 Module Obj :	Operations on internal representations of values.	67
26 Module Oo :	Operations on objects	68
27 Module Parsing :	The run-time library for parsers generated by ocaml yacc.	68
28 Module Pervasives :	The initially opened module.	69
28.1	Module Pervasives.LargeFile : Operations on large files.	84
29 Module Printexc :	Facilities for printing exceptions.	84
30 Module Printf :	Formatted output functions.	85
31 Module Queue :	First-in first-out queues.	87
32 Module Random :	Pseudo-random number generators (PRNG).	88
32.1	Module Random.State	90

33 Module Scnf : Formatted input functions.	90
33.1 Module Scnf.Scanning : Scanning buffers.	93
34 Module Set : Sets over ordered types.	94
34.1 Module type Set.OrderedType : Input signature of the functor Set.Make[34.3]. . . .	95
34.2 Module type Set.S : Output signature of the functor Set.Make[34.3].	95
34.3 Module Set.Make : Functor building an implementation of the set structure given a totally ordered type.	97
35 Module Sort : Sorting and merging lists.	97
36 Module Stack : Last-in first-out stacks.	98
37 Module StdLabels : Standard labeled libraries.	99
37.1 Module StdLabels.Array	99
37.2 Module StdLabels.List	100
37.3 Module StdLabels.String	101
38 Module Stream : Streams and parsers.	102
39 Module String : String operations.	103
40 Module StringLabels : String operations.	106
41 Module Sys : System interface.	108
42 Module Weak : Arrays of weak pointers and hash tables of weak pointers.	111
42.1 Module type Weak.S : The output signature of the functor Weak.Make[42.2].	113
42.2 Module Weak.Make : Functor building an implementation of the weak hash table structure.	114
43 Module Unix : Interface to the Unix system	114
43.1 Module Unix.LargeFile : File operations on large files.	142
44 Module Str : Regular expressions and high-level string processing	143
45 Module Bigarray : Large, multi-dimensional, numerical arrays.	147
45.1 Module Bigarray.Genarray	152
45.2 Module Bigarray.Array1 : One-dimensional arrays.	156
45.3 Module Bigarray.Array2 : Two-dimensional arrays.	157
45.4 Module Bigarray.Array3 : Three-dimensional arrays.	159
46 Module Num : Operation on arbitrary-precision numbers.	161

1 Module Arg : Parsing of command line arguments.

This module provides a general mechanism for extracting options and arguments from the command line to the program.

Syntax of command lines: A keyword is a character string starting with a `-`. An option is a keyword alone or followed by an argument. The types of keywords are: `Unit`, `Bool`, `Set`, `Clear`, `String`, `Set_string`, `Int`, `Set_int`, `Float`, `Set_float`, `Tuple`, `Symbol`, and `Rest`. `Unit`, `Set` and `Clear` keywords take no argument. A `Rest` keyword takes the remaining of the command line as arguments. Every other keyword takes the following word on the command line as argument. Arguments not preceded by a keyword are called anonymous arguments.

Examples (`cmd` is assumed to be the command name):

- `cmd -flag` (a unit option)
- `cmd -int 1` (an int option with argument 1)
- `cmd -string foobar` (a string option with argument "foobar")
- `cmd -float 12.34` (a float option with argument 12.34)
- `cmd a b c` (three anonymous arguments: "a", "b", and "c")
- `cmd a b - c d` (two anonymous arguments and a rest option with two arguments)

```
type spec =
| Unit of (unit -> unit)
    Call the function with unit argument
| Bool of (bool -> unit)
    Call the function with a bool argument
| Set of bool Pervasives.ref
    Set the reference to true
| Clear of bool Pervasives.ref
    Set the reference to false
| String of (string -> unit)
    Call the function with a string argument
| Set_string of string Pervasives.ref
    Set the reference to the string argument
| Int of (int -> unit)
    Call the function with an int argument
| Set_int of int Pervasives.ref
    Set the reference to the int argument
| Float of (float -> unit)
    Call the function with a float argument
| Set_float of float Pervasives.ref
    Set the reference to the float argument
```

| Tuple of spec list

Take several arguments according to the spec list

| Symbol of (string list * (string -> unit))

Take one of the symbols as argument and call the function with the symbol

| Rest of (string -> unit)

Stop interpreting keywords and call the function with each remaining argument

The concrete type describing the behavior associated with a keyword.

```
type key = string
```

```
type doc = string
```

```
type usage_msg = string
```

```
type anon_fun = string -> unit
```

```
val parse : (key * spec * doc) list -> anon_fun -> usage_msg -> unit
```

`Arg.parse speclist anon_fun usage_msg` parses the command line. `speclist` is a list of triples (`key`, `spec`, `doc`). `key` is the option keyword, it must start with a '-' character. `spec` gives the option type and the function to call when this option is found on the command line. `doc` is a one-line description of this option. `anon_fun` is called on anonymous arguments. The functions in `spec` and `anon_fun` are called in the same order as their arguments appear on the command line.

If an error occurs, `Arg.parse` exits the program, after printing an error message as follows:

- The reason for the error: unknown option, invalid or missing argument, etc.
- `usage_msg`
- The list of options, each followed by the corresponding `doc` string.

For the user to be able to specify anonymous arguments starting with a -, include for example `("-", String anon_fun, doc)` in `speclist`.

By default, `parse` recognizes two unit options, `-help` and `-help`, which will display `usage_msg` and the list of options, and exit the program. You can override this behaviour by specifying your own `-help` and `-help` options in `speclist`.

```
val parse_argv :
```

```
  ?current:int Pervasives.ref ->
```

```
string array ->
```

```
(key * spec * doc) list -> anon_fun -> usage_msg -> unit
```

`Arg.parse_argv ~current args speclist anon_fun usage_msg` parses the array `args` as if it were the command line. It uses and updates the value of `~current` (if given), or `Arg.current`. You must set it before calling `parse_argv`. The initial value of `current` is the index of the program name (argument 0) in the array. If an error occurs, `Arg.parse_argv` raises `Arg.Bad` with the error message as argument. If option `-help` or `-help` is given, `Arg.parse_argv` raises `Arg.Help` with the help message as argument.

```
exception Help of string
```

Raised by `Arg.parse_argv` when the user asks for help.

exception Bad of string

Functions in `spec` or `anon_fun` can raise `Arg.Bad` with an error message to reject invalid arguments. `Arg.Bad` is also raised by `Arg.parse_argv` in case of an error.

val usage : (key * spec * doc) list -> usage_msg -> unit

`Arg.usage speclist usage_msg` prints an error message including the list of valid options. This is the same message that `Arg.parse[1]` prints in case of error. `speclist` and `usage_msg` are the same as for `Arg.parse`.

val current : int Pervasives.ref

Position (in `Sys.argv[41]`) of the argument being processed. You can change this value, e.g. to force `Arg.parse[1]` to skip some arguments. `Arg.parse[1]` uses the initial value of `Arg.current[1]` as the index of argument 0 (the program name) and starts parsing arguments at the next element.

2 Module Array : Array operations.

val length : 'a array -> int

Return the length (number of elements) of the given array.

val get : 'a array -> int -> 'a

`Array.get a n` returns the element number `n` of array `a`. The first element has number 0. The last element has number `Array.length a - 1`.

Raise `Invalid_argument "Array.get"` if `n` is outside the range 0 to `(Array.length a - 1)`. You can also write `a.(n)` instead of `Array.get a n`.

val set : 'a array -> int -> 'a -> unit

`Array.set a n x` modifies array `a` in place, replacing element number `n` with `x`.

Raise `Invalid_argument "Array.set"` if `n` is outside the range 0 to `Array.length a - 1`. You can also write `a.(n) <- x` instead of `Array.set a n x`.

val make : int -> 'a -> 'a array

`Array.make n x` returns a fresh array of length `n`, initialized with `x`. All the elements of this new array are initially physically equal to `x` (in the sense of the `==` predicate). Consequently, if `x` is mutable, it is shared among all elements of the array, and modifying `x` through one of the array entries will modify all other entries at the same time.

Raise `Invalid_argument` if `n < 0` or `n > Sys.max_array_length`. If the value of `x` is a floating-point number, then the maximum size is only `Sys.max_array_length / 2`.

val create : int -> 'a -> 'a array

Deprecated. `Array.create` is an alias for `Array.make[2]`.

`val init : int -> (int -> 'a) -> 'a array`

`Array.init n f` returns a fresh array of length `n`, with element number `i` initialized to the result of `f i`. In other terms, `Array.init n f` tabulates the results of `f` applied to the integers 0 to `n-1`.

Raise `Invalid_argument` if `n < 0` or `n > Sys.max_array_length`. If the return type of `f` is `float`, then the maximum size is only `Sys.max_array_length / 2`.

`val make_matrix : int -> int -> 'a -> 'a array array`

`Array.make_matrix dimx dimy e` returns a two-dimensional array (an array of arrays) with first dimension `dimx` and second dimension `dimy`. All the elements of this new matrix are initially physically equal to `e`. The element `(x,y)` of a matrix `m` is accessed with the notation `m.(x).(y)`.

Raise `Invalid_argument` if `dimx` or `dimy` is negative or greater than `Sys.max_array_length`. If the value of `e` is a floating-point number, then the maximum size is only `Sys.max_array_length / 2`.

`val create_matrix : int -> int -> 'a -> 'a array array`

Deprecated. `Array.create_matrix` is an alias for `Array.make_matrix[2]`.

`val append : 'a array -> 'a array -> 'a array`

`Array.append v1 v2` returns a fresh array containing the concatenation of the arrays `v1` and `v2`.

`val concat : 'a array list -> 'a array`

Same as `Array.append`, but concatenates a list of arrays.

`val sub : 'a array -> int -> int -> 'a array`

`Array.sub a start len` returns a fresh array of length `len`, containing the elements number `start` to `start + len - 1` of array `a`.

Raise `Invalid_argument "Array.sub"` if `start` and `len` do not designate a valid subarray of `a`; that is, if `start < 0`, or `len < 0`, or `start + len > Array.length a`.

`val copy : 'a array -> 'a array`

`Array.copy a` returns a copy of `a`, that is, a fresh array containing the same elements as `a`.

`val fill : 'a array -> int -> int -> 'a -> unit`

`Array.fill a ofs len x` modifies the array `a` in place, storing `x` in elements number `ofs` to `ofs + len - 1`.

Raise `Invalid_argument "Array.fill"` if `ofs` and `len` do not designate a valid subarray of `a`.

`val blit : 'a array -> int -> 'a array -> int -> int -> unit`

`Array.blit v1 o1 v2 o2 len` copies `len` elements from array `v1`, starting at element number `o1`, to array `v2`, starting at element number `o2`. It works correctly even if `v1` and `v2` are the same array, and the source and destination chunks overlap.

Raise `Invalid_argument "Array.blit"` if `o1` and `len` do not designate a valid subarray of `v1`, or if `o2` and `len` do not designate a valid subarray of `v2`.

`val to_list : 'a array -> 'a list`

`Array.to_list a` returns the list of all the elements of `a`.

`val of_list : 'a list -> 'a array`

`Array.of_list l` returns a fresh array containing the elements of `l`.

`val iter : ('a -> unit) -> 'a array -> unit`

`Array.iter f a` applies function `f` in turn to all the elements of `a`. It is equivalent to `f a.(0); f a.(1); ...; f a.(Array.length a - 1); ()`.

`val map : ('a -> 'b) -> 'a array -> 'b array`

`Array.map f a` applies function `f` to all the elements of `a`, and builds an array with the results returned by `f`: `[| f a.(0); f a.(1); ...; f a.(Array.length a - 1) |]`.

`val iteri : (int -> 'a -> unit) -> 'a array -> unit`

Same as `Array.iter[2]`, but the function is applied to the index of the element as first argument, and the element itself as second argument.

`val mapi : (int -> 'a -> 'b) -> 'a array -> 'b array`

Same as `Array.map[2]`, but the function is applied to the index of the element as first argument, and the element itself as second argument.

`val fold_left : ('a -> 'b -> 'a) -> 'a -> 'b array -> 'a`

`Array.fold_left f x a` computes `f (... (f (f x a.(0)) a.(1)) ...) a.(n-1)`, where `n` is the length of the array `a`.

`val fold_right : ('a -> 'b -> 'b) -> 'a array -> 'b -> 'b`

`Array.fold_right f a x` computes `f a.(0) (f a.(1) (... (f a.(n-1) x) ...))`, where `n` is the length of the array `a`.

Sorting

`val sort : ('a -> 'a -> int) -> 'a array -> unit`

Sort an array in increasing order according to a comparison function. The comparison function must return 0 if its arguments compare as equal, a positive integer if the first is greater, and a negative integer if the first is smaller (see below for a complete specification). For example, `Pervasives.compare[28]` is a suitable comparison function, provided there are no floating-point NaN values in the data. After calling `Array.sort`, the array is sorted in place in increasing order. `Array.sort` is guaranteed to run in constant heap space and (at most) logarithmic stack space.

The current implementation uses Heap Sort. It runs in constant stack space.

Specification of the comparison function: Let `a` be the array and `cmp` the comparison function. The following must be true for all `x`, `y`, `z` in `a` :

- `cmp x y > 0` if and only if `cmp y x < 0`
- if `cmp x y ≥ 0` and `cmp y z ≥ 0` then `cmp x z ≥ 0`

When `Array.sort` returns, `a` contains the same elements as before, reordered in such a way that for all `i` and `j` valid indices of `a` :

- `cmp a.(i) a.(j) ≥ 0` if and only if `i ≥ j`

```
val stable_sort : ('a -> 'a -> int) -> 'a array -> unit
```

Same as `Array.sort[2]`, but the sorting algorithm is stable (i.e. elements that compare equal are kept in their original order) and not guaranteed to run in constant heap space.

The current implementation uses Merge Sort. It uses `n/2` words of heap space, where `n` is the length of the array. It is usually faster than the current implementation of `Array.sort[2]`.

```
val fast_sort : ('a -> 'a -> int) -> 'a array -> unit
```

Same as `Array.sort[2]` or `Array.stable_sort[2]`, whichever is faster on typical input.

3 Module `ArrayLabels` : Array operations.

```
val length : 'a array -> int
```

Return the length (number of elements) of the given array.

```
val get : 'a array -> int -> 'a
```

`Array.get a n` returns the element number `n` of array `a`. The first element has number 0. The last element has number `Array.length a - 1`. Raise `Invalid_argument "Array.get"` if `n` is outside the range 0 to `(Array.length a - 1)`. You can also write `a.(n)` instead of `Array.get a n`.

```
val set : 'a array -> int -> 'a -> unit
```

`Array.set a n x` modifies array `a` in place, replacing element number `n` with `x`.

Raise `Invalid_argument "Array.set"` if `n` is outside the range 0 to `Array.length a - 1`. You can also write `a.(n) <- x` instead of `Array.set a n x`.

```
val make : int -> 'a -> 'a array
```

`Array.make n x` returns a fresh array of length `n`, initialized with `x`. All the elements of this new array are initially physically equal to `x` (in the sense of the `==` predicate). Consequently, if `x` is mutable, it is shared among all elements of the array, and modifying `x` through one of the array entries will modify all other entries at the same time.

Raise `Invalid_argument` if `n < 0` or `n > Sys.max_array_length`. If the value of `x` is a floating-point number, then the maximum size is only `Sys.max_array_length / 2`.

```

val create : int -> 'a -> 'a array
    Deprecated. Array.create is an alias for ArrayLabels.make[3].

val init : int -> f:(int -> 'a) -> 'a array
    Array.init n f returns a fresh array of length n, with element number i initialized to the
    result of f i. In other terms, Array.init n f tabulates the results of f applied to the
    integers 0 to n-1.

val make_matrix : dimx:int -> dimy:int -> 'a -> 'a array array
    Array.make_matrix dimx dimy e returns a two-dimensional array (an array of arrays) with
    first dimension dimx and second dimension dimy. All the elements of this new matrix are
    initially physically equal to e. The element (x,y) of a matrix m is accessed with the notation
    m.(x).(y).

    Raise Invalid_argument if dimx or dimy is less than 1 or greater than
    Sys.max_array_length. If the value of e is a floating-point number, then the maximum size
    is only Sys.max_array_length / 2.

val create_matrix : dimx:int -> dimy:int -> 'a -> 'a array array
    Deprecated. Array.create_matrix is an alias for ArrayLabels.make_matrix[3].

val append : 'a array -> 'a array -> 'a array
    Array.append v1 v2 returns a fresh array containing the concatenation of the arrays v1 and
    v2.

val concat : 'a array list -> 'a array
    Same as Array.append, but concatenates a list of arrays.

val sub : 'a array -> pos:int -> len:int -> 'a array
    Array.sub a start len returns a fresh array of length len, containing the elements
    number start to start + len - 1 of array a.

    Raise Invalid_argument "Array.sub" if start and len do not designate a valid subarray
    of a; that is, if start < 0, or len < 0, or start + len > Array.length a.

val copy : 'a array -> 'a array
    Array.copy a returns a copy of a, that is, a fresh array containing the same elements as a.

val fill : 'a array -> pos:int -> len:int -> 'a -> unit
    Array.fill a ofs len x modifies the array a in place, storing x in elements number ofs to
    ofs + len - 1.

    Raise Invalid_argument "Array.fill" if ofs and len do not designate a valid subarray of
    a.

val blit :
    src:'a array -> src_pos:int -> dst:'a array -> dst_pos:int -> len:int -> unit

```

`Array.blit v1 o1 v2 o2 len` copies `len` elements from array `v1`, starting at element number `o1`, to array `v2`, starting at element number `o2`. It works correctly even if `v1` and `v2` are the same array, and the source and destination chunks overlap.

Raise `Invalid_argument "Array.blit"` if `o1` and `len` do not designate a valid subarray of `v1`, or if `o2` and `len` do not designate a valid subarray of `v2`.

`val to_list : 'a array -> 'a list`

`Array.to_list a` returns the list of all the elements of `a`.

`val of_list : 'a list -> 'a array`

`Array.of_list l` returns a fresh array containing the elements of `l`.

`val iter : f:('a -> unit) -> 'a array -> unit`

`Array.iter f a` applies function `f` in turn to all the elements of `a`. It is equivalent to `f a.(0); f a.(1); ...; f a.(Array.length a - 1); ()`.

`val map : f:('a -> 'b) -> 'a array -> 'b array`

`Array.map f a` applies function `f` to all the elements of `a`, and builds an array with the results returned by `f`: `[| f a.(0); f a.(1); ...; f a.(Array.length a - 1) |]`.

`val iteri : f:(int -> 'a -> unit) -> 'a array -> unit`

Same as `ArrayLabels.iter[3]`, but the function is applied to the index of the element as first argument, and the element itself as second argument.

`val mapi : f:(int -> 'a -> 'b) -> 'a array -> 'b array`

Same as `ArrayLabels.map[3]`, but the function is applied to the index of the element as first argument, and the element itself as second argument.

`val fold_left : f:('a -> 'b -> 'a) -> init:'a -> 'b array -> 'a`

`Array.fold_left f x a` computes `f (... (f (f x a.(0)) a.(1)) ...) a.(n-1)`, where `n` is the length of the array `a`.

`val fold_right : f:('a -> 'b -> 'b) -> 'a array -> init:'b -> 'b`

`Array.fold_right f a x` computes `f a.(0) (f a.(1) (... (f a.(n-1) x) ...))`, where `n` is the length of the array `a`.

Sorting

`val sort : cmp:('a -> 'a -> int) -> 'a array -> unit`

Sort an array in increasing order according to a comparison function. The comparison function must return 0 if its arguments compare as equal, a positive integer if the first is greater, and a negative integer if the first is smaller. For example, the `Pervasives.compare[28]` function is a suitable comparison function. After calling `Array.sort`, the array is sorted in place in increasing order. `Array.sort` is guaranteed to run in constant heap space and logarithmic stack space.

The current implementation uses Heap Sort. It runs in constant stack space.

```
val stable_sort : cmp:('a -> 'a -> int) -> 'a array -> unit
```

Same as `ArrayLabels.sort[3]`, but the sorting algorithm is stable and not guaranteed to use a fixed amount of heap memory. The current implementation is Merge Sort. It uses $n/2$ words of heap space, where n is the length of the array. It is faster than the current implementation of `ArrayLabels.sort[3]`.

```
val fast_sort : cmp:('a -> 'a -> int) -> 'a array -> unit
```

Same as `Array.sort[2]` or `Array.stable_sort[2]`, whichever is faster on typical input.

4 Module Buffer : Extensible string buffers.

This module implements string buffers that automatically expand as necessary. It provides accumulative concatenation of strings in quasi-linear time (instead of quadratic time when strings are concatenated pairwise).

```
type t
```

The abstract type of buffers.

```
val create : int -> t
```

`create n` returns a fresh buffer, initially empty. The n parameter is the initial size of the internal string that holds the buffer contents. That string is automatically reallocated when more than n characters are stored in the buffer, but shrinks back to n characters when `reset` is called. For best performance, n should be of the same order of magnitude as the number of characters that are expected to be stored in the buffer (for instance, 80 for a buffer that holds one output line). Nothing bad will happen if the buffer grows beyond that limit, however. In doubt, take $n = 16$ for instance. If n is not between 1 and `Sys.max_string_length`[41], it will be clipped to that interval.

```
val contents : t -> string
```

Return a copy of the current contents of the buffer. The buffer itself is unchanged.

```
val length : t -> int
```

Return the number of characters currently contained in the buffer.

```
val clear : t -> unit
```

Empty the buffer.

```
val reset : t -> unit
```

Empty the buffer and deallocate the internal string holding the buffer contents, replacing it with the initial internal string of length n that was allocated by `Buffer.create`[4] n . For long-lived buffers that may have grown a lot, `reset` allows faster reclamation of the space used by the buffer.

```
val add_char : t -> char -> unit
```

`add_char b c` appends the character `c` at the end of the buffer `b`.

`val add_string : t -> string -> unit`
`add_string b s` appends the string `s` at the end of the buffer `b`.

`val add_substring : t -> string -> int -> int -> unit`
`add_substring b s ofs len` takes `len` characters from offset `ofs` in string `s` and appends them at the end of the buffer `b`.

`val add_substitute : t -> (string -> string) -> string -> unit`
`add_substitute b f s` appends the string pattern `s` at the end of the buffer `b` with substitution. The substitution process looks for variables into the pattern and substitutes each variable name by its value, as obtained by applying the mapping `f` to the variable name. Inside the string pattern, a variable name immediately follows a non-escaped `$` character and is one of the following:

- a non empty sequence of alphanumeric or `_` characters,
- an arbitrary sequence of characters enclosed by a pair of matching parentheses or curly brackets. An escaped `$` character is a `$` that immediately follows a backslash character; it then stands for a plain `$`. Raise `Not_found` if the closing character of a parenthesized variable cannot be found.

`val add_buffer : t -> t -> unit`
`add_buffer b1 b2` appends the current contents of buffer `b2` at the end of buffer `b1`. `b2` is not modified.

`val add_channel : t -> Pervasives.in_channel -> int -> unit`
`add_channel b ic n` reads exactly `n` character from the input channel `ic` and stores them at the end of buffer `b`. Raise `End_of_file` if the channel contains fewer than `n` characters.

`val output_buffer : Pervasives.out_channel -> t -> unit`
`output_buffer oc b` writes the current contents of buffer `b` on the output channel `oc`.

5 Module Callback : Registering Caml values with the C runtime.

This module allows Caml values to be registered with the C runtime under a symbolic name, so that C code can later call back registered Caml functions, or raise registered Caml exceptions.

`val register : string -> 'a -> unit`
`Callback.register n v` registers the value `v` under the name `n`. C code can later retrieve a handle to `v` by calling `caml_named_value(n)`.

`val register_exception : string -> exn -> unit`

`Callback.register_exception n exn` registers the exception contained in the exception value `exn` under the name `n`. C code can later retrieve a handle to the exception by calling `caml_named_value(n)`. The exception value thus obtained is suitable for passign as first argument to `raise_constant` or `raise_with_arg`.

6 Module `Camlinternal00` : Run-time support for objects and classes.

All functions in this module are for system use only, not for the casual user.

Methods

```
type label
```

```
val new_method : string -> label
```

```
val public_method_label : string -> label
```

Classes

```
type table
```

```
type meth
```

```
type t
```

```
type obj
```

```
val new_variable : table -> string -> int
```

```
val get_variable : table -> string -> int
```

```
val get_method_label : table -> string -> label
```

```
val get_method : table -> label -> meth
```

```
val set_method : table -> label -> meth -> unit
```

```
val narrow : table -> string list -> string list -> string list -> unit
```

```
val widen : table -> unit
```

```
val add_initializer : table -> (obj -> unit) -> unit
```

```
val dummy_table : table
```

```
val create_table : string list -> table
```

```
val init_class : table -> unit
```

Objects

```
val copy : (< .. > as 'a) -> 'a
```

```
val create_object : table -> obj
```

```
val create_object_opt : obj -> table -> obj
```

```
val run_initializers : obj -> table -> unit
```

```
val run_initializers_opt : obj ->
```

```
obj -> table -> obj
```

```
val create_object_and_run_initializers : obj -> table -> obj
```

```
val send : obj -> label -> t
```

Parameters

```

type params = {
  mutable compact_table : bool ;
  mutable copy_parent : bool ;
  mutable clean_when_copying : bool ;
  mutable retry_count : int ;
  mutable bucket_small_size : int ;
}

val params : params
  Statistics

type stats = {
  classes : int ;
  labels : int ;
  methods : int ;
  inst_vars : int ;
  buckets : int ;
  distrib : int array ;
  small_bucket_count : int ;
  small_bucket_max : int ;
}

val stats : unit -> stats
val show_buckets : unit -> unit

```

7 Module Char : Character operations.

```

val code : char -> int
  Return the ASCII code of the argument.

val chr : int -> char
  Return the character with the given ASCII code. Raise Invalid_argument "Char.chr" if
  the argument is outside the range 0–255.

val escaped : char -> string
  Return a string representing the given character, with special characters escaped following
  the lexical conventions of Objective Caml.

val lowercase : char -> char
  Convert the given character to its equivalent lowercase character.

val uppercase : char -> char
  Convert the given character to its equivalent uppercase character.

type t = char
  An alias for the type of characters.

```

```
val compare : t -> t -> int
```

The comparison function for characters, with the same specification as `Pervasives.compare`[28]. Along with the type `t`, this function `compare` allows the module `Char` to be passed as argument to the functors `Set.Make`[34.3] and `Map.Make`[21.3].

8 Module Complex : Complex numbers.

This module provides arithmetic operations on complex numbers. Complex numbers are represented by their real and imaginary parts (cartesian representation). Each part is represented by a double-precision floating-point number (type `float`).

```
type t = {  
  re : float ;  
  im : float ;  
}
```

The type of complex numbers. `re` is the real part and `im` the imaginary part.

```
val zero : t
```

The complex number 0.

```
val one : t
```

The complex number 1.

```
val i : t
```

The complex number `i`.

```
val neg : t -> t
```

Unary negation.

```
val conj : t -> t
```

Conjugate: given the complex `x + i.y`, returns `x - i.y`.

```
val add : t -> t -> t
```

Addition

```
val sub : t -> t -> t
```

Subtraction

```
val mul : t -> t -> t
```

Multiplication

```
val inv : t -> t
```

Multiplicative inverse ($1/z$).


```

val div : t -> t -> t
    Division

val sqrt : t -> t
    Square root. The result  $x + i.y$  is such that  $x > 0$  or  $x = 0$  and  $y \geq 0$ . This function has
    a discontinuity along the negative real axis.

val norm2 : t -> float
    Norm squared: given  $x + i.y$ , returns  $x^2 + y^2$ .

val norm : t -> float
    Norm: given  $x + i.y$ , returns  $\text{sqrt}(x^2 + y^2)$ .

val arg : t -> float
    Argument. The argument of a complex number is the angle in the complex plane between
    the positive real axis and a line passing through zero and the number. This angle ranges
    from  $-\pi$  to  $\pi$ . This function has a discontinuity along the negative real axis.

val polar : float -> float -> t
    polar norm arg returns the complex having norm norm and argument arg.

val exp : t -> t
    Exponentiation. exp z returns  $e$  to the  $z$  power.

val log : t -> t
    Natural logarithm (in base  $e$ ).

val pow : t -> t -> t
    Power function. pow z1 z2 returns  $z1$  to the  $z2$  power.

```

9 Module Digest : MD5 message digest.

This module provides functions to compute 128-bit “digests” of arbitrary-length strings or files. The digests are of cryptographic quality: it is very hard, given a digest, to forge a string having that digest. The algorithm used is MD5.

```

type t = string
    The type of digests: 16-character strings.

val string : string -> t
    Return the digest of the given string.

val substring : string -> int -> int -> t

```

`Digest.substring s ofs len` returns the digest of the substring of `s` starting at character number `ofs` and containing `len` characters.

`val channel : Pervasives.in_channel -> int -> t`

If `len` is nonnegative, `Digest.channel ic len` reads `len` characters from channel `ic` and returns their digest, or raises `End_of_file` if end-of-file is reached before `len` characters are read. If `len` is negative, `Digest.channel ic len` reads all characters from `ic` until end-of-file is reached and return their digest.

`val file : string -> t`

Return the digest of the file whose name is given.

`val output : Pervasives.out_channel -> t -> unit`

Write a digest on the given output channel.

`val input : Pervasives.in_channel -> t`

Read a digest from the given input channel.

`val to_hex : t -> string`

Return the printable hexadecimal representation of the given digest.

10 Module Filename : Operations on file names.

`val current_dir_name : string`

The conventional name for the current directory (e.g. `.` in Unix).

`val parent_dir_name : string`

The conventional name for the parent of the current directory (e.g. `..` in Unix).

`val concat : string -> string -> string`

`concat dir file` returns a file name that designates file `file` in directory `dir`.

`val is_relative : string -> bool`

Return `true` if the file name is relative to the current directory, `false` if it is absolute (i.e. in Unix, starts with `/`).

`val is_implicit : string -> bool`

Return `true` if the file name is relative and does not start with an explicit reference to the current directory (`./` or `../` in Unix), `false` if it starts with an explicit reference to the root directory or the current directory.

`val check_suffix : string -> string -> bool`

`check_suffix name suff` returns `true` if the filename `name` ends with the suffix `suff`.

```
val chop_suffix : string -> string -> string
```

`chop_suffix name suff` removes the suffix `suff` from the filename `name`. The behavior is undefined if `name` does not end with the suffix `suff`.

```
val chop_extension : string -> string
```

Return the given file name without its extension. The extension is the shortest suffix starting with a period, `.xyz` for instance.

Raise `Invalid_argument` if the given name does not contain a period.

```
val basename : string -> string
```

Split a file name into directory name / base file name. `concat (dirname name) (basename name)` returns a file name which is equivalent to `name`. Moreover, after setting the current directory to `dirname name` (with `Sys.chdir[41]`), references to `basename name` (which is a relative file name) designate the same file as `name` before the call to `Sys.chdir[41]`.

```
val dirname : string -> string
```

See `Filename.basename[10]`.

```
val temp_file : string -> string -> string
```

`temp_file prefix suffix` returns the name of a fresh temporary file in the temporary directory. The base name of the temporary file is formed by concatenating `prefix`, then a suitably chosen integer number, then `suffix`. The temporary file is created empty, with permissions `0o600` (readable and writable only by the file owner). The file is guaranteed to be different from any other file that existed when `temp_file` was called. Under Unix, the temporary directory is `/tmp` by default; if set, the value of the environment variable `TMPDIR` is used instead. Under Windows, the name of the temporary directory is the value of the environment variable `TEMP`, or `C:\temp` by default. Under MacOS 9, the name of the temporary directory is given by the environment variable `TempFolder`; if not set, temporary files are created in the current directory.

```
val open_temp_file :
```

`?mode:Pervasives.open_flag list ->`

```
string -> string -> string * Pervasives.out_channel
```

Same as `Filename.temp_file[10]`, but returns both the name of a fresh temporary file, and an output channel opened (atomically) on this file. This function is more secure than `temp_file`: there is no risk that the temporary file will be modified (e.g. replaced by a symbolic link) before the program opens it. The optional argument `mode` is a list of additional flags to control the opening of the file. It can contain one or several of `Open_append`, `Open_binary`, and `Open_text`. The default is `[Open_text]` (open in text mode).

```
val quote : string -> string
```

Return a quoted version of a file name, suitable for use as one argument in a shell command line, escaping all shell meta-characters.

11 Module Format : Pretty printing.

This module implements a pretty-printing facility to format text within “pretty-printing boxes”. The pretty-printer breaks lines at specified break hints, and indents lines according to the box structure.

Warning: the material output by the following functions is delayed in the pretty-printer queue in order to compute the proper line breaking. Hence, you should not mix calls to the printing functions of the basic I/O system with calls to the functions of this module: this could result in some strange output seemingly unrelated with the evaluation order of printing commands.

You may consider this module as providing an extension to the `printf` facility to provide automatic line breaking. The addition of pretty-printing annotations to your regular `printf` formats gives you fancy indentation and line breaks. Pretty-printing annotations are described below in the documentation of the function `Format.fprintf[11]`.

You may also use the explicit box management and printing functions provided by this module. This style is more basic but more verbose than the `fprintf` concise formats.

For instance, the sequence `open_box 0; print_string "x ="; print_space (); print_int 1; close_box ()` that prints `x = 1` within a pretty-printing box, can be abbreviated as `printf "[%s@ %i@]" "x =" 1`, or even shorter `printf "@[x =@ %i@]" 1`.

Rule of thumb for casual users of this library:

- use simple boxes (as obtained by `open_box 0`);
- use simple break hints (as obtained by `print_cut ()` that outputs a simple break hint, or by `print_space ()` that outputs a space indicating a break hint);
- once a box is opened, display its material with basic printing functions (e. g. `print_int` and `print_string`);
- when the material for a box has been printed, call `close_box ()` to close the box;
- at the end of your routine, evaluate `print_newline ()` to close all remaining boxes and flush the pretty-printer.

The behaviour of pretty-printing commands is unspecified if there is no opened pretty-printing box. Each box opened via one of the `open_` functions below must be closed using `close_box` for proper formatting. Otherwise, some of the material printed in the boxes may not be output, or may be formatted incorrectly.

In case of interactive use, the system closes all opened boxes and flushes all pending text (as with the `print_newline` function) after each phrase. Each phrase is therefore executed in the initial state of the pretty-printer.

Boxes

```
val open_box : int -> unit
```

`open_box d` opens a new pretty-printing box with offset `d`. This box is the general purpose pretty-printing box. Material in this box is displayed “horizontal or vertical”: break hints inside the box may lead to a new line, if there is no more room on the line to print the remainder of the box, or if a new line may lead to a new indentation (demonstrating the indentation of the box). When a new line is printed in the box, `d` is added to the current indentation.

`val close_box : unit -> unit`

Closes the most recently opened pretty-printing box.

Formatting functions

`val print_string : string -> unit`

`print_string str` prints `str` in the current box.

`val print_as : int -> string -> unit`

`print_as len str` prints `str` in the current box. The pretty-printer formats `str` as if it were of length `len`.

`val print_int : int -> unit`

Prints an integer in the current box.

`val print_float : float -> unit`

Prints a floating point number in the current box.

`val print_char : char -> unit`

Prints a character in the current box.

`val print_bool : bool -> unit`

Prints a boolean in the current box.

Break hints

`val print_space : unit -> unit`

`print_space ()` is used to separate items (typically to print a space between two words). It indicates that the line may be split at this point. It either prints one space or splits the line. It is equivalent to `print_break 1 0`.

`val print_cut : unit -> unit`

`print_cut ()` is used to mark a good break position. It indicates that the line may be split at this point. It either prints nothing or splits the line. This allows line splitting at the current point, without printing spaces or adding indentation. It is equivalent to `print_break 0 0`.

`val print_break : int -> int -> unit`

Inserts a break hint in a pretty-printing box. `print_break nspaces offset` indicates that the line may be split (a newline character is printed) at this point, if the contents of the current box does not fit on the current line. If the line is split at that point, `offset` is added to the current indentation. If the line is not split, `nspaces` spaces are printed.

`val print_flush : unit -> unit`

Flushes the pretty printer: all opened boxes are closed, and all pending text is displayed.

`val print_newline : unit -> unit`

Equivalent to `print_flush` followed by a new line.

```
val force_newline : unit -> unit
```

Forces a newline in the current box. Not the normal way of pretty-printing, you should prefer break hints.

```
val print_if_newline : unit -> unit
```

Executes the next formatting command if the preceding line has just been split. Otherwise, ignore the next formatting command.

Margin

```
val set_margin : int -> unit
```

`set_margin d` sets the value of the right margin to `d` (in characters): this value is used to detect line overflows that leads to split lines. Nothing happens if `d` is smaller than 2 or bigger than 999999999.

```
val get_margin : unit -> int
```

Returns the position of the right margin.

Maximum indentation limit

```
val set_max_indent : int -> unit
```

`set_max_indent d` sets the value of the maximum indentation limit to `d` (in characters): once this limit is reached, boxes are rejected to the left, if they do not fit on the current line. Nothing happens if `d` is smaller than 2 or bigger than 999999999.

```
val get_max_indent : unit -> int
```

Return the value of the maximum indentation limit (in characters).

Formatting depth: maximum number of boxes allowed before ellipsis

```
val set_max_boxes : int -> unit
```

`set_max_boxes max` sets the maximum number of boxes simultaneously opened. Material inside boxes nested deeper is printed as an ellipsis (more precisely as the text returned by `get_ellipsis_text ()`). Nothing happens if `max` is not greater than 1.

```
val get_max_boxes : unit -> int
```

Returns the maximum number of boxes allowed before ellipsis.

```
val over_max_boxes : unit -> bool
```

Tests if the maximum number of boxes allowed have already been opened.

Advanced formatting

```
val open_hbox : unit -> unit
```

`open_hbox ()` opens a new pretty-printing box. This box is “horizontal”: the line is not split in this box (new lines may still occur inside boxes nested deeper).

`val open_vbox : int -> unit`

`open_vbox d` opens a new pretty-printing box with offset `d`. This box is “vertical”: every break hint inside this box leads to a new line. When a new line is printed in the box, `d` is added to the current indentation.

`val open_hvbox : int -> unit`

`open_hvbox d` opens a new pretty-printing box with offset `d`. This box is “horizontal-vertical”: it behaves as an “horizontal” box if it fits on a single line, otherwise it behaves as a “vertical” box. When a new line is printed in the box, `d` is added to the current indentation.

`val open_hovbox : int -> unit`

`open_hovbox d` opens a new pretty-printing box with offset `d`. This box is “horizontal or vertical”: break hints inside this box may lead to a new line, if there is no more room on the line to print the remainder of the box. When a new line is printed in the box, `d` is added to the current indentation.

Tabulations

`val open_tbox : unit -> unit`

Opens a tabulation box.

`val close_tbox : unit -> unit`

Closes the most recently opened tabulation box.

`val print_tbreak : int -> int -> unit`

Break hint in a tabulation box. `print_tbreak spaces offset` moves the insertion point to the next tabulation (`spaces` being added to this position). Nothing occurs if insertion point is already on a tabulation mark. If there is no next tabulation on the line, then a newline is printed and the insertion point moves to the first tabulation of the box. If a new line is printed, `offset` is added to the current indentation.

`val set_tab : unit -> unit`

Sets a tabulation mark at the current insertion point.

`val print_tab : unit -> unit`

`print_tab ()` is equivalent to `print_tbreak (0,0)`.

Ellipsis

`val set_ellipsis_text : string -> unit`

Set the text of the ellipsis printed when too many boxes are opened (a single dot, `.`, by default).

`val get_ellipsis_text : unit -> string`

Return the text of the ellipsis.

Tags

```
type tag = string
```

Tags are used to decorate printed entities for user's defined purposes, e.g. setting font and giving size indications for a display device, or marking delimitations of semantics entities (e.g. HTML or TeX elements or terminal escape sequences).

By default, those tags do not influence line breaking calculation: the tag "markers" are not considered as part of the printing material that drives line breaking (in other words, the length of those strings is considered as zero for line breaking).

Thus, tag handling is in some sense transparent to pretty-printing and does not interfere with usual pretty-printing. Hence, a single pretty printing routine can output both simple "verbatim" material or richer decorated output depending on the treatment of tags. By default, tags are not active, hence the output is not decorated with tag information. Once `set_tags` is set to `true`, the pretty printer engine honors tags and decorates the output accordingly.

When a tag has been opened (or closed), it is both and successively "printed" and "marked". Printing a tag means calling a formatter specific function with the name of the tag as argument: that "tag printing" function can then print any regular material to the formatter (so that this material is enqueued as usual in the formatter queue for further line-breaking computation). Marking a tag means to output an arbitrary string (the "tag marker"), directly into the output device of the formatter. Hence, the formatter specific "tag marking" function must return the tag marker string associated to its tag argument. Being flushed directly into the output device of the formatter, tag marker strings are not considered as part of the printing material that drives line breaking (in other words, the length of the strings corresponding to tag markers is considered as zero for line breaking). In addition, advanced users may take advantage of the specificity of tag markers to be precisely output when the pretty printer has already decided where to break the lines, and precisely when the queue is flushed into the output device.

In the spirit of HTML tags, the default tag marking functions output tags enclosed in "<" and ">": hence, the opening marker of tag `t` is "<`t`>" and the closing marker "</`t`>".

Default tag printing functions just do nothing.

Tag marking and tag printing functions are user definable and can be set by calling `set_formatter_tag_func`

```
val open_tag : tag -> unit
```

`open_tag t` opens the tag named `t`; the `print_open_tag` function of the formatter is called with `t` as argument; the tag marker `mark_open_tag t` will be flushed into the output device of the formatter.

```
val close_tag : unit -> unit
```

`close_tag ()` closes the most recently opened tag `t`. In addition, the `print_close_tag` function of the formatter is called with `t` as argument. The marker `mark_close_tag t` will be flushed into the output device of the formatter.

```
val set_tags : bool -> unit
```

`set_tags b` turns on or off the treatment of tags (default is off).

```
val set_print_tags : bool -> unit
```

```
val set_mark_tags : bool -> unit
```


`set_print_tags b` turns on or off the printing of tags, while `set_mark_tags b` turns on or off the output of tag markers.

```
val get_print_tags : unit -> bool
```

```
val get_mark_tags : unit -> bool
```

Return the current status of tags printing and tags marking.

Redirecting formatter output

```
val set_formatter_out_channel : Pervasives.out_channel -> unit
```

Redirect the pretty-printer output to the given channel.

```
val set_formatter_output_functions :
```

```
(string -> int -> int -> unit) -> (unit -> unit) -> unit
```

`set_formatter_output_functions out flush` redirects the pretty-printer output to the functions `out` and `flush`.

The `out` function performs the pretty-printer output. It is called with a string `s`, a start position `p`, and a number of characters `n`; it is supposed to output characters `p` to `p + n - 1` of `s`. The `flush` function is called whenever the pretty-printer is flushed using `print_flush` or `print_newline`.

```
val get_formatter_output_functions :
```

```
unit -> (string -> int -> int -> unit) * (unit -> unit)
```

Return the current output functions of the pretty-printer.

Changing the meaning of printing tags

```
type formatter_tag_functions = {  
  mark_open_tag : tag -> string ;  
  mark_close_tag : tag -> string ;  
  print_open_tag : tag -> unit ;  
  print_close_tag : tag -> unit ;  
}
```

The tag handling functions specific to a formatter: **mark** versions are the “tag marking” functions that associate a string marker to a tag in order for the pretty-printing engine to flush those markers as 0 length tokens in the output device of the formatter. **print** versions are the “tag printing” functions that can perform regular printing when a tag is closed or opened.

```
val set_formatter_tag_functions : formatter_tag_functions -> unit
```

`set_formatter_tag_functions tag_funs` changes the meaning of opening and closing tags to use the functions in `tag_funs`.

When opening a tag name `t`, the string `t` is passed to the opening tag marking function (the `mark_open_tag` field of the record `tag_funs`), that must return the opening tag marker for that name. When the next call to `close_tag ()` happens, the tag name `t` is sent back to the closing tag marking function (the `mark_close_tag` field of record `tag_funs`), that must return a closing tag marker for that name.

The `print_` field of the record contains the functions that are called at tag opening and tag closing time, to output regular material in the pretty-printer queue.

```
val get_formatter_tag_functions : unit -> formatter_tag_functions
```

Return the current tag functions of the pretty-printer.

Changing the meaning of pretty printing (indentation, line breaking, and printing material)

```
val set_all_formatter_output_functions :  
  out:(string -> int -> int -> unit) ->  
  flush:(unit -> unit) ->  
  newline:(unit -> unit) -> spaces:(int -> unit) -> unit
```

`set_all_formatter_output_functions out flush outnewline outspace` redirects the pretty-printer output to the functions `out` and `flush` as described in `set_formatter_output_functions`. In addition, the pretty-printer function that outputs a newline is set to the function `outnewline` and the function that outputs indentation spaces is set to the function `outspace`.

This way, you can change the meaning of indentation (which can be something else than just printing space characters) and the meaning of new lines opening (which can be connected to any other action needed by the application at hand). The two functions `outspace` and `outnewline` are normally connected to `out` and `flush`: respective default values for `outspace` and `outnewline` are `out (String.make n ' ') 0 n` and `out "\n" 0 1`.

```
val get_all_formatter_output_functions :  
  unit ->  
  (string -> int -> int -> unit) * (unit -> unit) * (unit -> unit) *  
  (int -> unit)
```

Return the current output functions of the pretty-printer, including line breaking and indentation functions.

Multiple formatted output

```
type formatter
```

Abstract data type corresponding to a pretty-printer (also called a formatter) and all its machinery. Defining new pretty-printers permits the output of material in parallel on several channels. Parameters of a pretty-printer are local to this pretty-printer: margin, maximum indentation limit, maximum number of boxes simultaneously opened, ellipsis, and so on, are specific to each pretty-printer and may be fixed independently. Given an output channel `oc`, a new formatter writing to that channel is obtained by calling `formatter_of_out_channel oc`. Alternatively, the `make_formatter` function allocates a new formatter with explicit output and flushing functions (convenient to output material to strings for instance).

```
val formatter_of_out_channel : Pervasives.out_channel -> formatter  
  formatter_of_out_channel oc returns a new formatter that writes to the corresponding channel oc.
```

```
val std_formatter : formatter
```

The standard formatter used by the formatting functions above. It is defined as `formatter_of_out_channel stdout`.

`val err_formatter : formatter`

A formatter to use with formatting functions below for output to standard error. It is defined as `formatter_of_out_channel stderr`.

`val formatter_of_buffer : Buffer.t -> formatter`

`formatter_of_buffer b` returns a new formatter writing to buffer `b`. As usual, the formatter has to be flushed at the end of pretty printing, using `pp_print_flush` or `pp_print_newline`, to display all the pending material.

`val stdbuf : Buffer.t`

The string buffer in which `str_formatter` writes.

`val str_formatter : formatter`

A formatter to use with formatting functions below for output to the `stdbuf` string buffer. `str_formatter` is defined as `formatter_of_buffer stdbuf`.

`val flush_str_formatter : unit -> string`

Returns the material printed with `str_formatter`, flushes the formatter and resets the corresponding buffer.

`val make_formatter :`

`(string -> int -> int -> unit) -> (unit -> unit) -> formatter`

`make_formatter out flush` returns a new formatter that writes according to the output function `out`, and the flushing function `flush`. Hence, a formatter to the out channel `oc` is returned by `make_formatter (output oc) (fun () -> flush oc)`.

Basic functions to use with formatters

`val pp_open_hbox : formatter -> unit -> unit`

`val pp_open_vbox : formatter -> int -> unit`

`val pp_open_hvbox : formatter -> int -> unit`

`val pp_open_hovbox : formatter -> int -> unit`

`val pp_open_box : formatter -> int -> unit`

`val pp_close_box : formatter -> unit -> unit`

`val pp_open_tag : formatter -> string -> unit`

`val pp_close_tag : formatter -> unit -> unit`

`val pp_print_string : formatter -> string -> unit`

`val pp_print_as : formatter -> int -> string -> unit`

`val pp_print_int : formatter -> int -> unit`

`val pp_print_float : formatter -> float -> unit`

`val pp_print_char : formatter -> char -> unit`

```

val pp_print_bool : formatter -> bool -> unit
val pp_print_break : formatter -> int -> int -> unit
val pp_print_cut : formatter -> unit -> unit
val pp_print_space : formatter -> unit -> unit
val pp_force_newline : formatter -> unit -> unit
val pp_print_flush : formatter -> unit -> unit
val pp_print_newline : formatter -> unit -> unit
val pp_print_if_newline : formatter -> unit -> unit
val pp_open_tbox : formatter -> unit -> unit
val pp_close_tbox : formatter -> unit -> unit
val pp_print_tbreak : formatter -> int -> int -> unit
val pp_set_tab : formatter -> unit -> unit
val pp_print_tab : formatter -> unit -> unit
val pp_set_tags : formatter -> bool -> unit
val pp_set_print_tags : formatter -> bool -> unit
val pp_set_mark_tags : formatter -> bool -> unit
val pp_get_print_tags : formatter -> unit -> bool
val pp_get_mark_tags : formatter -> unit -> bool
val pp_set_margin : formatter -> int -> unit
val pp_get_margin : formatter -> unit -> int
val pp_set_max_indent : formatter -> int -> unit
val pp_get_max_indent : formatter -> unit -> int
val pp_set_max_boxes : formatter -> int -> unit
val pp_get_max_boxes : formatter -> unit -> int
val pp_over_max_boxes : formatter -> unit -> bool
val pp_set_ellipsis_text : formatter -> string -> unit
val pp_get_ellipsis_text : formatter -> unit -> string
val pp_set_formatter_out_channel :
  formatter -> Pervasives.out_channel -> unit
val pp_set_formatter_output_functions :
  formatter -> (string -> int -> int -> unit) -> (unit -> unit) -> unit
val pp_get_formatter_output_functions :
  formatter -> unit -> (string -> int -> int -> unit) * (unit -> unit)
val pp_set_all_formatter_output_functions :
  formatter ->
  out:(string -> int -> int -> unit) ->
  flush:(unit -> unit) ->
  newline:(unit -> unit) -> spaces:(int -> unit) -> unit
val pp_get_all_formatter_output_functions :

```

```

    formatter ->
unit ->
(string -> int -> int -> unit) * (unit -> unit) * (unit -> unit) *
(int -> unit)
val pp_set_formatter_tag_functions :
    formatter -> formatter_tag_functions -> unit
val pp_get_formatter_tag_functions :
    formatter -> unit -> formatter_tag_functions

```

These functions are the basic ones: usual functions operating on the standard formatter are defined via partial evaluation of these primitives. For instance, `print_string` is equal to `pp_print_string std_formatter`.

`printf` like functions for pretty-printing.

```

val fprintf : formatter -> ('a, formatter, unit) Pervasives.format -> 'a
fprintf ff format arg1 ... argN formats the arguments arg1 to argN according to the
format string format, and outputs the resulting string on the formatter ff. The format is a
character string which contains three types of objects: plain characters and conversion
specifications as specified in the printf module, and pretty-printing indications. The
pretty-printing indication characters are introduced by a @ character, and their meanings are:

```

- @[: open a pretty-printing box. The type and offset of the box may be optionally specified with the following syntax: the < character, followed by an optional box type indication, then an optional integer offset, and the closing > character. Box type is one of `h`, `v`, `hv`, `b`, or `hov`, which stand respectively for an horizontal box, a vertical box, an “horizontal-vertical” box, or an “horizontal or vertical” box (`b` standing for an “horizontal or vertical” box demonstrating indentation and `hov` standing for a regular “horizontal or vertical” box). For instance, `@[<hov 2>` opens an “horizontal or vertical” box with indentation 2 as obtained with `open_hovbox 2`. For more details about boxes, see the various box opening functions `open_*box`.
- @]: close the most recently opened pretty-printing box.
- @,: output a good break as with `print_cut ()`.
- @ : output a space, as with `print_space ()`.
- @\n: force a newline, as with `force_newline ()`.
- @;: output a good break as with `print_break`. The `nspaces` and `offset` parameters of the break may be optionally specified with the following syntax: the < character, followed by an integer `nspaces` value, then an integer offset, and a closing > character.
- @?: flush the pretty printer as with `print_flush ()`. This is equivalent to the conversion `%%$`.
- @.: flush the pretty printer and output a new line, as with `print_newline ()`.
- @<n>: print the following item as if it were of length `n`. Hence, `printf "@<0>%s" arg` is equivalent to `print_as 0 arg`. If `@<n>` is not followed by a conversion specification, then the following character of the format is printed as if it were of length `n`.

- `@{`: open a tag. The name of the tag may be optionally specified with the following syntax: the `<` character, followed by an optional string specification, and the closing `>` character. The string specification is any character string that does not contain the closing character `'>'`. If omitted, the tag name defaults to the empty string. For more details about tags, see the functions `open_tag` and `close_tag`.
- `@}`: close the most recently opened tag.
- `@@`: print a plain `@` character.

Example: `printf "@[%s@ %d@]" "x =" 1` is equivalent to `open_box (); print_string "x ="; print_space (); print_int 1; close_box ()`. It prints `x = 1` within a pretty-printing box.

`val printf : ('a, formatter, unit) Pervasives.format -> 'a`

Same as `fprintf` above, but output on `std_formatter`.

`val fprintf : ('a, formatter, unit) Pervasives.format -> 'a`

Same as `fprintf` above, but output on `err_formatter`.

`val sprintf : ('a, unit, string) Pervasives.format -> 'a`

Same as `printf` above, but instead of printing on a formatter, returns a string containing the result of formatting the arguments. Note that the pretty-printer queue is flushed at the end of each call to `sprintf`.

In case of multiple and related calls to `sprintf` to output material on a single string, you should consider using `fprintf` with a formatter writing to a buffer: flushing the buffer at the end of pretty-printing returns the desired string. You can also use the predefined formatter `str_formatter` and call `flush_str_formatter ()` to get the result.

`val bprintf : Buffer.t -> ('a, formatter, unit) Pervasives.format -> 'a`

Same as `sprintf` above, but instead of printing on a string, writes into the given extensible buffer. As for `sprintf`, the pretty-printer queue is flushed at the end of each call to `bprintf`.

In case of multiple and related calls to `bprintf` to output material on the same buffer `b`, you should consider using `fprintf` with a formatter writing to the buffer `b` (as obtained by `formatter_of_buffer b`), otherwise the repeated flushes of the pretty-printer queue would result in unexpected and badly formatted output.

`val kprintf : (string -> 'a) -> ('b, unit, string, 'a) format4 -> 'b`

Same as `sprintf` above, but instead of returning the string, passes it to the first argument.

12 Module Gc : Memory management control and statistics; finalised values.

```
type stat = {
  minor_words : float ;
```

Number of words allocated in the minor heap since the program was started. This number is accurate in byte-code programs, but only an approximation in programs compiled to native code.

`promoted_words : float ;`

Number of words allocated in the minor heap that survived a minor collection and were moved to the major heap since the program was started.

`major_words : float ;`

Number of words allocated in the major heap, including the promoted words, since the program was started.

`minor_collections : int ;`

Number of minor collections since the program was started.

`major_collections : int ;`

Number of major collection cycles completed since the program was started.

`heap_words : int ;`

Total size of the major heap, in words.

`heap_chunks : int ;`

Number of contiguous pieces of memory that make up the major heap.

`live_words : int ;`

Number of words of live data in the major heap, including the header words.

`live_blocks : int ;`

Number of live blocks in the major heap.

`free_words : int ;`

Number of words in the free list.

`free_blocks : int ;`

Number of blocks in the free list.

`largest_free : int ;`

Size (in words) of the largest block in the free list.

`fragments : int ;`

Number of wasted words due to fragmentation. These are 1-words free blocks placed between two live blocks. They are not available for allocation.

`compactions : int ;`

Number of heap compactions since the program was started.

`top_heap_words : int ;`

Maximum size reached by the major heap, in words.

}

The memory management counters are returned in a **stat** record.

The total amount of memory allocated by the program since it was started is (in words) **minor_words + major_words - promoted_words**. Multiply by the word size (4 on a 32-bit machine, 8 on a 64-bit machine) to get the number of bytes.

```
type control = {
  mutable minor_heap_size : int ;
    The size (in words) of the minor heap. Changing this parameter will trigger a minor
    collection. Default: 32k.

  mutable major_heap_increment : int ;
    The minimum number of words to add to the major heap when increasing it. Default:
    62k.

  mutable space_overhead : int ;
    The major GC speed is computed from this parameter. This is the memory that will
    be "wasted" because the GC does not immediatly collect unreachable blocks. It is
    expressed as a percentage of the memory used for live data. The GC will work more
    (use more CPU time and collect blocks more eagerly) if space_overhead is smaller.
    Default: 80.

  mutable verbose : int ;
    This value controls the GC messages on standard error output. It is a sum of some of
    the following flags, to print messages on the corresponding events:

    • 0x001 Start of major GC cycle.
    • 0x002 Minor collection and major GC slice.
    • 0x004 Growing and shrinking of the heap.
    • 0x008 Resizing of stacks and memory manager tables.
    • 0x010 Heap compaction.
    • 0x020 Change of GC parameters.
    • 0x040 Computation of major GC slice size.
    • 0x080 Calling of finalisation functions.
    • 0x100 Bytecode executable search at start-up.
    • 0x200 Computation of compaction triggering condition. Default: 0.

  mutable max_overhead : int ;
    Heap compaction is triggered when the estimated amount of "wasted" memory is more
    than max_overhead percent of the amount of live data. If max_overhead is set to 0,
    heap compaction is triggered at the end of each major GC cycle (this setting is
    intended for testing purposes only). If max_overhead >= 1000000, compaction is never
    triggered. Default: 500.

  mutable stack_limit : int ;
```


The maximum size of the stack (in words). This is only relevant to the byte-code runtime, as the native code runtime uses the operating system's stack. Default: 256k.

}

The GC parameters are given as a `control` record.

`val stat : unit -> stat`

Return the current values of the memory management counters in a `stat` record.

`val counters : unit -> float * float * float`

Return (`minor_words`, `promoted_words`, `major_words`). Much faster than `stat`.

`val get : unit -> control`

Return the current values of the GC parameters in a `control` record.

`val set : control -> unit`

`set r` changes the GC parameters according to the `control` record `r`. The normal usage is:
`Gc.set { (Gc.get()) with Gc.verbose = 0x00d }`

`val minor : unit -> unit`

Trigger a minor collection.

`val major_slice : int -> int`

Do a minor collection and a slice of major collection. The argument is the size of the slice, 0 to use the automatically-computed slice size. In all cases, the result is the computed slice size.

`val major : unit -> unit`

Do a minor collection and finish the current major collection cycle.

`val full_major : unit -> unit`

Do a minor collection, finish the current major collection cycle, and perform a complete new cycle. This will collect all currently unreachable blocks.

`val compact : unit -> unit`

Perform a full major collection and compact the heap. Note that heap compaction is a lengthy operation.

`val print_stat : Pervasives.out_channel -> unit`

Print the current values of the memory management counters (in human-readable form) into the channel argument.

`val allocated_bytes : unit -> float`

Return the total number of bytes allocated since the program was started. It is returned as a `float` to avoid overflow problems with `int` on 32-bit machines.

```
val finalise : ('a -> unit) -> 'a -> unit
```

`finalise f v` registers `f` as a finalisation function for `v`. `v` must be heap-allocated. `f` will be called with `v` as argument at some point between the first time `v` becomes unreachable and the time `v` is collected by the GC. Several functions can be registered for the same value, or even several instances of the same function. Each instance will be called once (or never, if the program terminates before `v` becomes unreachable).

A number of pitfalls are associated with finalised values: finalisation functions are called asynchronously, sometimes even during the execution of other finalisation functions. In a multithreaded program, finalisation functions are called from any thread, thus they must not acquire any mutex.

Anything reachable from the closure of finalisation functions is considered reachable, so the following code will not work as expected:

```
• let v = ... in Gc.finalise (fun x -> ...) v
```

Instead you should write:

```
• let f = fun x -> ... ;; let v = ... in Gc.finalise f v
```

The `f` function can use all features of O'Caml, including assignments that make the value reachable again. It can also loop forever (in this case, the other finalisation functions will be called during the execution of `f`). It can call `finalise` on `v` or other values to register other functions or even itself. It can raise an exception; in this case the exception will interrupt whatever the program was doing when the function was called.

`finalise` will raise `Invalid_argument` if `v` is not heap-allocated. Some examples of values that are not heap-allocated are integers, constant constructors, booleans, the empty array, the empty list, the unit value. The exact list of what is heap-allocated or not is implementation-dependent. Some constant values can be heap-allocated but never deallocated during the lifetime of the program, for example a list of integer constants; this is also implementation-dependent. You should also be aware that compiler optimisations may duplicate some immutable values, for example floating-point numbers when stored into arrays, so they can be finalised and collected while another copy is still in use by the program.

The results of calling `String.make`[39], `String.create`[39], `Array.make`[2], and `Pervasives.ref`[28] are guaranteed to be heap-allocated and non-constant except when the length argument is 0.

```
type alarm
```

An alarm is a piece of data that calls a user function at the end of each major GC cycle. The following functions are provided to create and delete alarms.

```
val create_alarm : (unit -> unit) -> alarm
```

`create_alarm f` will arrange for `f` to be called at the end of each major GC cycle, starting with the current cycle or the next one. A value of type `alarm` is returned that you can use to call `delete_alarm`.

```
val delete_alarm : alarm -> unit
```

`delete_alarm a` will stop the calls to the function associated to `a`. Calling `delete_alarm a` again has no effect.

13 Module Genlex : A generic lexical analyzer.

This module implements a simple “standard” lexical analyzer, presented as a function from character streams to token streams. It implements roughly the lexical conventions of Caml, but is parameterized by the set of keywords of your language.

Example: a lexer suitable for a desk calculator is obtained by

```
let lexer = make_lexer ["+"; "-"; "*"; "/"; "let"; "="; "("; ")"]
```

The associated parser would be a function from `token stream` to, for instance, `int`, and would have rules such as:

```
let parse_expr = parser
  [< 'Int n >] -> n
  | [< 'Kwd "("; n = parse_expr; 'Kwd ")" >] -> n
  | [< n1 = parse_expr; n2 = parse_remainder n1 >] -> n2
and parse_remainder n1 = parser
  [< 'Kwd "+"; n2 = parse_expr >] -> n1+n2
  | ...
```

```
type token =
| Kwd of string
| Ident of string
| Int of int
| Float of float
| String of string
| Char of char
```

The type of tokens. The lexical classes are: `Int` and `Float` for integer and floating-point numbers; `String` for string literals, enclosed in double quotes; `Char` for character literals, enclosed in single quotes; `Ident` for identifiers (either sequences of letters, digits, underscores and quotes, or sequences of “operator characters” such as `+`, `*`, etc); and `Kwd` for keywords (either identifiers or single “special characters” such as `(`, `}`, etc).

```
val make_lexer : string list -> char Stream.t -> token Stream.t
```

Construct the lexer function. The first argument is the list of keywords. An identifier `s` is returned as `Kwd s` if `s` belongs to this list, and as `Ident s` otherwise. A special character `s` is returned as `Kwd s` if `s` belongs to this list, and cause a lexical error (exception `Parse_error`) otherwise. Blanks and newlines are skipped. Comments delimited by `(*` and `*)` are skipped as well, and can be nested.

14 Module Hashtbl : Hash tables and hash functions.

Hash tables are hashed association tables, with in-place modification.

Generic interface

`type ('a, 'b) t`

The type of hash tables from type 'a to type 'b.

`val create : int -> ('a, 'b) t`

`Hashtbl.create n` creates a new, empty hash table, with initial size `n`. For best results, `n` should be on the order of the expected number of elements that will be in the table. The table grows as needed, so `n` is just an initial guess.

`val clear : ('a, 'b) t -> unit`

Empty a hash table.

`val add : ('a, 'b) t -> 'a -> 'b -> unit`

`Hashtbl.add tbl x y` adds a binding of `x` to `y` in table `tbl`. Previous bindings for `x` are not removed, but simply hidden. That is, after performing `Hashtbl.remove[14] tbl x`, the previous binding for `x`, if any, is restored. (Same behavior as with association lists.)

`val copy : ('a, 'b) t -> ('a, 'b) t`

Return a copy of the given hashtable.

`val find : ('a, 'b) t -> 'a -> 'b`

`Hashtbl.find tbl x` returns the current binding of `x` in `tbl`, or raises `Not_found` if no such binding exists.

`val find_all : ('a, 'b) t -> 'a -> 'b list`

`Hashtbl.find_all tbl x` returns the list of all data associated with `x` in `tbl`. The current binding is returned first, then the previous bindings, in reverse order of introduction in the table.

`val mem : ('a, 'b) t -> 'a -> bool`

`Hashtbl.mem tbl x` checks if `x` is bound in `tbl`.

`val remove : ('a, 'b) t -> 'a -> unit`

`Hashtbl.remove tbl x` removes the current binding of `x` in `tbl`, restoring the previous binding if it exists. It does nothing if `x` is not bound in `tbl`.

`val replace : ('a, 'b) t -> 'a -> 'b -> unit`

`Hashtbl.replace tbl x y` replaces the current binding of `x` in `tbl` by a binding of `x` to `y`. If `x` is unbound in `tbl`, a binding of `x` to `y` is added to `tbl`. This is functionally equivalent to `Hashtbl.remove[14] tbl x` followed by `Hashtbl.add[14] tbl x y`.

```
val iter : ('a -> 'b -> unit) -> ('a, 'b) t -> unit
```

`Hashtbl.iter f tbl` applies `f` to all bindings in table `tbl`. `f` receives the key as first argument, and the associated value as second argument. Each binding is presented exactly once to `f`. The order in which the bindings are passed to `f` is unspecified. However, if the table contains several bindings for the same key, they are passed to `f` in reverse order of introduction, that is, the most recent binding is passed first.

```
val fold : ('a -> 'b -> 'c -> 'c) -> ('a, 'b) t -> 'c -> 'c
```

`Hashtbl.fold f tbl init` computes `(f kN dN ... (f k1 d1 init) ...)`, where `k1 ... kN` are the keys of all bindings in `tbl`, and `d1 ... dN` are the associated values. Each binding is presented exactly once to `f`. The order in which the bindings are passed to `f` is unspecified. However, if the table contains several bindings for the same key, they are passed to `f` in reverse order of introduction, that is, the most recent binding is passed first.

Functorial interface

```
module type HashedType = sig end
```

[14.1]

```
module type S = sig end
```

[14.2]

```
module Make : functor (H : HashedType) -> sig end
```

[14.3]

The polymorphic hash primitive

```
val hash : 'a -> int
```

`Hashtbl.hash x` associates a positive integer to any value of any type. It is guaranteed that if `x = y`, then `hash x = hash y`. Moreover, `hash` always terminates, even on cyclic structures.

```
val hash_param : int -> int -> 'a -> int
```

`Hashtbl.hash_param n m x` computes a hash value for `x`, with the same properties as for `hash`. The two extra parameters `n` and `m` give more precise control over hashing. Hashing performs a depth-first, right-to-left traversal of the structure `x`, stopping after `n` meaningful nodes were encountered, or `m` nodes, meaningful or not, were encountered. Meaningful nodes are: integers; floating-point numbers; strings; characters; booleans; and constant constructors. Larger values of `m` and `n` means that more nodes are taken into account to compute the final hash value, and therefore collisions are less likely to happen. However, hashing takes longer. The parameters `m` and `n` govern the tradeoff between accuracy and speed.

14.1 Module type `Hashtbl.HashedType` : The input signature of the functor `Hashtbl.Make`[14.3].

```
module type HashedType = sig
```

```
type t
```

The type of the hashtable keys.

```
val equal : t -> t -> bool
```

The equality predicate used to compare keys.

```
val hash : t -> int
```

A hashing function on keys. It must be such that if two keys are equal according to `equal`, then they have identical hash values as computed by `hash`. Examples: suitable (`equal`, `hash`) pairs for arbitrary key types include `(=)`, `Hashtbl.hash[14]` for comparing objects by structure, and `(==)`, `Hashtbl.hash[14]` for comparing objects by addresses (e.g. for mutable or cyclic keys).

```
end
```

14.2 Module type `Hashtbl.S` : The output signature of the functor `Hashtbl.Make`[14.3].

```
module type S = sig
```

```
  type key
```

```
  type 'a t
```

```
  val create : int -> 'a t
```

```
  val clear : 'a t -> unit
```

```
  val copy : 'a t -> 'a t
```

```
  val add : 'a t -> key -> 'a -> unit
```

```
  val remove : 'a t -> key -> unit
```

```
  val find : 'a t -> key -> 'a
```

```
  val find_all : 'a t -> key -> 'a list
```

```
  val replace : 'a t -> key -> 'a -> unit
```

```
  val mem : 'a t -> key -> bool
```

```
  val iter : (key -> 'a -> unit) -> 'a t -> unit
```

```
  val fold : (key -> 'a -> 'b -> 'b) -> 'a t -> 'b -> 'b
```

```
end
```

14.3 Module `Hashtbl.Make` : Functor building an implementation of the hashtable structure.

```
module Make : sig
```

The functor `Hashtbl.Make` returns a structure containing a type `key` of keys and a type `'a t` of hash tables associating data of type `'a` to keys of type `key`. The operations perform similarly to those of the generic interface, but use the hashing and equality functions specified in the functor argument `H` instead of generic equality and hashing.

Parameters:

- `H : Hashtbl.HashedType`

end

15 Module `Int32` : 32-bit integers.

This module provides operations on the type `int32` of signed 32-bit integers. Unlike the built-in `int` type, the type `int32` is guaranteed to be exactly 32-bit wide on all platforms. All arithmetic operations over `int32` are taken modulo 2^{32} .

Performance notice: values of type `int32` occupy more memory space than values of type `int`, and arithmetic operations on `int32` are generally slower than those on `int`. Use `int32` only when the application requires exact 32-bit arithmetic.

`val zero : int32`

The 32-bit integer 0.

`val one : int32`

The 32-bit integer 1.

`val minus_one : int32`

The 32-bit integer -1.

`val neg : int32 -> int32`

Unary negation.

`val add : int32 -> int32 -> int32`

Addition.

`val sub : int32 -> int32 -> int32`

Subtraction.

`val mul : int32 -> int32 -> int32`

Multiplication.

`val div : int32 -> int32 -> int32`

Integer division. Raise `Division_by_zero` if the second argument is zero. This division rounds the real quotient of its arguments towards zero, as specified for `Pervasives.(/)`[28].

`val rem : int32 -> int32 -> int32`

Integer remainder. If `y` is not zero, the result of `Int32.rem x y` satisfies the following properties: `Int32.zero <= Int32.rem x y < Int32.abs y` and `x = Int32.add (Int32.mul (Int32.div x y) y) (Int32.rem x y)`. If `y = 0`, `Int32.rem x y` raises `Division_by_zero`.

```

val succ : int32 -> int32
    Successor. Int32.succ x is Int32.add x Int32.one.

val pred : int32 -> int32
    Predecessor. Int32.pred x is Int32.sub x Int32.one.

val abs : int32 -> int32
    Return the absolute value of its argument.

val max_int : int32
    The greatest representable 32-bit integer,  $2^{31} - 1$ .

val min_int : int32
    The smallest representable 32-bit integer,  $-2^{31}$ .

val logand : int32 -> int32 -> int32
    Bitwise logical and.

val logor : int32 -> int32 -> int32
    Bitwise logical or.

val logxor : int32 -> int32 -> int32
    Bitwise logical exclusive or.

val lognot : int32 -> int32
    Bitwise logical negation

val shift_left : int32 -> int -> int32
    Int32.shift_left x y shifts x to the left by y bits. The result is unspecified if y < 0 or y
    >= 32.

val shift_right : int32 -> int -> int32
    Int32.shift_right x y shifts x to the right by y bits. This is an arithmetic shift: the sign
    bit of x is replicated and inserted in the vacated bits. The result is unspecified if y < 0 or y
    >= 32.

val shift_right_logical : int32 -> int -> int32
    Int32.shift_right_logical x y shifts x to the right by y bits. This is a logical shift:
    zeroes are inserted in the vacated bits regardless of the sign of x. The result is unspecified if
    y < 0 or y >= 32.

val of_int : int -> int32
    Convert the given integer (type int) to a 32-bit integer (type int32).

val to_int : int32 -> int

```


Convert the given 32-bit integer (type `int32`) to an integer (type `int`). On 32-bit platforms, the 32-bit integer is taken modulo 2^{31} , i.e. the high-order bit is lost during the conversion. On 64-bit platforms, the conversion is exact.

```
val of_float : float -> int32
```

Convert the given floating-point number to a 32-bit integer, discarding the fractional part (truncate towards 0). The result of the conversion is undefined if, after truncation, the number is outside the range `[Int32.min_int[15], Int32.max_int[15]]`.

```
val to_float : int32 -> float
```

Convert the given 32-bit integer to a floating-point number.

```
val of_string : string -> int32
```

Convert the given string to a 32-bit integer. The string is read in decimal (by default) or in hexadecimal, octal or binary if the string begins with `0x`, `0o` or `0b` respectively. Raise `Failure "int_of_string"` if the given string is not a valid representation of an integer.

```
val to_string : int32 -> string
```

Return the string representation of its argument, in signed decimal.

```
type t = int32
```

An alias for the type of 32-bit integers.

```
val compare : t -> t -> int
```

The comparison function for 32-bit integers, with the same specification as `Pervasives.compare`[28]. Along with the type `t`, this function `compare` allows the module `Int32` to be passed as argument to the functors `Set.Make`[34.3] and `Map.Make`[21.3].

16 Module `Int64` : 64-bit integers.

This module provides operations on the type `int64` of signed 64-bit integers. Unlike the built-in `int` type, the type `int64` is guaranteed to be exactly 64-bit wide on all platforms. All arithmetic operations over `int64` are taken modulo 2^{64} .

Performance notice: values of type `int64` occupy more memory space than values of type `int`, and arithmetic operations on `int64` are generally slower than those on `int`. Use `int64` only when the application requires exact 64-bit arithmetic.

```
val zero : int64
```

The 64-bit integer 0.

```
val one : int64
```

The 64-bit integer 1.

```
val minus_one : int64
```

The 64-bit integer -1.

```
val neg : int64 -> int64
```

Unary negation.

```
val add : int64 -> int64 -> int64
```

Addition.

```
val sub : int64 -> int64 -> int64
```

Subtraction.

```
val mul : int64 -> int64 -> int64
```

Multiplication.

```
val div : int64 -> int64 -> int64
```

Integer division. Raise `Division_by_zero` if the second argument is zero. This division rounds the real quotient of its arguments towards zero, as specified for `Pervasives.(/)`[28].

```
val rem : int64 -> int64 -> int64
```

Integer remainder. If `y` is not zero, the result of `Int64.rem x y` satisfies the following properties: `Int64.zero <= Int64.rem x y < Int64.abs y` and `x = Int64.add (Int64.mul (Int64.div x y) y) (Int64.rem x y)`. If `y = 0`, `Int64.rem x y` raises `Division_by_zero`.

```
val succ : int64 -> int64
```

Successor. `Int64.succ x` is `Int64.add x Int64.one`.

```
val pred : int64 -> int64
```

Predecessor. `Int64.pred x` is `Int64.sub x Int64.one`.

```
val abs : int64 -> int64
```

Return the absolute value of its argument.

```
val max_int : int64
```

The greatest representable 64-bit integer, $2^{63} - 1$.

```
val min_int : int64
```

The smallest representable 64-bit integer, -2^{63} .

```
val logand : int64 -> int64 -> int64
```

Bitwise logical and.

```
val logor : int64 -> int64 -> int64
```

Bitwise logical or.

```

val logxor : int64 -> int64 -> int64
    Bitwise logical exclusive or.

val lognot : int64 -> int64
    Bitwise logical negation

val shift_left : int64 -> int -> int64
    Int64.shift_left x y shifts x to the left by y bits. The result is unspecified if y < 0 or y
    >= 64.

val shift_right : int64 -> int -> int64
    Int64.shift_right x y shifts x to the right by y bits. This is an arithmetic shift: the sign
    bit of x is replicated and inserted in the vacated bits. The result is unspecified if y < 0 or y
    >= 64.

val shift_right_logical : int64 -> int -> int64
    Int64.shift_right_logical x y shifts x to the right by y bits. This is a logical shift:
    zeroes are inserted in the vacated bits regardless of the sign of x. The result is unspecified if
    y < 0 or y >= 64.

val of_int : int -> int64
    Convert the given integer (type int) to a 64-bit integer (type int64).

val to_int : int64 -> int
    Convert the given 64-bit integer (type int64) to an integer (type int). On 64-bit platforms,
    the 64-bit integer is taken modulo  $2^{63}$ , i.e. the high-order bit is lost during the conversion.
    On 32-bit platforms, the 64-bit integer is taken modulo  $2^{31}$ , i.e. the top 33 bits are lost
    during the conversion.

val of_float : float -> int64
    Convert the given floating-point number to a 64-bit integer, discarding the fractional part
    (truncate towards 0). The result of the conversion is undefined if, after truncation, the
    number is outside the range [Int64.min_int[16], Int64.max_int[16]].

val to_float : int64 -> float
    Convert the given 64-bit integer to a floating-point number.

val of_int32 : int32 -> int64
    Convert the given 32-bit integer (type int32) to a 64-bit integer (type int64).

val to_int32 : int64 -> int32
    Convert the given 64-bit integer (type int64) to a 32-bit integer (type int32). The 64-bit
    integer is taken modulo  $2^{32}$ , i.e. the top 32 bits are lost during the conversion.

val of_nativeint : nativeint -> int64

```

Convert the given native integer (type `nativeint`) to a 64-bit integer (type `int64`).

`val to_nativeint : int64 -> nativeint`

Convert the given 64-bit integer (type `int64`) to a native integer. On 32-bit platforms, the 64-bit integer is taken modulo 2^{32} . On 64-bit platforms, the conversion is exact.

`val of_string : string -> int64`

Convert the given string to a 64-bit integer. The string is read in decimal (by default) or in hexadecimal, octal or binary if the string begins with `0x`, `0o` or `0b` respectively. Raise `Failure "int_of_string"` if the given string is not a valid representation of an integer.

`val to_string : int64 -> string`

Return the string representation of its argument, in decimal.

`val bits_of_float : float -> int64`

Return the internal representation of the given float according to the IEEE 754 floating-point “double format” bit layout. Bit 63 of the result represents the sign of the float; bits 62 to 52 represent the (biased) exponent; bits 51 to 0 represent the mantissa.

`val float_of_bits : int64 -> float`

Return the floating-point number whose internal representation, according to the IEEE 754 floating-point “double format” bit layout, is the given `int64`.

`type t = int64`

An alias for the type of 64-bit integers.

`val compare : t -> t -> int`

The comparison function for 64-bit integers, with the same specification as `Pervasives.compare`[28]. Along with the type `t`, this function `compare` allows the module `Int64` to be passed as argument to the functors `Set.Make`[34.3] and `Map.Make`[21.3].

17 Module Lazy : Deferred computations.

`type 'a t = 'a lazy_t`

A value of type `'a Lazy.t` is a deferred computation, called a suspension, that has a result of type `'a`. The special expression syntax `lazy (expr)` makes a suspension of the computation of `expr`, without computing `expr` itself yet. “Forcing” the suspension will then compute `expr` and return its result.

Note: `lazy_t` is the built-in type constructor used by the compiler for the `lazy` keyword. You should not use it directly. Always use `Lazy.t` instead.

Note: if the program is compiled with the `-rectypes` option, ill-founded recursive definitions of the form `let rec x = lazy x` or `let rec x = lazy(lazy(...(lazy x)))` are accepted

by the type-checker and lead, when forced, to ill-formed values that trigger infinite loops in the garbage collector and other parts of the run-time system. Without the `-rectypes` option, such ill-founded recursive definitions are rejected by the type-checker.

```
exception Undefined
```

```
val force : 'a t -> 'a
```

`force x` forces the suspension `x` and returns its result. If `x` has already been forced, `Lazy.force x` returns the same value again without recomputing it. If it raised an exception, the same exception is raised again. Raise `Undefined` if the forcing of `x` tries to force `x` itself recursively.

```
val force_val : 'a t -> 'a
```

`force_val x` forces the suspension `x` and returns its result. If `x` has already been forced, `force_val x` returns the same value again without recomputing it. Raise `Undefined` if the forcing of `x` tries to force `x` itself recursively. If the computation of `x` raises an exception, it is unspecified whether `force_val x` raises the same exception or `Undefined`.

```
val lazy_from_fun : (unit -> 'a) -> 'a t
```

`lazy_from_fun f` is the same as `lazy (f ())` but slightly more efficient.

```
val lazy_from_val : 'a -> 'a t
```

`lazy_from_val v` returns an already-forced suspension of `v`. This is for special purposes only and should not be confused with `lazy (v)`.

```
val lazy_is_val : 'a t -> bool
```

`lazy_is_val x` returns `true` if `x` has already been forced and did not raise an exception.

18 Module Lexing : The run-time library for lexers generated by ocamllex.

Positions

```
type position = {  
  pos_fname : string ;  
  pos_lnum : int ;  
  pos_bol : int ;  
  pos_cnum : int ;  
}
```

A value of type `position` describes a point in a source file. `pos_fname` is the file name; `pos_lnum` is the line number; `pos_bol` is the offset of the beginning of the line (number of characters between the beginning of the file and the beginning of the line); `pos_cnum` is the offset of the position (number of characters between the beginning of the file and the position).

```
val dummy_pos : position
```

A value of type `position`, guaranteed to be different from any valid position.

Lexer buffers

```
type lexbuf = {  
  refill_buff : lexbuf -> unit ;  
  mutable lex_buffer : string ;  
  mutable lex_buffer_len : int ;  
  mutable lex_abs_pos : int ;  
  mutable lex_start_pos : int ;  
  mutable lex_curr_pos : int ;  
  mutable lex_last_pos : int ;  
  mutable lex_last_action : int ;  
  mutable lex_eof_reached : bool ;  
  mutable lex_mem : int array ;  
  mutable lex_start_p : position ;  
  mutable lex_curr_p : position ;  
}
```

The type of lexer buffers. A lexer buffer is the argument passed to the scanning functions defined by the generated scanners. The lexer buffer holds the current state of the scanner, plus a function to refill the buffer from the input.

Note that the lexing engine will only manage the `pos_cnum` field of `lex_curr_p` by updating it with the number of characters read since the start of the `lexbuf`. For the other fields to be accurate, they must be initialised before the first use of the `lexbuf`, and updated by the lexer actions.

```
val from_channel : Pervasives.in_channel -> lexbuf
```

Create a lexer buffer on the given input channel. `Lexing.from_channel inchan` returns a lexer buffer which reads from the input channel `inchan`, at the current reading position.

```
val from_string : string -> lexbuf
```

Create a lexer buffer which reads from the given string. Reading starts from the first character in the string. An end-of-input condition is generated when the end of the string is reached.

```
val from_function : (string -> int -> int) -> lexbuf
```

Create a lexer buffer with the given function as its reading method. When the scanner needs more characters, it will call the given function, giving it a character string `s` and a character count `n`. The function should put `n` characters or less in `s`, starting at character number 0, and return the number of characters provided. A return value of 0 means end of input.

Functions for lexer semantic actions

The following functions can be called from the semantic actions of lexer definitions (the ML code enclosed in braces that computes the value returned by lexing functions). They give access to the character string matched by the regular expression associated with the semantic action. These

functions must be applied to the argument `lexbuf`, which, in the code generated by `ocamllex`, is bound to the lexer buffer passed to the parsing function.

`val lexeme : lexbuf -> string`

`Lexing.lexeme lexbuf` returns the string matched by the regular expression.

`val lexeme_char : lexbuf -> int -> char`

`Lexing.lexeme_char lexbuf i` returns character number `i` in the matched string.

`val lexeme_start : lexbuf -> int`

`Lexing.lexeme_start lexbuf` returns the offset in the input stream of the first character of the matched string. The first character of the stream has offset 0.

`val lexeme_end : lexbuf -> int`

`Lexing.lexeme_end lexbuf` returns the offset in the input stream of the character following the last character of the matched string. The first character of the stream has offset 0.

`val lexeme_start_p : lexbuf -> position`

Like `lexeme_start`, but return a complete `position` instead of an offset.

`val lexeme_end_p : lexbuf -> position`

Like `lexeme_end`, but return a complete `position` instead of an offset.

Miscellaneous functions

`val flush_input : lexbuf -> unit`

Discard the contents of the buffer and reset the current position to 0. The next use of the `lexbuf` will trigger a refill.

19 Module List : List operations.

Some functions are flagged as not tail-recursive. A tail-recursive function uses constant stack space, while a non-tail-recursive function uses stack space proportional to the length of its list argument, which can be a problem with very long lists. When the function takes several list arguments, an approximate formula giving stack usage (in some unspecified constant unit) is shown in parentheses.

The above considerations can usually be ignored if your lists are not longer than about 10000 elements.

`val length : 'a list -> int`

Return the length (number of elements) of the given list.

`val hd : 'a list -> 'a`

Return the first element of the given list. Raise `Failure "hd"` if the list is empty.

`val tl : 'a list -> 'a list`

Return the given list without its first element. Raise `Failure "tl"` if the list is empty.

```
val nth : 'a list -> int -> 'a
```

Return the *n*-th element of the given list. The first element (head of the list) is at position 0. Raise `Failure "nth"` if the list is too short.

```
val rev : 'a list -> 'a list
```

List reversal.

```
val append : 'a list -> 'a list -> 'a list
```

Catenate two lists. Same function as the infix operator `@`. Not tail-recursive (length of the first argument). The `@` operator is not tail-recursive either.

```
val rev_append : 'a list -> 'a list -> 'a list
```

`List.rev_append l1 l2` reverses `l1` and concatenates it to `l2`. This is equivalent to `List.rev[19] l1 @ l2`, but `rev_append` is tail-recursive and more efficient.

```
val concat : 'a list list -> 'a list
```

Concatenate a list of lists. The elements of the argument are all concatenated together (in the same order) to give the result. Not tail-recursive (length of the argument + length of the longest sub-list).

```
val flatten : 'a list list -> 'a list
```

Same as `concat`. Not tail-recursive (length of the argument + length of the longest sub-list).

Iterators

```
val iter : ('a -> unit) -> 'a list -> unit
```

`List.iter f [a1; ...; an]` applies function `f` in turn to `a1`; ...; `an`. It is equivalent to `begin f a1; f a2; ...; f an; () end`.

```
val map : ('a -> 'b) -> 'a list -> 'b list
```

`List.map f [a1; ...; an]` applies function `f` to `a1`, ..., `an`, and builds the list `[f a1; ...; f an]` with the results returned by `f`. Not tail-recursive.

```
val rev_map : ('a -> 'b) -> 'a list -> 'b list
```

`List.rev_map f l` gives the same result as `List.rev[19] (List.map[19] f l)`, but is tail-recursive and more efficient.

```
val fold_left : ('a -> 'b -> 'a) -> 'a -> 'b list -> 'a
```

`List.fold_left f a [b1; ...; bn]` is `f (... (f (f a b1) b2) ...) bn`.

```
val fold_right : ('a -> 'b -> 'b) -> 'a list -> 'b -> 'b
```

`List.fold_right f [a1; ...; an] b` is `f a1 (f a2 (... (f an b) ...))`. Not tail-recursive.

Iterators on two lists

```
val iter2 : ('a -> 'b -> unit) -> 'a list -> 'b list -> unit
  List.iter2 f [a1; ...; an] [b1; ...; bn] calls in turn f a1 b1; ...; f an bn.
  Raise Invalid_argument if the two lists have different lengths.

val map2 : ('a -> 'b -> 'c) -> 'a list -> 'b list -> 'c list
  List.map2 f [a1; ...; an] [b1; ...; bn] is [f a1 b1; ...; f an bn]. Raise
  Invalid_argument if the two lists have different lengths. Not tail-recursive.

val rev_map2 : ('a -> 'b -> 'c) -> 'a list -> 'b list -> 'c list
  List.rev_map2 f l gives the same result as List.rev[19] (List.map2[19] f l), but is
  tail-recursive and more efficient.

val fold_left2 : ('a -> 'b -> 'c -> 'a) -> 'a -> 'b list -> 'c list -> 'a
  List.fold_left2 f a [b1; ...; bn] [c1; ...; cn] is f (... (f (f a b1 c1) b2
  c2) ...) bn cn. Raise Invalid_argument if the two lists have different lengths.

val fold_right2 : ('a -> 'b -> 'c -> 'c) -> 'a list -> 'b list -> 'c -> 'c
  List.fold_right2 f [a1; ...; an] [b1; ...; bn] c is f a1 b1 (f a2 b2 (... (f
  an bn c) ...)). Raise Invalid_argument if the two lists have different lengths. Not
  tail-recursive.
```

List scanning

```
val for_all : ('a -> bool) -> 'a list -> bool
  for_all p [a1; ...; an] checks if all elements of the list satisfy the predicate p. That is,
  it returns (p a1) && (p a2) && ... && (p an).

val exists : ('a -> bool) -> 'a list -> bool
  exists p [a1; ...; an] checks if at least one element of the list satisfies the predicate p.
  That is, it returns (p a1) || (p a2) || ... || (p an).

val for_all2 : ('a -> 'b -> bool) -> 'a list -> 'b list -> bool
  Same as List.for_all[19], but for a two-argument predicate. Raise Invalid_argument if
  the two lists have different lengths.

val exists2 : ('a -> 'b -> bool) -> 'a list -> 'b list -> bool
  Same as List.exists[19], but for a two-argument predicate. Raise Invalid_argument if the
  two lists have different lengths.

val mem : 'a -> 'a list -> bool
  mem a l is true if and only if a is equal to an element of l.

val memq : 'a -> 'a list -> bool
  Same as List.mem[19], but uses physical equality instead of structural equality to compare
  list elements.
```

List searching

val find : ('a -> bool) -> 'a list -> 'a

find *p* *l* returns the first element of the list *l* that satisfies the predicate *p*. Raise **Not_found** if there is no value that satisfies *p* in the list *l*.

val filter : ('a -> bool) -> 'a list -> 'a list

filter *p* *l* returns all the elements of the list *l* that satisfy the predicate *p*. The order of the elements in the input list is preserved.

val find_all : ('a -> bool) -> 'a list -> 'a list

find_all is another name for **List.filter**[19].

val partition : ('a -> bool) -> 'a list -> 'a list * 'a list

partition *p* *l* returns a pair of lists (*l1*, *l2*), where *l1* is the list of all the elements of *l* that satisfy the predicate *p*, and *l2* is the list of all the elements of *l* that do not satisfy *p*. The order of the elements in the input list is preserved.

Association lists

val assoc : 'a -> ('a * 'b) list -> 'b

assoc *a* *l* returns the value associated with key *a* in the list of pairs *l*. That is, **assoc** *a* [*...*; (*a*,*b*); *...*] = *b* if (*a*,*b*) is the leftmost binding of *a* in list *l*. Raise **Not_found** if there is no value associated with *a* in the list *l*.

val assq : 'a -> ('a * 'b) list -> 'b

Same as **List.assoc**[19], but uses physical equality instead of structural equality to compare keys.

val mem_assoc : 'a -> ('a * 'b) list -> bool

Same as **List.assoc**[19], but simply return true if a binding exists, and false if no bindings exist for the given key.

val mem_assq : 'a -> ('a * 'b) list -> bool

Same as **List.mem_assoc**[19], but uses physical equality instead of structural equality to compare keys.

val remove_assoc : 'a -> ('a * 'b) list -> ('a * 'b) list

remove_assoc *a* *l* returns the list of pairs *l* without the first pair with key *a*, if any. Not tail-recursive.

val remove_assq : 'a -> ('a * 'b) list -> ('a * 'b) list

Same as **List.remove_assoc**[19], but uses physical equality instead of structural equality to compare keys. Not tail-recursive.

Lists of pairs

val split : ('a * 'b) list -> 'a list * 'b list

Transform a list of pairs into a pair of lists: `split [(a1,b1); ...; (an,bn)]` is `([a1; ...; an], [b1; ...; bn])`. Not tail-recursive.

```
val combine : 'a list -> 'b list -> ('a * 'b) list
```

Transform a pair of lists into a list of pairs: `combine [a1; ...; an] [b1; ...; bn]` is `[(a1,b1); ...; (an,bn)]`. Raise `Invalid_argument` if the two lists have different lengths. Not tail-recursive.

Sorting

```
val sort : ('a -> 'a -> int) -> 'a list -> 'a list
```

Sort a list in increasing order according to a comparison function. The comparison function must return 0 if its arguments compare as equal, a positive integer if the first is greater, and a negative integer if the first is smaller (see `Array.sort` for a complete specification). For example, `Pervasives.compare`[28] is a suitable comparison function, provided there are no floating-point NaN values in the data. The resulting list is sorted in increasing order. `List.sort` is guaranteed to run in constant heap space (in addition to the size of the result list) and logarithmic stack space.

The current implementation uses Merge Sort. It runs in constant heap space and logarithmic stack space.

```
val stable_sort : ('a -> 'a -> int) -> 'a list -> 'a list
```

Same as `List.sort`[19], but the sorting algorithm is guaranteed to be stable (i.e. elements that compare equal are kept in their original order) .

The current implementation uses Merge Sort. It runs in constant heap space and logarithmic stack space.

```
val fast_sort : ('a -> 'a -> int) -> 'a list -> 'a list
```

Same as `List.sort`[19] or `List.stable_sort`[19], whichever is faster on typical input.

```
val merge : ('a -> 'a -> int) -> 'a list -> 'a list -> 'a list
```

Merge two lists: Assuming that `l1` and `l2` are sorted according to the comparison function `cmp`, `merge cmp l1 l2` will return a sorted list containing all the elements of `l1` and `l2`. If several elements compare equal, the elements of `l1` will be before the elements of `l2`. Not tail-recursive (sum of the lengths of the arguments).

20 Module `ListLabels` : List operations.

Some functions are flagged as not tail-recursive. A tail-recursive function uses constant stack space, while a non-tail-recursive function uses stack space proportional to the length of its list argument, which can be a problem with very long lists. When the function takes several list arguments, an approximate formula giving stack usage (in some unspecified constant unit) is shown in parentheses.

The above considerations can usually be ignored if your lists are not longer than about 10000 elements.

```
val length : 'a list -> int
```

Return the length (number of elements) of the given list.

```
val hd : 'a list -> 'a
```

Return the first element of the given list. Raise `Failure` "hd" if the list is empty.

```
val tl : 'a list -> 'a list
```

Return the given list without its first element. Raise `Failure` "tl" if the list is empty.

```
val nth : 'a list -> int -> 'a
```

Return the n-th element of the given list. The first element (head of the list) is at position 0. Raise `Failure` "nth" if the list is too short.

```
val rev : 'a list -> 'a list
```

List reversal.

```
val append : 'a list -> 'a list -> 'a list
```

Catenate two lists. Same function as the infix operator `@`. Not tail-recursive (length of the first argument). The `@` operator is not tail-recursive either.

```
val rev_append : 'a list -> 'a list -> 'a list
```

`List.rev_append l1 l2` reverses `l1` and concatenates it to `l2`. This is equivalent to `ListLabels.rev[20] l1 @ l2`, but `rev_append` is tail-recursive and more efficient.

```
val concat : 'a list list -> 'a list
```

Concatenate a list of lists. Not tail-recursive (length of the argument + length of the longest sub-list).

```
val flatten : 'a list list -> 'a list
```

Flatten a list of lists. Not tail-recursive (length of the argument + length of the longest sub-list).

Iterators

```
val iter : f:( 'a -> unit) -> 'a list -> unit
```

`List.iter f [a1; ...; an]` applies function `f` in turn to `a1`; ...; `an`. It is equivalent to `begin f a1; f a2; ...; f an; () end`.

```
val map : f:( 'a -> 'b) -> 'a list -> 'b list
```

`List.map f [a1; ...; an]` applies function `f` to `a1`, ..., `an`, and builds the list `[f a1; ...; f an]` with the results returned by `f`. Not tail-recursive.

```
val rev_map : f:( 'a -> 'b) -> 'a list -> 'b list
```

`List.rev_map f l` gives the same result as `ListLabels.rev[20] (ListLabels.map[20] f l)`, but is tail-recursive and more efficient.

```
val fold_left : f:( 'a -> 'b -> 'a) -> init:'a -> 'b list -> 'a
```

```

List.fold_left f a [b1; ...; bn] is f (... (f (f a b1) b2) ...) bn.

val fold_right : f:(’a -> ’b -> ’b) -> ’a list -> init:’b -> ’b
  List.fold_right f [a1; ...; an] b is f a1 (f a2 (... (f an b) ...)). Not
  tail-recursive.

Iterators on two lists

val iter2 : f:(’a -> ’b -> unit) -> ’a list -> ’b list -> unit
  List.iter2 f [a1; ...; an] [b1; ...; bn] calls in turn f a1 b1; ...; f an bn.
  Raise Invalid_argument if the two lists have different lengths.

val map2 : f:(’a -> ’b -> ’c) -> ’a list -> ’b list -> ’c list
  List.map2 f [a1; ...; an] [b1; ...; bn] is [f a1 b1; ...; f an bn]. Raise
  Invalid_argument if the two lists have different lengths. Not tail-recursive.

val rev_map2 : f:(’a -> ’b -> ’c) -> ’a list -> ’b list -> ’c list
  List.rev_map2 f l gives the same result as ListLabels.rev[20] (ListLabels.map2[20] f
  l), but is tail-recursive and more efficient.

val fold_left2 :
  f:(’a -> ’b -> ’c -> ’a) -> init:’a -> ’b list -> ’c list -> ’a
  List.fold_left2 f a [b1; ...; bn] [c1; ...; cn] is f (... (f (f a b1 c1) b2
  c2) ...) bn cn. Raise Invalid_argument if the two lists have different lengths.

val fold_right2 :
  f:(’a -> ’b -> ’c -> ’c) -> ’a list -> ’b list -> init:’c -> ’c
  List.fold_right2 f [a1; ...; an] [b1; ...; bn] c is f a1 b1 (f a2 b2 (... (f
  an bn c) ...)). Raise Invalid_argument if the two lists have different lengths. Not
  tail-recursive.

List scanning

val for_all : f:(’a -> bool) -> ’a list -> bool
  for_all p [a1; ...; an] checks if all elements of the list satisfy the predicate p. That is,
  it returns (p a1) && (p a2) && ... && (p an).

val exists : f:(’a -> bool) -> ’a list -> bool
  exists p [a1; ...; an] checks if at least one element of the list satisfies the predicate p.
  That is, it returns (p a1) || (p a2) || ... || (p an).

val for_all2 : f:(’a -> ’b -> bool) -> ’a list -> ’b list -> bool
  Same as ListLabels.for_all[20], but for a two-argument predicate. Raise
  Invalid_argument if the two lists have different lengths.

val exists2 : f:(’a -> ’b -> bool) -> ’a list -> ’b list -> bool

```

Same as `ListLabels.exists[20]`, but for a two-argument predicate. Raise `Invalid_argument` if the two lists have different lengths.

```
val mem : 'a -> set:'a list -> bool
```

`mem a l` is true if and only if `a` is equal to an element of `l`.

```
val memq : 'a -> set:'a list -> bool
```

Same as `ListLabels.mem[20]`, but uses physical equality instead of structural equality to compare list elements.

List searching

```
val find : f:( 'a -> bool) -> 'a list -> 'a
```

`find p l` returns the first element of the list `l` that satisfies the predicate `p`. Raise `Not_found` if there is no value that satisfies `p` in the list `l`.

```
val filter : f:( 'a -> bool) -> 'a list -> 'a list
```

`filter p l` returns all the elements of the list `l` that satisfy the predicate `p`. The order of the elements in the input list is preserved.

```
val find_all : f:( 'a -> bool) -> 'a list -> 'a list
```

`find_all` is another name for `ListLabels.filter[20]`.

```
val partition : f:( 'a -> bool) -> 'a list -> 'a list * 'a list
```

`partition p l` returns a pair of lists (`l1`, `l2`), where `l1` is the list of all the elements of `l` that satisfy the predicate `p`, and `l2` is the list of all the elements of `l` that do not satisfy `p`. The order of the elements in the input list is preserved.

Association lists

```
val assoc : 'a -> ('a * 'b) list -> 'b
```

`assoc a l` returns the value associated with key `a` in the list of pairs `l`. That is, `assoc a [...; (a,b); ...] = b` if `(a,b)` is the leftmost binding of `a` in list `l`. Raise `Not_found` if there is no value associated with `a` in the list `l`.

```
val assq : 'a -> ('a * 'b) list -> 'b
```

Same as `ListLabels.assoc[20]`, but uses physical equality instead of structural equality to compare keys.

```
val mem_assoc : 'a -> map:( 'a * 'b) list -> bool
```

Same as `ListLabels.assoc[20]`, but simply return true if a binding exists, and false if no bindings exist for the given key.

```
val mem_assq : 'a -> map:( 'a * 'b) list -> bool
```

Same as `ListLabels.mem_assoc[20]`, but uses physical equality instead of structural equality to compare keys.

val remove_assoc : 'a -> ('a * 'b) list -> ('a * 'b) list

remove_assoc a l returns the list of pairs l without the first pair with key a, if any. Not tail-recursive.

val remove_assq : 'a -> ('a * 'b) list -> ('a * 'b) list

Same as **ListLabels.remove_assq**[20], but uses physical equality instead of structural equality to compare keys. Not tail-recursive.

Lists of pairs

val split : ('a * 'b) list -> 'a list * 'b list

Transform a list of pairs into a pair of lists: **split** [(a1,b1); ...; (an,bn)] is ([a1; ...; an], [b1; ...; bn]). Not tail-recursive.

val combine : 'a list -> 'b list -> ('a * 'b) list

Transform a pair of lists into a list of pairs: **combine** [a1; ...; an] [b1; ...; bn] is [(a1,b1); ...; (an,bn)]. Raise **Invalid_argument** if the two lists have different lengths. Not tail-recursive.

Sorting

val sort : cmp:('a -> 'a -> int) -> 'a list -> 'a list

Sort a list in increasing order according to a comparison function. The comparison function must return 0 if its arguments compare as equal, a positive integer if the first is greater, and a negative integer if the first is smaller. For example, the **compare** function is a suitable comparison function. The resulting list is sorted in increasing order. **List.sort** is guaranteed to run in constant heap space (in addition to the size of the result list) and logarithmic stack space.

The current implementation uses Merge Sort and is the same as **ListLabels.stable_sort**[20].

val stable_sort : cmp:('a -> 'a -> int) -> 'a list -> 'a list

Same as **ListLabels.sort**[20], but the sorting algorithm is stable.

The current implementation is Merge Sort. It runs in constant heap space and logarithmic stack space.

val fast_sort : cmp:('a -> 'a -> int) -> 'a list -> 'a list

Same as **List.sort**[19] or **List.stable_sort**[19], whichever is faster on typical input.

val merge : cmp:('a -> 'a -> int) -> 'a list -> 'a list -> 'a list

Merge two lists: Assuming that l1 and l2 are sorted according to the comparison function **cmp**, **merge cmp l1 l2** will return a sorted list containing all the elements of l1 and l2. If several elements compare equal, the elements of l1 will be before the elements of l2. Not tail-recursive (sum of the lengths of the arguments).

21 Module Map : Association tables over ordered types.

This module implements applicative association tables, also known as finite maps or dictionaries, given a total ordering function over the keys. All operations over maps are purely applicative (no side-effects). The implementation uses balanced binary trees, and therefore searching and insertion take time logarithmic in the size of the map.

```
module type OrderedType = sig end
[21.1]
module type S = sig end
[21.2]
module Make : functor (Ord : OrderedType) -> sig end
[21.3]
```

21.1 Module type Map.OrderedType : Input signature of the functor Map.Make[21.3].

```
module type OrderedType = sig
```

```
  type t
```

The type of the map keys.

```
  val compare : t -> t -> int
```

A total ordering function over the keys. This is a two-argument function `f` such that `f e1 e2` is zero if the keys `e1` and `e2` are equal, `f e1 e2` is strictly negative if `e1` is smaller than `e2`, and `f e1 e2` is strictly positive if `e1` is greater than `e2`. Example: a suitable ordering function is the generic structural comparison function `Pervasives.compare`[28].

```
end
```

21.2 Module type Map.S : Output signature of the functor Map.Make[21.3].

```
module type S = sig
```

```
  type key
```

The type of the map keys.

```
  type +'a t
```

The type of maps from type `key` to type `'a`.

```
  val empty : 'a t
```

The empty map.

```
  val add : key -> 'a -> 'a t -> 'a t
```

`add x y m` returns a map containing the same bindings as `m`, plus a binding of `x` to `y`. If `x` was already bound in `m`, its previous binding disappears.


```

val find : key -> 'a t -> 'a
    find x m returns the current binding of x in m, or raises Not_found if no such binding exists.

val remove : key -> 'a t -> 'a t
    remove x m returns a map containing the same bindings as m, except for x which is unbound
    in the returned map.

val mem : key -> 'a t -> bool
    mem x m returns true if m contains a binding for x, and false otherwise.

val iter : (key -> 'a -> unit) -> 'a t -> unit
    iter f m applies f to all bindings in map m. f receives the key as first argument, and the
    associated value as second argument. The order in which the bindings are passed to f is
    unspecified. Only current bindings are presented to f: bindings hidden by more recent
    bindings are not passed to f.

val map : ('a -> 'b) -> 'a t -> 'b t
    map f m returns a map with same domain as m, where the associated value a of all bindings
    of m has been replaced by the result of the application of f to a. The order in which the
    associated values are passed to f is unspecified.

val mapi : (key -> 'a -> 'b) -> 'a t -> 'b t
    Same as Map.S.map[21.2], but the function receives as arguments both the key and the
    associated value for each binding of the map.

val fold : (key -> 'a -> 'b -> 'b) -> 'a t -> 'b -> 'b
    fold f m a computes (f kN dN ... (f k1 d1 a)...), where k1 ... kN are the keys of
    all bindings in m, and d1 ... dN are the associated data. The order in which the bindings
    are presented to f is unspecified.

end

```

21.3 Module `Map.Make` : Functor building an implementation of the map structure given a totally ordered type.

```

module Make : sig
  Parameters:
    • Ord : Map.OrderedType
end

```

22 Module Marshal : Marshaling of data structures.

This module provides functions to encode arbitrary data structures as sequences of bytes, which can then be written on a file or sent over a pipe or network connection. The bytes can then be read back later, possibly in another process, and decoded back into a data structure. The format for the byte sequences is compatible across all machines for a given version of Objective Caml.

Warning: marshaling is currently not type-safe. The type of marshaled data is not transmitted along the value of the data, making it impossible to check that the data read back possesses the type expected by the context. In particular, the result type of the `Marshal.from_*` functions is given as `'a`, but this is misleading: the returned Caml value does not possess type `'a` for all `'a`; it has one, unique type which cannot be determined at compile-time. The programmer should explicitly give the expected type of the returned value, using the following syntax:

- (`Marshal.from_channel chan : type`). Anything can happen at run-time if the object in the file does not belong to the given type.

The representation of marshaled values is not human-readable, and uses bytes that are not printable characters. Therefore, input and output channels used in conjunction with `Marshal.to_channel` and `Marshal.from_channel` must be opened in binary mode, using e.g. `open_out_bin` or `open_in_bin`; channels opened in text mode will cause unmarshaling errors on platforms where text channels behave differently than binary channels, e.g. Windows.

```
type extern_flags =  
  | No_sharing  
    Don't preserve sharing  
  | Closures  
    Send function closures  
The flags to the Marshal.to_* functions below.
```

```
val to_channel : Pervasives.out_channel -> 'a -> extern_flags list -> unit
```

`Marshal.to_channel chan v flags` writes the representation of `v` on channel `chan`. The `flags` argument is a possibly empty list of flags that governs the marshaling behavior with respect to sharing and functional values.

If `flags` does not contain `Marshal.No_sharing`, circularities and sharing inside the value `v` are detected and preserved in the sequence of bytes produced. In particular, this guarantees that marshaling always terminates. Sharing between values marshaled by successive calls to `Marshal.to_channel` is not detected, though. If `flags` contains `Marshal.No_sharing`, sharing is ignored. This results in faster marshaling if `v` contains no shared substructures, but may cause slower marshaling and larger byte representations if `v` actually contains sharing, or even non-termination if `v` contains cycles.

If `flags` does not contain `Marshal.Closures`, marshaling fails when it encounters a functional value inside `v`: only “pure” data structures, containing neither functions nor objects, can safely be transmitted between different programs. If `flags` contains `Marshal.Closures`, functional values will be marshaled as a position in the code of the program. In this case, the output of marshaling can only be read back in processes that run

exactly the same program, with exactly the same compiled code. (This is checked at un-marshaling time, using an MD5 digest of the code transmitted along with the code position.)

```
val to_string : 'a -> extern_flags list -> string
```

`Marshal.to_string v flags` returns a string containing the representation of `v` as a sequence of bytes. The `flags` argument has the same meaning as for `Marshal.to_channel[22]`.

```
val to_buffer : string -> int -> int -> 'a -> extern_flags list -> int
```

`Marshal.to_buffer buff ofs len v flags` marshals the value `v`, storing its byte representation in the string `buff`, starting at character number `ofs`, and writing at most `len` characters. It returns the number of characters actually written to the string. If the byte representation of `v` does not fit in `len` characters, the exception `Failure` is raised.

```
val from_channel : Pervasives.in_channel -> 'a
```

`Marshal.from_channel chan` reads from channel `chan` the byte representation of a structured value, as produced by one of the `Marshal.to_*` functions, and reconstructs and returns the corresponding value.

```
val from_string : string -> int -> 'a
```

`Marshal.from_string buff ofs` unmarshals a structured value like `Marshal.from_channel[22]` does, except that the byte representation is not read from a channel, but taken from the string `buff`, starting at position `ofs`.

```
val header_size : int
```

The bytes representing a marshaled value are composed of a fixed-size header and a variable-sized data part, whose size can be determined from the header.

`Marshal.header_size[22]` is the size, in characters, of the header. `Marshal.data_size[22] buff ofs` is the size, in characters, of the data part, assuming a valid header is stored in `buff` starting at position `ofs`. Finally, `Marshal.total_size[22] buff ofs` is the total size, in characters, of the marshaled value. Both `Marshal.data_size[22]` and `Marshal.total_size[22]` raise `Failure` if `buff, ofs` does not contain a valid header.

To read the byte representation of a marshaled value into a string buffer, the program needs to read first `Marshal.header_size[22]` characters into the buffer, then determine the length of the remainder of the representation using `Marshal.data_size[22]`, make sure the buffer is large enough to hold the remaining data, then read it, and finally call `Marshal.from_string[22]` to unmarshal the value.

```
val data_size : string -> int -> int
```

See `Marshal.header_size[22]`.

```
val total_size : string -> int -> int
```

See `Marshal.header_size[22]`.

23 Module MoreLabels : Extra labeled libraries.

This meta-module provides labeled version of the `Hashtbl`[14], `Map`[21] and `Set`[34] modules.

They only differ by their labels. They are provided to help porting from previous versions of Objective Caml. The contents of this module are subject to change.

```
module Hashtbl : sig end
  [23.1]
module Map : sig end
  [23.2]
module Set : sig end
  [23.3]
```

23.1 Module MoreLabels.Hashtbl

```
module Hashtbl : sig

  type ('a, 'b) t = ('a, 'b) Hashtbl.t
  val create : int -> ('a, 'b) t
  val clear : ('a, 'b) t -> unit
  val add : ('a, 'b) t -> key:'a -> data:'b -> unit
  val copy : ('a, 'b) t -> ('a, 'b) t
  val find : ('a, 'b) t -> 'a -> 'b
  val find_all : ('a, 'b) t -> 'a -> 'b list
  val mem : ('a, 'b) t -> 'a -> bool
  val remove : ('a, 'b) t -> 'a -> unit
  val replace : ('a, 'b) t -> key:'a -> data:'b -> unit
  val iter : f:(key:'a -> data:'b -> unit) -> ('a, 'b) t -> unit
  val fold : f:(key:'a -> data:'b -> 'c -> 'c) ->
    ('a, 'b) t -> init:'c -> 'c
  module type HashedType = Hashtbl.HashedType
    [23.1.1]
  module type S = sig end
    [23.1.2]
  module Make : functor (H : HashedType) -> sig end
    [23.1.3]
  val hash : 'a -> int
  val hash_param : int -> int -> 'a -> int
end
```

23.1.1 Module type MoreLabels.Hashtbl.HashedType

```
module type HashedType = sig

end
```

23.1.2 Module type MoreLabels.Hashtbl.S

```
module type S = sig

  type key
  type 'a t
  val create : int -> 'a t
  val clear : 'a t -> unit
  val copy : 'a t -> 'a t
  val add : 'a t -> key:key -> data:'a -> unit
  val remove : 'a t -> key -> unit
  val find : 'a t -> key -> 'a
  val find_all : 'a t -> key -> 'a list
  val replace : 'a t -> key:key -> data:'a -> unit
  val mem : 'a t -> key -> bool
  val iter : f:(key:key -> data:'a -> unit) ->
    'a t -> unit
  val fold : f:(key:key -> data:'a -> 'b -> 'b) ->
    'a t -> init:'b -> 'b
end
```

23.1.3 Module MoreLabels.Hashtbl.Make

```
module Make : sig
  Parameters:
    • H : MoreLabels.Hashtbl.HashedType

end
```

23.2 Module MoreLabels.Map

```
module Map : sig

  module type OrderedType = Map.OrderedType
  [23.2.1]
```

```

module type S = sig
  end
  [23.2.2]
module Make : functor (Ord : OrderedType) -> sig
  end
  [23.2.3]
end

```

23.2.1 Module type MoreLabels.Map.OrderedType

```

module type OrderedType = sig

end

```

23.2.2 Module type MoreLabels.Map.S

```

module type S = sig

  type key
  type +'a t
  val empty : 'a t
  val add : key:key ->
  data:'a -> 'a t -> 'a t
  val find : key -> 'a t -> 'a
  val remove : key -> 'a t -> 'a t
  val mem : key -> 'a t -> bool
  val iter : f:(key:key -> data:'a -> unit) ->
  'a t -> unit
  val map : f:( 'a -> 'b) -> 'a t -> 'b t
  val mapi : f:(key -> 'a -> 'b) ->
  'a t -> 'b t
  val fold : f:(key:key -> data:'a -> 'b -> 'b) ->
  'a t -> init:'b -> 'b
end

```

23.2.3 Module MoreLabels.Map.Make

```

module Make : sig
  Parameters:
    • Ord : MoreLabels.Map.OrderedType

end

```

23.3 Module MoreLabels.Set

```
module Set : sig

  module type OrderedType = Set.OrderedType
    [23.3.1]
  module type S = sig end
    [23.3.2]
  module Make : functor (Ord : OrderedType) -> sig end
    [23.3.3]
end
```

23.3.1 Module type MoreLabels.Set.OrderedType

```
module type OrderedType = sig

end
```

23.3.2 Module type MoreLabels.Set.S

```
module type S = sig

  type elt
  type t
  val empty : t
  val is_empty : t -> bool
  val mem : elt -> t -> bool
  val add : elt -> t -> t
  val singleton : elt -> t
  val remove : elt -> t -> t
  val union : t -> t -> t
  val inter : t -> t -> t
  val diff : t -> t -> t
  val compare : t -> t -> int
  val equal : t -> t -> bool
  val subset : t -> t -> bool
  val iter : f:(elt -> unit) -> t -> unit
  val fold : f:(elt -> 'a -> 'a) -> t -> init:'a -> 'a
  val for_all : f:(elt -> bool) -> t -> bool
  val exists : f:(elt -> bool) -> t -> bool
  val filter : f:(elt -> bool) -> t -> t
```

```

val partition : f:(elt -> bool) ->
t -> t * t
val cardinal : t -> int
val elements : t -> elt list
val min_elt : t -> elt
val max_elt : t -> elt
val choose : t -> elt
end

```

23.3.3 Module MoreLabels.Set.Make

```

module Make : sig
  Parameters:
    • Ord : MoreLabels.Set.OrderedType

end

```

24 Module Nativeint : Processor-native integers.

This module provides operations on the type `nativeint` of signed 32-bit integers (on 32-bit platforms) or signed 64-bit integers (on 64-bit platforms). This integer type has exactly the same width as that of a `long` integer type in the C compiler. All arithmetic operations over `nativeint` are taken modulo 2^{32} or 2^{64} depending on the word size of the architecture.

Performance notice: values of type `nativeint` occupy more memory space than values of type `int`, and arithmetic operations on `nativeint` are generally slower than those on `int`. Use `nativeint` only when the application requires the extra bit of precision over the `int` type.

```

val zero : nativeint
  The native integer 0.

val one : nativeint
  The native integer 1.

val minus_one : nativeint
  The native integer -1.

val neg : nativeint -> nativeint
  Unary negation.

val add : nativeint -> nativeint -> nativeint
  Addition.

```



```

val sub : nativeint -> nativeint -> nativeint
    Subtraction.

val mul : nativeint -> nativeint -> nativeint
    Multiplication.

val div : nativeint -> nativeint -> nativeint
    Integer division. Raise Division_by_zero if the second argument is zero. This division
    rounds the real quotient of its arguments towards zero, as specified for Pervasives.(/)[28].

val rem : nativeint -> nativeint -> nativeint
    Integer remainder. If y is not zero, the result of Nativeint.rem x y satisfies the following
    properties: Nativeint.zero <= Nativeint.rem x y < Nativeint.abs y and x =
Nativeint.add (Nativeint.mul (Nativeint.div x y) y) (Nativeint.rem x y). If y =
0, Nativeint.rem x y raises Division_by_zero.

val succ : nativeint -> nativeint
    Successor. Nativeint.succ x is Nativeint.add x Nativeint.one.

val pred : nativeint -> nativeint
    Predecessor. Nativeint.pred x is Nativeint.sub x Nativeint.one.

val abs : nativeint -> nativeint
    Return the absolute value of its argument.

val size : int
    The size in bits of a native integer. This is equal to 32 on a 32-bit platform and to 64 on a
    64-bit platform.

val max_int : nativeint
    The greatest representable native integer, either  $2^{31} - 1$  on a 32-bit platform, or  $2^{63} - 1$  on a
    64-bit platform.

val min_int : nativeint
    The greatest representable native integer, either  $-2^{31}$  on a 32-bit platform, or  $-2^{63}$  on a 64-bit
    platform.

val logand : nativeint -> nativeint -> nativeint
    Bitwise logical and.

val logor : nativeint -> nativeint -> nativeint
    Bitwise logical or.

val logxor : nativeint -> nativeint -> nativeint
    Bitwise logical exclusive or.

```

```

val lognot : nativeint -> nativeint
    Bitwise logical negation

val shift_left : nativeint -> int -> nativeint
    Nativeint.shift_left x y shifts x to the left by y bits. The result is unspecified if y < 0
    or y >= bitsize, where bitsize is 32 on a 32-bit platform and 64 on a 64-bit platform.

val shift_right : nativeint -> int -> nativeint
    Nativeint.shift_right x y shifts x to the right by y bits. This is an arithmetic shift: the
    sign bit of x is replicated and inserted in the vacated bits. The result is unspecified if y < 0
    or y >= bitsize.

val shift_right_logical : nativeint -> int -> nativeint
    Nativeint.shift_right_logical x y shifts x to the right by y bits. This is a logical shift:
    zeroes are inserted in the vacated bits regardless of the sign of x. The result is unspecified if
    y < 0 or y >= bitsize.

val of_int : int -> nativeint
    Convert the given integer (type int) to a native integer (type nativeint).

val to_int : nativeint -> int
    Convert the given native integer (type nativeint) to an integer (type int). The high-order
    bit is lost during the conversion.

val of_float : float -> nativeint
    Convert the given floating-point number to a native integer, discarding the fractional part
    (truncate towards 0). The result of the conversion is undefined if, after truncation, the
    number is outside the range [Nativeint.min_int[24], Nativeint.max_int[24]].

val to_float : nativeint -> float
    Convert the given native integer to a floating-point number.

val of_int32 : int32 -> nativeint
    Convert the given 32-bit integer (type int32) to a native integer.

val to_int32 : nativeint -> int32
    Convert the given native integer to a 32-bit integer (type int32). On 64-bit platforms, the
    64-bit native integer is taken modulo  $2^{32}$ , i.e. the top 32 bits are lost. On 32-bit platforms,
    the conversion is exact.

val of_string : string -> nativeint
    Convert the given string to a native integer. The string is read in decimal (by default) or in
    hexadecimal, octal or binary if the string begins with 0x, 0o or 0b respectively. Raise
    Failure "int_of_string" if the given string is not a valid representation of an integer.

```

```
val to_string : nativeint -> string
```

Return the string representation of its argument, in decimal.

```
type t = nativeint
```

An alias for the type of native integers.

```
val compare : t -> t -> int
```

The comparison function for native integers, with the same specification as `Pervasives.compare`[28]. Along with the type `t`, this function `compare` allows the module `Nativeint` to be passed as argument to the functors `Set.Make`[34.3] and `Map.Make`[21.3].

25 Module Obj : Operations on internal representations of values.

Not for the casual user.

```
type t
```

```
val repr : 'a -> t
```

```
val obj : t -> 'a
```

```
val magic : 'a -> 'b
```

```
val is_block : t -> bool
```

```
val is_int : t -> bool
```

```
val tag : t -> int
```

```
val set_tag : t -> int -> unit
```

```
val size : t -> int
```

```
val truncate : t -> int -> unit
```

```
val field : t -> int -> t
```

```
val set_field : t -> int -> t -> unit
```

```
val new_block : int -> int -> t
```

```
val dup : t -> t
```

```
val lazy_tag : int
```

```
val closure_tag : int
```

```
val object_tag : int
```

```
val infix_tag : int
```

```
val forward_tag : int
```

```
val no_scan_tag : int
```

```
val abstract_tag : int
```

```
val string_tag : int
```

```
val double_tag : int
```

```
val double_array_tag : int
```

```
val custom_tag : int
```

```
val final_tag : int
```

The following two functions are deprecated. Use module `Marshal`[22] instead.

```
val marshal : t -> string
```

```
val unmarshal : string -> int -> t * int
```

26 Module `Oo` : Operations on objects

```
val copy : (< .. > as 'a) -> 'a
```

`Oo.copy o` returns a copy of object `o`, that is a fresh object with the same methods and instance variables as `o`

```
val id : < .. > -> int
```

Return an integer identifying this object, unique for the current execution of the program.

27 Module `Parsing` : The run-time library for parsers generated by `ocamlyacc`.

```
val symbol_start : unit -> int
```

`symbol_start` and `Parsing.symbol_end`[27] are to be called in the action part of a grammar rule only. They return the offset of the string that matches the left-hand side of the rule: `symbol_start()` returns the offset of the first character; `symbol_end()` returns the offset after the last character. The first character in a file is at offset 0.

```
val symbol_end : unit -> int
```

See `Parsing.symbol_start`[27].

```
val rhs_start : int -> int
```

Same as `Parsing.symbol_start`[27] and `Parsing.symbol_end`[27], but return the offset of the string matching the `n`th item on the right-hand side of the rule, where `n` is the integer parameter to `lhs_start` and `lhs_end`. `n` is 1 for the leftmost item.

```
val rhs_end : int -> int
```

See `Parsing.rhs_start`[27].

```
val symbol_start_pos : unit -> Lexing.position
```

Same as `symbol_start`, but return a `position` instead of an offset.

```
val symbol_end_pos : unit -> Lexing.position
```

Same as `symbol_end`, but return a `position` instead of an offset.

```
val rhs_start_pos : int -> Lexing.position
    Same as rhs_start, but return a position instead of an offset.

val rhs_end_pos : int -> Lexing.position
    Same as rhs_end, but return a position instead of an offset.

val clear_parser : unit -> unit
    Empty the parser stack. Call it just after a parsing function has returned, to remove all
    pointers from the parser stack to structures that were built by semantic actions during
    parsing. This is optional, but lowers the memory requirements of the programs.

exception Parse_error
    Raised when a parser encounters a syntax error. Can also be raised from the action part of a
    grammar rule, to initiate error recovery.
```

28 Module Pervasives : The initially opened module.

This module provides the basic operations over the built-in types (numbers, booleans, strings, exceptions, references, lists, arrays, input-output channels, ...)

This module is automatically opened at the beginning of each compilation. All components of this module can therefore be referred by their short name, without prefixing them by **Pervasives**.

Exceptions

```
val raise : exn -> 'a
    Raise the given exception value

val invalid_arg : string -> 'a
    Raise exception Invalid_argument with the given string.

val failwith : string -> 'a
    Raise exception Failure with the given string.
```

exception Exit

The **Exit** exception is not raised by any library function. It is provided for use in your programs.

Comparisons

```
val (=) : 'a -> 'a -> bool
    e1 = e2 tests for structural equality of e1 and e2. Mutable structures (e.g. references and
    arrays) are equal if and only if their current contents are structurally equal, even if the two
    mutable objects are not the same physical object. Equality between functional values may
    raise Invalid_argument. Equality between cyclic data structures may not terminate.

val (<>) : 'a -> 'a -> bool
```

Negation of `Pervasives.(=)`[28].

`val (<) : 'a -> 'a -> bool`
See `Pervasives.(>=)`[28].

`val (>) : 'a -> 'a -> bool`
See `Pervasives.(>=)`[28].

`val (<=) : 'a -> 'a -> bool`
See `Pervasives.(>=)`[28].

`val (>=) : 'a -> 'a -> bool`
Structural ordering functions. These functions coincide with the usual orderings over integers, characters, strings and floating-point numbers, and extend them to a total ordering over all types. The ordering is compatible with `(=)`. As in the case of `(=)`, mutable structures are compared by contents. Comparison between functional values may raise `Invalid_argument`. Comparison between cyclic structures may not terminate.

`val compare : 'a -> 'a -> int`
`compare x y` returns 0 if `x=y`, a negative integer if `x<y`, and a positive integer if `x>y`. The same restrictions as for `=` apply. `compare` can be used as the comparison function required by the `Set.Make`[34.3] and `Map.Make`[21.3] functors.

`val min : 'a -> 'a -> 'a`
Return the smaller of the two arguments.

`val max : 'a -> 'a -> 'a`
Return the greater of the two arguments.

`val (==) : 'a -> 'a -> bool`
`e1 == e2` tests for physical equality of `e1` and `e2`. On integers and characters, physical equality is identical to structural equality. On mutable structures, `e1 == e2` is true if and only if physical modification of `e1` also affects `e2`. On non-mutable structures, the behavior of `(==)` is implementation-dependent; however, it is guaranteed that `e1 == e2` implies `e1 = e2`.

`val (!=) : 'a -> 'a -> bool`
Negation of `Pervasives.(==)`[28].

Boolean operations

`val not : bool -> bool`
The boolean negation.

`val (&&) : bool -> bool -> bool`

The boolean “and”. Evaluation is sequential, left-to-right: in `e1 && e2`, `e1` is evaluated first, and if it returns `false`, `e2` is not evaluated at all.

```
val (&) : bool -> bool -> bool
```

Deprecated. `Pervasives.&&`[28] should be used instead.

```
val (||) : bool -> bool -> bool
```

The boolean “or”. Evaluation is sequential, left-to-right: in `e1 || e2`, `e1` is evaluated first, and if it returns `true`, `e2` is not evaluated at all.

```
val or : bool -> bool -> bool
```

Deprecated. `Pervasives.(||)`[28] should be used instead.

Integer arithmetic

Integers are 31 bits wide (or 63 bits on 64-bit processors). All operations are taken modulo 2^{31} (or 2^{63}). They do not fail on overflow.

```
val (~-) : int -> int
```

Unary negation. You can also write `-e` instead of `~-e`.

```
val succ : int -> int
```

`succ x` is `x+1`.

```
val pred : int -> int
```

`pred x` is `x-1`.

```
val (+) : int -> int -> int
```

Integer addition.

```
val (-) : int -> int -> int
```

Integer subtraction.

```
val (*) : int -> int -> int
```

Integer multiplication.

```
val (/) : int -> int -> int
```

Integer division. Raise `Division_by_zero` if the second argument is 0. Integer division rounds the real quotient of its arguments towards zero. More precisely, if `x >= 0` and `y > 0`, `x / y` is the greatest integer less than or equal to the real quotient of `x` by `y`. Moreover, `(-x) / y = x / (-y) = -(x / y)`.

```
val mod : int -> int -> int
```

Integer remainder. If `y` is not zero, the result of `x mod y` satisfies the following properties: `x = (x / y) * y + x mod y` and `abs(x mod y) <= abs(y)-1`. If `y = 0`, `x mod y` raises `Division_by_zero`. Notice that `x mod y` is negative if and only if `x < 0`.

`val abs : int -> int`

Return the absolute value of the argument.

`val max_int : int`

The greatest representable integer.

`val min_int : int`

The smallest representable integer.

Bitwise operations

`val land : int -> int -> int`

Bitwise logical and.

`val lor : int -> int -> int`

Bitwise logical or.

`val lxor : int -> int -> int`

Bitwise logical exclusive or.

`val lnot : int -> int`

Bitwise logical negation.

`val lsl : int -> int -> int`

`n lsl m` shifts `n` to the left by `m` bits. The result is unspecified if `m < 0` or `m >= bitsize`, where `bitsize` is 32 on a 32-bit platform and 64 on a 64-bit platform.

`val lsr : int -> int -> int`

`n lsr m` shifts `n` to the right by `m` bits. This is a logical shift: zeroes are inserted regardless of the sign of `n`. The result is unspecified if `m < 0` or `m >= bitsize`.

`val asr : int -> int -> int`

`n asr m` shifts `n` to the right by `m` bits. This is an arithmetic shift: the sign bit of `n` is replicated. The result is unspecified if `m < 0` or `m >= bitsize`.

Floating-point arithmetic

Caml's floating-point numbers follow the IEEE 754 standard, using double precision (64 bits) numbers. Floating-point operations never raise an exception on overflow, underflow, division by zero, etc. Instead, special IEEE numbers are returned as appropriate, such as `infinity` for `1.0 /. 0.0`, `neg_infinity` for `-1.0 /. 0.0`, and `nan` ("not a number") for `0.0 /. 0.0`. These special numbers then propagate through floating-point computations as expected: for instance, `1.0 /. infinity` is `0.0`, and any operation with `nan` as argument returns `nan` as result.

`val (~-.): float -> float`

Unary negation. You can also write `-.e` instead of `~-.e`.

`val (+.): float -> float -> float`


```

    Floating-point addition

val (-.) : float -> float -> float
    Floating-point subtraction

val (*.) : float -> float -> float
    Floating-point multiplication

val (/.) : float -> float -> float
    Floating-point division.

val (**) : float -> float -> float
    Exponentiation

val sqrt : float -> float
    Square root

val exp : float -> float
    Exponential.

val log : float -> float
    Natural logarithm.

val log10 : float -> float
    Base 10 logarithm.

val cos : float -> float
    See Pervasives.atan2[28].

val sin : float -> float
    See Pervasives.atan2[28].

val tan : float -> float
    See Pervasives.atan2[28].

val acos : float -> float
    See Pervasives.atan2[28].

val asin : float -> float
    See Pervasives.atan2[28].

val atan : float -> float
    See Pervasives.atan2[28].

val atan2 : float -> float -> float

```

The usual trigonometric functions.

`val cosh : float -> float`

See `Pervasives.tanh`[28].

`val sinh : float -> float`

See `Pervasives.tanh`[28].

`val tanh : float -> float`

The usual hyperbolic trigonometric functions.

`val ceil : float -> float`

See `Pervasives.floor`[28].

`val floor : float -> float`

Round the given float to an integer value. `floor f` returns the greatest integer value less than or equal to `f`. `ceil f` returns the least integer value greater than or equal to `f`.

`val abs_float : float -> float`

Return the absolute value of the argument.

`val mod_float : float -> float -> float`

`mod_float a b` returns the remainder of `a` with respect to `b`. The returned value is `a -.` `n` `*.` `b`, where `n` is the quotient `a /. b` rounded towards zero to an integer.

`val frexp : float -> float * int`

`frexp f` returns the pair of the significant and the exponent of `f`. When `f` is zero, the significant `x` and the exponent `n` of `f` are equal to zero. When `f` is non-zero, they are defined by `f = x *.` `2 ** n` and `0.5 <= x < 1.0`.

`val ldexp : float -> int -> float`

`ldexp x n` returns `x *.` `2 ** n`.

`val modf : float -> float * float`

`modf f` returns the pair of the fractional and integral part of `f`.

`val float : int -> float`

Same as `Pervasives.float_of_int`[28].

`val float_of_int : int -> float`

Convert an integer to floating-point.

`val truncate : float -> int`

Same as `Pervasives.int_of_float`[28].

```

val int_of_float : float -> int
    Truncate the given floating-point number to an integer. The result is unspecified if it falls
    outside the range of representable integers.

val infinity : float
    Positive infinity.

val neg_infinity : float
    Negative infinity.

val nan : float
    A special floating-point value denoting the result of an undefined operation such as 0.0 /.
    0.0. Stands for “not a number”.

val max_float : float
    The largest positive finite value of type float.

val min_float : float
    The smallest positive, non-zero, non-denormalized value of type float.

val epsilon_float : float
    The smallest positive float x such that 1.0 +. x <> 1.0.

type fpclass =
| FP_normal
    Normal number, none of the below
| FP_subnormal
    Number very close to 0.0, has reduced precision
| FP_zero
    Number is 0.0 or -0.0
| FP_infinite
    Number is positive or negative infinity
| FP_nan
    Not a number: result of an undefined operation
    The five classes of floating-point numbers, as determined by the
    Pervasives.classify_float[28] function.

val classify_float : float -> fpclass
    Return the class of the given floating-point number: normal, subnormal, zero, infinite, or not
    a number.

```

String operations

More string operations are provided in module `String`[39].

```
val (^) : string -> string -> string
```

String concatenation.

Character operations

More character operations are provided in module `Char`[7].

```
val int_of_char : char -> int
```

Return the ASCII code of the argument.

```
val char_of_int : int -> char
```

Return the character with the given ASCII code. Raise `Invalid_argument "char_of_int"` if the argument is outside the range 0–255.

Unit operations

```
val ignore : 'a -> unit
```

Discard the value of its argument and return `()`. For instance, `ignore(f x)` discards the result of the side-effecting function `f`. It is equivalent to `f x; ()`, except that the latter may generate a compiler warning; writing `ignore(f x)` instead avoids the warning.

String conversion functions

```
val string_of_bool : bool -> string
```

Return the string representation of a boolean.

```
val bool_of_string : string -> bool
```

Convert the given string to a boolean. Raise `Invalid_argument "bool_of_string"` if the string is not `"true"` or `"false"`.

```
val string_of_int : int -> string
```

Return the string representation of an integer, in decimal.

```
val int_of_string : string -> int
```

Convert the given string to an integer. The string is read in decimal (by default) or in hexadecimal (if it begins with `0x` or `0X`), octal (if it begins with `0o` or `0O`), or binary (if it begins with `0b` or `0B`). Raise `Failure "int_of_string"` if the given string is not a valid representation of an integer.

```
val string_of_float : float -> string
```

Return the string representation of a floating-point number.

```
val float_of_string : string -> float
```

Convert the given string to a float. Raise `Failure "float_of_string"` if the given string is not a valid representation of a float.

Pair operations

```
val fst : 'a * 'b -> 'a
```

Return the first component of a pair.

```
val snd : 'a * 'b -> 'b
```

Return the second component of a pair.

List operations

More list operations are provided in module `List`[19].

```
val (@) : 'a list -> 'a list -> 'a list
```

List concatenation.

Input/output

```
type in_channel
```

The type of input channel.

```
type out_channel
```

The type of output channel.

```
val stdin : in_channel
```

The standard input for the process.

```
val stdout : out_channel
```

The standard output for the process.

```
val stderr : out_channel
```

The standard error output for the process.

Output functions on standard output

```
val print_char : char -> unit
```

Print a character on standard output.

```
val print_string : string -> unit
```

Print a string on standard output.

```
val print_int : int -> unit
```

Print an integer, in decimal, on standard output.

```
val print_float : float -> unit
```

Print a floating-point number, in decimal, on standard output.

```
val print_endline : string -> unit
```

Print a string, followed by a newline character, on standard output and flush standard output.

`val print_newline : unit -> unit`

Print a newline character on standard output, and flush standard output. This can be used to simulate line buffering of standard output.

Output functions on standard error

`val prerr_char : char -> unit`

Print a character on standard error.

`val prerr_string : string -> unit`

Print a string on standard error.

`val prerr_int : int -> unit`

Print an integer, in decimal, on standard error.

`val prerr_float : float -> unit`

Print a floating-point number, in decimal, on standard error.

`val prerr_endline : string -> unit`

Print a string, followed by a newline character on standard error and flush standard error.

`val prerr_newline : unit -> unit`

Print a newline character on standard error, and flush standard error.

Input functions on standard input

`val read_line : unit -> string`

Flush standard output, then read characters from standard input until a newline character is encountered. Return the string of all characters read, without the newline character at the end.

`val read_int : unit -> int`

Flush standard output, then read one line from standard input and convert it to an integer. Raise `Failure "int_of_string"` if the line read is not a valid representation of an integer.

`val read_float : unit -> float`

Flush standard output, then read one line from standard input and convert it to a floating-point number. The result is unspecified if the line read is not a valid representation of a floating-point number.

General output functions

`type open_flag =`

`| Open_rdonly`

open for reading.

`| Open_wronly`

open for writing.

- | `Open_append`
open for appending: always write at end of file.
- | `Open_creat`
create the file if it does not exist.
- | `Open_trunc`
empty the file if it already exists.
- | `Open_excl`
fail if the file already exists.
- | `Open_binary`
open in binary mode (no conversion).
- | `Open_text`
open in text mode (may perform conversions).
- | `Open_nonblock`
open in non-blocking mode.

Opening modes for `Pervasives.open_out_gen[28]` and `Pervasives.open_in_gen[28]`.

val `open_out` : `string` -> `out_channel`
Open the named file for writing, and return a new output channel on that file, positionned at the beginning of the file. The file is truncated to zero length if it already exists. It is created if it does not already exists. Raise `Sys_error` if the file could not be opened.

val `open_out_bin` : `string` -> `out_channel`
Same as `Pervasives.open_out[28]`, but the file is opened in binary mode, so that no translation takes place during writes. On operating systems that do not distinguish between text mode and binary mode, this function behaves like `Pervasives.open_out[28]`.

val `open_out_gen` : `open_flag list` -> `int` -> `string` -> `out_channel`
Open the named file for writing, as above. The extra argument `mode` specify the opening mode. The extra argument `perm` specifies the file permissions, in case the file must be created. `Pervasives.open_out[28]` and `Pervasives.open_out_bin[28]` are special cases of this function.

val `flush` : `out_channel` -> `unit`
Flush the buffer associated with the given output channel, performing all pending writes on that channel. Interactive programs must be careful about flushing standard output and standard error at the right time.

val `flush_all` : `unit` -> `unit`
Flush all open output channels; ignore errors.

val `output_char` : `out_channel` -> `char` -> `unit`

Write the character on the given output channel.

```
val output_string : out_channel -> string -> unit
```

Write the string on the given output channel.

```
val output : out_channel -> string -> int -> int -> unit
```

`output oc buf pos len` writes `len` characters from string `buf`, starting at offset `pos`, to the given output channel `oc`. Raise `Invalid_argument "output"` if `pos` and `len` do not designate a valid substring of `buf`.

```
val output_byte : out_channel -> int -> unit
```

Write one 8-bit integer (as the single character with that code) on the given output channel. The given integer is taken modulo 256.

```
val output_binary_int : out_channel -> int -> unit
```

Write one integer in binary format on the given output channel. The only reliable way to read it back is through the `Pervasives.input_binary_int[28]` function. The format is compatible across all machines for a given version of Objective Caml.

```
val output_value : out_channel -> 'a -> unit
```

Write the representation of a structured value of any type to a channel. Circularities and sharing inside the value are detected and preserved. The object can be read back, by the function `Pervasives.input_value[28]`. See the description of module `Marshal[22]` for more information. `Pervasives.output_value[28]` is equivalent to `Marshal.to_channel[22]` with an empty list of flags.

```
val seek_out : out_channel -> int -> unit
```

`seek_out chan pos` sets the current writing position to `pos` for channel `chan`. This works only for regular files. On files of other kinds (such as terminals, pipes and sockets), the behavior is unspecified.

```
val pos_out : out_channel -> int
```

Return the current writing position for the given channel.

```
val out_channel_length : out_channel -> int
```

Return the total length (number of characters) of the given channel. This works only for regular files. On files of other kinds, the result is meaningless.

```
val close_out : out_channel -> unit
```

Close the given channel, flushing all buffered write operations. Output functions raise a `Sys_error` exception when they are applied to a closed output channel, except `close_out` and `flush`, which do nothing when applied to an already closed channel. Note that `close_out` may raise `Sys_error` if the operating system signals an error when flushing or closing.

`val close_out_noerr : out_channel -> unit`

Same as `close_out`, but ignore all errors.

`val set_binary_mode_out : out_channel -> bool -> unit`

`set_binary_mode_out oc true` sets the channel `oc` to binary mode: no translations take place during output. `set_binary_mode_out oc false` sets the channel `oc` to text mode: depending on the operating system, some translations may take place during output. For instance, under Windows, end-of-lines will be translated from `\n` to `\r\n`. This function has no effect under operating systems that do not distinguish between text mode and binary mode.

General input functions

`val open_in : string -> in_channel`

Open the named file for reading, and return a new input channel on that file, positioned at the beginning of the file. Raise `Sys_error` if the file could not be opened.

`val open_in_bin : string -> in_channel`

Same as `Pervasives.open_in[28]`, but the file is opened in binary mode, so that no translation takes place during reads. On operating systems that do not distinguish between text mode and binary mode, this function behaves like `Pervasives.open_in[28]`.

`val open_in_gen : open_flag list -> int -> string -> in_channel`

Open the named file for reading, as above. The extra arguments `mode` and `perm` specify the opening mode and file permissions. `Pervasives.open_in[28]` and `Pervasives.open_in_bin[28]` are special cases of this function.

`val input_char : in_channel -> char`

Read one character from the given input channel. Raise `End_of_file` if there are no more characters to read.

`val input_line : in_channel -> string`

Read characters from the given input channel, until a newline character is encountered. Return the string of all characters read, without the newline character at the end. Raise `End_of_file` if the end of the file is reached at the beginning of line.

`val input : in_channel -> string -> int -> int -> int`

`input ic buf pos len` reads up to `len` characters from the given channel `ic`, storing them in string `buf`, starting at character number `pos`. It returns the actual number of characters read, between 0 and `len` (inclusive). A return value of 0 means that the end of file was reached. A return value between 0 and `len` exclusive means that not all requested `len` characters were read, either because no more characters were available at that time, or because the implementation found it convenient to do a partial read; `input` must be called again to read the remaining characters, if desired. (See also `Pervasives.really_input[28]` for reading exactly `len` characters.) Exception `Invalid_argument "input"` is raised if `pos` and `len` do not designate a valid substring of `buf`.

```

val really_input : in_channel -> string -> int -> int -> unit
    really_input ic buf pos len reads len characters from channel ic, storing them in
    string buf, starting at character number pos. Raise End_of_file if the end of file is reached
    before len characters have been read. Raise Invalid_argument "really_input" if pos and
    len do not designate a valid substring of buf.

val input_byte : in_channel -> int
    Same as Pervasives.input_char[28], but return the 8-bit integer representing the
    character. Raise End_of_file if an end of file was reached.

val input_binary_int : in_channel -> int
    Read an integer encoded in binary format from the given input channel. See
    Pervasives.output_binary_int[28]. Raise End_of_file if an end of file was reached while
    reading the integer.

val input_value : in_channel -> 'a
    Read the representation of a structured value, as produced by
    Pervasives.output_value[28], and return the corresponding value. This function is
    identical to Marshal.from_channel[22]; see the description of module Marshal[22] for more
    information, in particular concerning the lack of type safety.

val seek_in : in_channel -> int -> unit
    seek_in chan pos sets the current reading position to pos for channel chan. This works
    only for regular files. On files of other kinds, the behavior is unspecified.

val pos_in : in_channel -> int
    Return the current reading position for the given channel.

val in_channel_length : in_channel -> int
    Return the total length (number of characters) of the given channel. This works only for
    regular files. On files of other kinds, the result is meaningless.

val close_in : in_channel -> unit
    Close the given channel. Input functions raise a Sys_error exception when they are applied
    to a closed input channel, except close_in, which does nothing when applied to an already
    closed channel. Note that close_in may raise Sys_error if the operating system signals an
    error.

val close_in_noerr : in_channel -> unit
    Same as close_in, but ignore all errors.

val set_binary_mode_in : in_channel -> bool -> unit

```

`set_binary_mode_in ic true` sets the channel `ic` to binary mode: no translations take place during input. `set_binary_mode_out ic false` sets the channel `ic` to text mode: depending on the operating system, some translations may take place during input. For instance, under Windows, end-of-lines will be translated from `\r\n` to `\n`. This function has no effect under operating systems that do not distinguish between text mode and binary mode.

Operations on large files

```
module LargeFile : sig end
[28.1]
```

References

```
type 'a ref = {
  mutable contents : 'a ;
}
```

The type of references (mutable indirection cells) containing a value of type `'a`.

```
val ref : 'a -> 'a ref
```

Return a fresh reference containing the given value.

```
val (!) : 'a ref -> 'a
```

`!r` returns the current contents of reference `r`. Equivalent to `fun r -> r.contents`.

```
val (:=) : 'a ref -> 'a -> unit
```

`r := a` stores the value of `a` in reference `r`. Equivalent to `fun r v -> r.contents <- v`.

```
val incr : int ref -> unit
```

Increment the integer contained in the given reference. Equivalent to `fun r -> r := succ !r`.

```
val decr : int ref -> unit
```

Decrement the integer contained in the given reference. Equivalent to `fun r -> r := pred !r`.

Operations on format strings

See modules `Printf`[30] and `Scanf`[33] for more operations on format strings.

```
type ('a, 'b, 'c) format = ('a, 'b, 'c, 'c) format4
```

Simplified type for format strings, included for backward compatibility with earlier releases of Objective Caml. `'a` is the type of the parameters of the format, `'c` is the result type for the "printf"-style function, and `'b` is the type of the first argument given to `%a` and `%t` printing functions.

```
val string_of_format : ('a, 'b, 'c, 'd) format4 -> string
```

Converts a format string into a string.

```
val format_of_string : ('a, 'b, 'c, 'd) format4 -> ('a, 'b, 'c, 'd) format4
```

`format_of_string s` returns a format string read from the string literal `s`.

`val (^) :`

`('a, 'b, 'c, 'd) format4 ->`

`('d, 'b, 'c, 'e) format4 -> ('a, 'b, 'c, 'e) format4`

`f1 ^f2` catenates formats `f1` and `f2`. The result is a format that accepts arguments from `f1`, then arguments from `f2`.

Program termination

`val exit : int -> 'a`

Terminate the process, returning the given status code to the operating system: usually 0 to indicate no errors, and a small positive integer to indicate failure. All open output channels are flushed with `flush_all`. An implicit `exit 0` is performed each time a program terminates normally. An implicit `exit 2` is performed if the program terminates early because of an uncaught exception.

`val at_exit : (unit -> unit) -> unit`

Register the given function to be called at program termination time. The functions registered with `at_exit` will be called when the program executes `Pervasives.exit[28]`, or terminates, either normally or because of an uncaught exception. The functions are called in “last in, first out” order: the function most recently added with `at_exit` is called first.

28.1 Module `Pervasives.LargeFile` : Operations on large files.

`module LargeFile : sig`

This sub-module provides 64-bit variants of the channel functions that manipulate file positions and file sizes. By representing positions and sizes by 64-bit integers (type `int64`) instead of regular integers (type `int`), these alternate functions allow operating on files whose sizes are greater than `max_int`.

`val seek_out : Pervasives.out_channel -> int64 -> unit`

`val pos_out : Pervasives.out_channel -> int64`

`val out_channel_length : Pervasives.out_channel -> int64`

`val seek_in : Pervasives.in_channel -> int64 -> unit`

`val pos_in : Pervasives.in_channel -> int64`

`val in_channel_length : Pervasives.in_channel -> int64`

`end`

29 Module `Printexc` : Facilities for printing exceptions.

`val to_string : exn -> string`

`Printexc.to_string e` returns a string representation of the exception `e`.

`val print : ('a -> 'b) -> 'a -> 'b`

`Printexc.print fn x` applies `fn` to `x` and returns the result. If the evaluation of `fn x` raises any exception, the name of the exception is printed on standard error output, and the exception is raised again. The typical use is to catch and report exceptions that escape a function application.

`val catch : ('a -> 'b) -> 'a -> 'b`

`Printexc.catch fn x` is similar to `Printexc.print`[29], but aborts the program with exit code 2 after printing the uncaught exception. This function is deprecated: the runtime system is now able to print uncaught exceptions as precisely as `Printexc.catch` does. Moreover, calling `Printexc.catch` makes it harder to track the location of the exception using the debugger or the stack backtrace facility. So, do not use `Printexc.catch` in new code.

30 Module Printf : Formatted output functions.

`val fprintf :`

`Pervasives.out_channel ->`

`('a, Pervasives.out_channel, unit) Pervasives.format -> 'a`

`fprintf outchan format arg1 ... argN` formats the arguments `arg1` to `argN` according to the format string `format`, and outputs the resulting string on the channel `outchan`.

The format is a character string which contains two types of objects: plain characters, which are simply copied to the output channel, and conversion specifications, each of which causes conversion and printing of one argument.

Conversion specifications consist in the `%` character, followed by optional flags and field widths, followed by one or two conversion character. The conversion characters and their meanings are:

- `d`, `i`, `n`, or `N`: convert an integer argument to signed decimal.
- `u`: convert an integer argument to unsigned decimal.
- `x`: convert an integer argument to unsigned hexadecimal, using lowercase letters.
- `X`: convert an integer argument to unsigned hexadecimal, using uppercase letters.
- `o`: convert an integer argument to unsigned octal.
- `s`: insert a string argument.
- `S`: insert a string argument in Caml syntax (double quotes, escapes).
- `c`: insert a character argument.
- `C`: insert a character argument in Caml syntax (single quotes, escapes).
- `f`: convert a floating-point argument to decimal notation, in the style `dddd.ddd`.
- `F`: convert a floating-point argument in Caml syntax (`dddd.ddd` with a mandatory `.`).

- **e** or **E**: convert a floating-point argument to decimal notation, in the style `d.ddd e+-dd` (mantissa and exponent).
- **g** or **G**: convert a floating-point argument to decimal notation, in style **f** or **e**, **E** (whichever is more compact).
- **B**: convert a boolean argument to the string `true` or `false`
- **b**: convert a boolean argument (for backward compatibility; do not use in new programs).
- **ld**, **li**, **lu**, **lx**, **lX**, **lo**: convert an `int32` argument to the format specified by the second letter (decimal, hexadecimal, etc).
- **nd**, **ni**, **nu**, **nx**, **nX**, **no**: convert a `nativeint` argument to the format specified by the second letter.
- **Ld**, **Li**, **Lu**, **Lx**, **LX**, **Lo**: convert an `int64` argument to the format specified by the second letter.
- **a**: user-defined printer. Takes two arguments and apply the first one to `outchan` (the current output channel) and to the second argument. The first argument must therefore have type `out_channel -> 'b -> unit` and the second `'b`. The output produced by the function is therefore inserted in the output of `fprintf` at the current point.
- **t**: same as `%a`, but takes only one argument (with type `out_channel -> unit`) and apply it to `outchan`.
- **!**: take no argument and flush the output.
- **%**: take no argument and output one `%` character.

The optional flags include:

- **-**: left-justify the output (default is right justification).
- **0**: for numerical conversions, pad with zeroes instead of spaces.
- **+**: for numerical conversions, prefix number with a `+` sign if positive.
- **space**: for numerical conversions, prefix number with a space if positive.
- **#**: request an alternate formatting style for numbers.

The field widths are composed of an optional integer literal indicating the minimal width of the result, possibly followed by a dot `.` and another integer literal indicating how many digits follow the decimal point in the `%f`, `%e`, and `%E` conversions. For instance, `%6d` prints an integer, prefixing it with spaces to fill at least 6 characters; and `%.4f` prints a float with 4 fractional digits. Each or both of the integer literals can also be specified as a `*`, in which case an extra integer argument is taken to specify the corresponding width or precision.

Warning: if too few arguments are provided, for instance because the `printf` function is partially applied, the format is immediately printed up to the conversion of the first missing argument; printing will then resume when the missing arguments are provided. For example, `List.iter (printf "x=%d y=%d " 1) [2;3]` prints `x=1 y=2 3` instead of the expected `x=1 y=2 x=1 y=3`. To get the expected behavior, do `List.iter (fun y -> printf "x=%d y=%d " 1 y) [2;3]`.

```

val printf : ('a, Pervasives.out_channel, unit) Pervasives.format -> 'a
    Same as Printf.fprintf[30], but output on stdout.

val eprintf : ('a, Pervasives.out_channel, unit) Pervasives.format -> 'a
    Same as Printf.fprintf[30], but output on stderr.

val sprintf : ('a, unit, string) Pervasives.format -> 'a
    Same as Printf.fprintf[30], but instead of printing on an output channel, return a string
    containing the result of formatting the arguments.

val bprintf : Buffer.t -> ('a, Buffer.t, unit) Pervasives.format -> 'a
    Same as Printf.fprintf[30], but instead of printing on an output channel, append the
    formatted arguments to the given extensible buffer (see module Buffer[4]).

val kprintf : (string -> 'a) -> ('b, unit, string, 'a) format4 -> 'b
    kprintf k format arguments is the same as sprintf format arguments, except that the
    resulting string is passed as argument to k; the result of k is then returned as the result of
    kprintf.

```

31 Module Queue : First-in first-out queues.

This module implements queues (FIFOs), with in-place modification.

```

type 'a t
    The type of queues containing elements of type 'a.

exception Empty
    Raised when Queue.take[31] or Queue.peek[31] is applied to an empty queue.

val create : unit -> 'a t
    Return a new queue, initially empty.

val add : 'a -> 'a t -> unit
    add x q adds the element x at the end of the queue q.

val push : 'a -> 'a t -> unit
    push is a synonym for add.

val take : 'a t -> 'a
    take q removes and returns the first element in queue q, or raises Empty if the queue is
    empty.

val pop : 'a t -> 'a

```

`pop` is a synonym for `take`.

`val peek : 'a t -> 'a`

`peek q` returns the first element in queue `q`, without removing it from the queue, or raises `Empty` if the queue is empty.

`val top : 'a t -> 'a`

`top` is a synonym for `peek`.

`val clear : 'a t -> unit`

Discard all elements from a queue.

`val copy : 'a t -> 'a t`

Return a copy of the given queue.

`val is_empty : 'a t -> bool`

Return `true` if the given queue is empty, `false` otherwise.

`val length : 'a t -> int`

Return the number of elements in a queue.

`val iter : ('a -> unit) -> 'a t -> unit`

`iter f q` applies `f` in turn to all elements of `q`, from the least recently entered to the most recently entered. The queue itself is unchanged.

`val fold : ('a -> 'b -> 'a) -> 'a -> 'b t -> 'a`

`fold f accu q` is equivalent to `List.fold_left f accu l`, where `l` is the list of `q`'s elements. The queue remains unchanged.

`val transfer : 'a t -> 'a t -> unit`

`transfer q1 q2` adds all of `q1`'s elements at the end of the queue `q2`, then clears `q1`. It is equivalent to the sequence `iter (fun x -> add x q2) q1; clear q1`, but runs in constant time.

32 Module Random : Pseudo-random number generators (PRNG).

Basic functions

`val init : int -> unit`

Initialize the generator, using the argument as a seed. The same seed will always yield the same sequence of numbers.

`val full_init : int array -> unit`

Same as `Random.init[32]` but takes more data as seed.


```

val self_init : unit -> unit
    Initialize the generator with a more-or-less random seed chosen in a system-dependent way.

val bits : unit -> int
    Return 30 random bits in a nonnegative integer.

val int : int -> int
    Random.int bound returns a random integer between 0 (inclusive) and bound (exclusive).
    bound must be more than 0 and less than  $2^{30}$ .

val int32 : Int32.t -> Int32.t
    Random.int32 bound returns a random integer between 0 (inclusive) and bound (exclusive).
    bound must be greater than 0.

val nativeint : Nativeint.t -> Nativeint.t
    Random.nativeint bound returns a random integer between 0 (inclusive) and bound
    (exclusive). bound must be greater than 0.

val int64 : Int64.t -> Int64.t
    Random.int64 bound returns a random integer between 0 (inclusive) and bound (exclusive).
    bound must be greater than 0.

val float : float -> float
    Random.float bound returns a random floating-point number between 0 (inclusive) and
    bound (exclusive). If bound is negative, the result is negative or zero. If bound is 0, the result
    is 0.

val bool : unit -> bool
    Random.bool () returns true or false with probability 0.5 each.

```

Advanced functions

The functions from module **State** manipulate the current state of the random generator explicitly. This allows using one or several deterministic PRNGs, even in a multi-threaded program, without interference from other parts of the program.

```

module State : sig end
    [32.1]
val get_state : unit -> State.t
    Return the current state of the generator used by the basic functions.

val set_state : State.t -> unit
    Set the state of the generator used by the basic functions.

```

32.1 Module Random.State

```
module State : sig
```

```
type t
```

The type of PRNG states.

```
val make : int array -> t
```

Create a new state and initialize it with the given seed.

```
val make_self_init : unit -> t
```

Create a new state and initialize it with a system-dependent low-entropy seed.

```
val copy : t -> t
```

Return a copy of the given state.

```
val bits : t -> int
```

```
val int : t -> int -> int
```

```
val int32 : t -> Int32.t -> Int32.t
```

```
val nativeint : t -> Nativeint.t -> Nativeint.t
```

```
val int64 : t -> Int64.t -> Int64.t
```

```
val float : t -> float -> float
```

```
val bool : t -> bool
```

These functions are the same as the basic functions, except that they use (and update) the given PRNG state instead of the default one.

```
end
```

33 Module Scanf : Formatted input functions.

```
module Scanning : sig end
```

[33.1]

```
exception Scan_failure of string
```

The exception that formatted input functions raise when the input cannot be read according to the given format.

```
val bscanf :
```

```
Scanning.scanbuf ->
```

```
('a, Scanning.scanbuf, 'b) Pervasives.format -> 'a -> 'b
```

bscanf *ib format f* reads tokens from the scanning buffer *ib* according to the format string *format*, converts these tokens to values, and applies the function *f* to these values. The result of this application of *f* is the result of the whole construct.

For instance, if *p* is the function `fun s i -> i + 1`, then `Scanf.sscanf "x = 1" "%s = %i" p` returns 2.

Raise `Scanf.Scan_failure` if the given input does not match the format.

Raise `Failure` if a conversion to a number is not possible.

Raise `End_of_file` if the end of input is encountered while scanning and the input matches the given format so far.

The format is a character string which contains three types of objects:

- plain characters, which are simply matched with the characters of the input,
- conversion specifications, each of which causes reading and conversion of one argument for *f*,
- scanning indications to specify boundaries of tokens.

Among plain characters the space character (ASCII code 32) has a special meaning: it matches “whitespace”, that is any number of tab, space, newline and carriage return characters. Hence, a space in the format matches any amount of whitespace in the input.

Conversion specifications consist in the % character, followed by an optional flag, an optional field width, and followed by one or two conversion characters. The conversion characters and their meanings are:

- **d**: reads an optionally signed decimal integer.
- **i**: reads an optionally signed integer (usual input formats for hexadecimal (`0x[d]+` and `0X[d]+`), octal (`0o[d]+`), and binary `0b[d]+` notations are understood).
- **u**: reads an unsigned decimal integer.
- **x** or **X**: reads an unsigned hexadecimal integer.
- **o**: reads an unsigned octal integer.
- **s**: reads a string argument (by default strings end with a space).
- **S**: reads a delimited string argument (delimiters and special escaped characters follow the lexical conventions of Caml).
- **c**: reads a single character. To test the current input character without reading it, specify a null field width, i.e. use specification `%0c`. Raise `Invalid_argument`, if the field width specification is greater than 1.
- **C**: reads a single delimited character (delimiters and special escaped characters follow the lexical conventions of Caml).
- **f**, **e**, **E**, **g**, **G**, **F**: reads an optionally signed floating-point number in decimal notation, in the style `dddd.ddd e/E+-dd`.
- **F**: reads a floating point number according to the lexical conventions of Caml (hence the decimal point is mandatory if the exponent part is not mentioned).

- **B**: reads a boolean argument (**true** or **false**).
- **b**: reads a boolean argument (for backward compatibility; do not use in new programs).
- **ld, li, lu, lx, lX, lo**: reads an **int32** argument to the format specified by the second letter (decimal, hexadecimal, etc).
- **nd, ni, nu, nx, nX, no**: reads a **nativeint** argument to the format specified by the second letter.
- **Ld, Li, Lu, Lx, LX, Lo**: reads an **int64** argument to the format specified by the second letter.
- **[range]**: reads characters that matches one of the characters mentioned in the range of characters **range** (or not mentioned in it, if the range starts with **^**). Returns a **string** that can be empty, if no character in the input matches the range. If a closing bracket appears in a range, it must occur as the first character of the range (or just after the **^** in case of range negation); hence **[]** matches a **]** character and **[^]** matches any character that is not **]**.
- **n**: applies **f** to the number of characters read so far.
- **N**: applies **f** to the number of tokens read so far.
- **!**: matches the end of input condition.
- **%**: matches one **%** character in the input.

Following the **%** character introducing a conversion, there may be the special flag **_**: the conversion that follows occurs as usual, but the resulting value is discarded.

The field widths are composed of an optional integer literal indicating the maximal width of the token to read. For instance, **%6d** reads an integer, having at most 6 decimal digits; and **%4f** reads a float with at most 4 characters.

Scanning indications appear just after string conversions **s** and **[range]** to delimit the end of the token. A scanning indication is introduced by a **@** character, followed by some constant character **c**. It means that the string token should end just before the next matching **c** (which is skipped). If no **c** character is encountered, the string token spreads as much as possible. For instance, **"%s@\t"** reads a string up to the next tabulation character. If a scanning indication **@c** does not follow a string conversion, it is ignored and treated as a plain **c** character.

Note:

- in addition to relevant digits, **'_'** characters may appear inside numbers (this is reminiscent to the usual Caml conventions). If stricter scanning is desired, use the range conversion facility instead of the number conversions.
- the **scanf** facility is not intended for heavy duty lexical analysis and parsing. If it appears not expressive enough for your needs, several alternative exists: regular expressions (module **Str**), stream parsers, **ocamllex**-generated lexers, **ocamlyacc**-generated parsers.

```

val fscanf :
  Pervasives.in_channel ->
('a, Scanning.scanbuf, 'b) Pervasives.format -> 'a -> 'b
  Same as Scanf.bscanf[33], but inputs from the given channel.
  Warning: since all scanning functions operate from a scanning buffer, be aware that each fscanf
  invocation must allocate a new fresh scanning buffer (unless careful use of partial evaluation in the
  program). Hence, there are chances that some characters seem to be skipped (in fact they are
  pending in the previously used buffer). This happens in particular when calling fscanf again after
  a scan involving a format that necessitates some look ahead (such as a format that ends by skipping
  whitespace in the input).
  To avoid confusion, consider using bscanf with an explicitly created scanning buffer. Use for
  instance Scanning.from_file f to allocate the scanning buffer reading from file f.
  This method is not only clearer it is also faster, since scanning buffers to files are optimized for
  fast bufferized reading.
val sscanf :
  string -> ('a, Scanning.scanbuf, 'b) Pervasives.format -> 'a -> 'b
  Same as Scanf.bscanf[33], but inputs from the given string.

val scanf : ('a, Scanning.scanbuf, 'b) Pervasives.format -> 'a -> 'b
  Same as Scanf.bscanf[33], but reads from the predefined scanning buffer Scanning.stdib
  that is connected to stdin.

val kscanf :
  Scanning.scanbuf ->
(Scanning.scanbuf -> exn -> 'a) ->
('b, Scanning.scanbuf, 'a) Pervasives.format -> 'b -> 'a
  Same as Scanf.bscanf[33], but takes an additional function argument ef that is called in
  case of error: if the scanning process or some conversion fails, the scanning function aborts
  and applies the error handling function ef to the scanning buffer and the exception that
  aborted the scanning process.

```

33.1 Module Scanf.Scanning : Scanning buffers.

```
module Scanning : sig
```

```
type scanbuf
```

The type of scanning buffers. A scanning buffer is the argument passed to the scanning functions used by the **scanf** family of functions. The scanning buffer holds the current state of the scan, plus a function to get the next char from the input, and a token buffer to store the string matched so far.

```
val stdib : scanbuf
```

The scanning buffer reading from **stdin**. **stdib** is equivalent to **Scanning.from_channel stdin**.

```

val from_string : string -> scanbuf
    Scanning.from_string s returns a scanning buffer which reads from the given string.
    Reading starts from the first character in the string. The end-of-input condition is set when
    the end of the string is reached.

val from_file : string -> scanbuf
    Bufferized file reading in text mode. The efficient and usual way to scan text mode files (in
    effect, from_file returns a buffer that reads characters in large chunks, rather than one
    character at a time as buffers returned by from_channel do). Scanning.from_file fname
    returns a scanning buffer which reads from the given file fname in text mode.

val from_file_bin : string -> scanbuf
    Bufferized file reading in binary mode.

val from_function : (unit -> char) -> scanbuf
    Scanning.from_function f returns a scanning buffer with the given function as its reading
    method. When scanning needs one more character, the given function is called. When the
    function has no more character to provide, it must signal an end-of-input condition by
    raising the exception End_of_file.

val from_channel : Pervasives.in_channel -> scanbuf
    Scanning.from_channel inchan returns a scanning buffer which reads one character at a
    time from the input channel inchan, starting at the current reading position.

val end_of_input : scanbuf -> bool
    Scanning.end_of_input scanbuf tests the end of input condition of the given buffer.

val beginning_of_input : scanbuf -> bool
    Scanning.beginning_of_input scanbuf tests the beginning of input condition of the given
    buffer.

end

```

34 Module Set : Sets over ordered types.

This module implements the set data structure, given a total ordering function over the set elements. All operations over sets are purely applicative (no side-effects). The implementation uses balanced binary trees, and is therefore reasonably efficient: insertion and membership take time logarithmic in the size of the set, for instance.

```

module type OrderedType = sig end
    [34.1]
module type S = sig end
    [34.2]
module Make : functor (Ord : OrderedType) -> sig end
    [34.3]

```

34.1 Module type `Set.OrderedType` : Input signature of the functor `Set.Make`[34.3].

```
module type OrderedType = sig
```

```
  type t
```

The type of the set elements.

```
  val compare : t -> t -> int
```

A total ordering function over the set elements. This is a two-argument function `f` such that `f e1 e2` is zero if the elements `e1` and `e2` are equal, `f e1 e2` is strictly negative if `e1` is smaller than `e2`, and `f e1 e2` is strictly positive if `e1` is greater than `e2`. Example: a suitable ordering function is the generic structural comparison function `Pervasives.compare`[28].

```
end
```

34.2 Module type `Set.S` : Output signature of the functor `Set.Make`[34.3].

```
module type S = sig
```

```
  type elt
```

The type of the set elements.

```
  type t
```

The type of sets.

```
  val empty : t
```

The empty set.

```
  val is_empty : t -> bool
```

Test whether a set is empty or not.

```
  val mem : elt -> t -> bool
```

`mem x s` tests whether `x` belongs to the set `s`.

```
  val add : elt -> t -> t
```

`add x s` returns a set containing all elements of `s`, plus `x`. If `x` was already in `s`, `s` is returned unchanged.

```
  val singleton : elt -> t
```

`singleton x` returns the one-element set containing only `x`.

```
  val remove : elt -> t -> t
```

`remove x s` returns a set containing all elements of `s`, except `x`. If `x` was not in `s`, `s` is returned unchanged.

```

val union : t -> t -> t
    Set union.

val inter : t -> t -> t
    Set intersection.

val diff : t -> t -> t
    Set difference.

val compare : t -> t -> int
    Total ordering between sets. Can be used as the ordering function for doing sets of sets.

val equal : t -> t -> bool
    equal s1 s2 tests whether the sets s1 and s2 are equal, that is, contain equal elements.

val subset : t -> t -> bool
    subset s1 s2 tests whether the set s1 is a subset of the set s2.

val iter : (elt -> unit) -> t -> unit
    iter f s applies f in turn to all elements of s. The order in which the elements of s are
    presented to f is unspecified.

val fold : (elt -> 'a -> 'a) -> t -> 'a -> 'a
    fold f s a computes (f xN ... (f x2 (f x1 a))), where x1 ... xN are the
    elements of s. The order in which elements of s are presented to f is unspecified.

val for_all : (elt -> bool) -> t -> bool
    for_all p s checks if all elements of the set satisfy the predicate p.

val exists : (elt -> bool) -> t -> bool
    exists p s checks if at least one element of the set satisfies the predicate p.

val filter : (elt -> bool) -> t -> t
    filter p s returns the set of all elements in s that satisfy predicate p.

val partition : (elt -> bool) -> t -> t * t
    partition p s returns a pair of sets (s1, s2), where s1 is the set of all the elements of s
    that satisfy the predicate p, and s2 is the set of all the elements of s that do not satisfy p.

val cardinal : t -> int
    Return the number of elements of a set.

val elements : t -> elt list

```


Return the list of all elements of the given set. The returned list is sorted in increasing order with respect to the ordering `Ord.compare`, where `Ord` is the argument given to `Set.Make[34.3]`.

```
val min_elt : t -> elt
```

Return the smallest element of the given set (with respect to the `Ord.compare` ordering), or raise `Not_found` if the set is empty.

```
val max_elt : t -> elt
```

Same as `Set.S.min_elt[34.2]`, but returns the largest element of the given set.

```
val choose : t -> elt
```

Return one element of the given set, or raise `Not_found` if the set is empty. Which element is chosen is unspecified, but equal elements will be chosen for equal sets.

```
end
```

34.3 Module `Set.Make` : Functor building an implementation of the set structure given a totally ordered type.

```
module Make : sig
```

```
  Parameters:
```

- `Ord` : `Set.OrderedType`

```
end
```

35 Module `Sort` : Sorting and merging lists.

This module is obsolete and exists only for backward compatibility. The sorting functions in `Array[2]` and `List[19]` should be used instead. The new functions are faster and use less memory. Sorting and merging lists.

```
val list : ('a -> 'a -> bool) -> 'a list -> 'a list
```

Sort a list in increasing order according to an ordering predicate. The predicate should return `true` if its first argument is less than or equal to its second argument.

```
val array : ('a -> 'a -> bool) -> 'a array -> unit
```

Sort an array in increasing order according to an ordering predicate. The predicate should return `true` if its first argument is less than or equal to its second argument. The array is sorted in place.

```
val merge : ('a -> 'a -> bool) -> 'a list -> 'a list -> 'a list
```

Merge two lists according to the given predicate. Assuming the two argument lists are sorted according to the predicate, `merge` returns a sorted list containing the elements from the two lists. The behavior is undefined if the two argument lists were not sorted.

36 Module Stack : Last-in first-out stacks.

This module implements stacks (LIFOs), with in-place modification.

`type 'a t`

The type of stacks containing elements of type `'a`.

`exception Empty`

Raised when `Stack.pop[36]` or `Stack.top[36]` is applied to an empty stack.

`val create : unit -> 'a t`

Return a new stack, initially empty.

`val push : 'a -> 'a t -> unit`

`push x s` adds the element `x` at the top of stack `s`.

`val pop : 'a t -> 'a`

`pop s` removes and returns the topmost element in stack `s`, or raises `Empty` if the stack is empty.

`val top : 'a t -> 'a`

`top s` returns the topmost element in stack `s`, or raises `Empty` if the stack is empty.

`val clear : 'a t -> unit`

Discard all elements from a stack.

`val copy : 'a t -> 'a t`

Return a copy of the given stack.

`val is_empty : 'a t -> bool`

Return `true` if the given stack is empty, `false` otherwise.

`val length : 'a t -> int`

Return the number of elements in a stack.

`val iter : ('a -> unit) -> 'a t -> unit`

`iter f s` applies `f` in turn to all elements of `s`, from the element at the top of the stack to the element at the bottom of the stack. The stack itself is unchanged.

37 Module StdLabels : Standard labeled libraries.

This meta-module provides labeled version of the `Array`[2], `List`[19] and `String`[39] modules.

They only differ by their labels. Detailed interfaces can be found in `arrayLabels.mli`, `listLabels.mli` and `stringLabels.mli`.

```
module Array : sig end
[37.1]
module List : sig end
[37.2]
module String : sig end
[37.3]
```

37.1 Module StdLabels.Array

```
module Array : sig

  val length : 'a array -> int
  val get : 'a array -> int -> 'a
  val set : 'a array -> int -> 'a -> unit
  val make : int -> 'a -> 'a array
  val create : int -> 'a -> 'a array
  val init : int -> f:(int -> 'a) -> 'a array
  val make_matrix : dimx:int -> dimy:int -> 'a -> 'a array array
  val create_matrix : dimx:int -> dimy:int -> 'a -> 'a array array
  val append : 'a array -> 'a array -> 'a array
  val concat : 'a array list -> 'a array
  val sub : 'a array -> pos:int -> len:int -> 'a array
  val copy : 'a array -> 'a array
  val fill : 'a array -> pos:int -> len:int -> 'a -> unit
  val blit :
    src:'a array -> src_pos:int -> dst:'a array -> dst_pos:int -> len:int -> unit
  val to_list : 'a array -> 'a list
  val of_list : 'a list -> 'a array
  val iter : f:( 'a -> unit) -> 'a array -> unit
  val map : f:( 'a -> 'b) -> 'a array -> 'b array
  val iteri : f:(int -> 'a -> unit) -> 'a array -> unit
  val mapi : f:(int -> 'a -> 'b) -> 'a array -> 'b array
  val fold_left : f:( 'a -> 'b -> 'a) -> init:'a -> 'b array -> 'a
  val fold_right : f:( 'a -> 'b -> 'b) -> 'a array -> init:'b -> 'b

end
```

```

val sort : cmp:( 'a -> 'a -> int) -> 'a array -> unit
val stable_sort : cmp:( 'a -> 'a -> int) -> 'a array -> unit
val unsafe_get : 'a array -> int -> 'a
val unsafe_set : 'a array -> int -> 'a -> unit
end

```

37.2 Module StdLabels.List

```

module List : sig

  val length : 'a list -> int
  val hd : 'a list -> 'a
  val tl : 'a list -> 'a list
  val nth : 'a list -> int -> 'a
  val rev : 'a list -> 'a list
  val append : 'a list -> 'a list -> 'a list
  val rev_append : 'a list -> 'a list -> 'a list
  val concat : 'a list list -> 'a list
  val flatten : 'a list list -> 'a list
  val iter : f:( 'a -> unit) -> 'a list -> unit
  val map : f:( 'a -> 'b) -> 'a list -> 'b list
  val rev_map : f:( 'a -> 'b) -> 'a list -> 'b list
  val fold_left : f:( 'a -> 'b -> 'a) -> init:'a -> 'b list -> 'a
  val fold_right : f:( 'a -> 'b -> 'b) -> 'a list -> init:'b -> 'b
  val iter2 : f:( 'a -> 'b -> unit) -> 'a list -> 'b list -> unit
  val map2 : f:( 'a -> 'b -> 'c) -> 'a list -> 'b list -> 'c list
  val rev_map2 : f:( 'a -> 'b -> 'c) -> 'a list -> 'b list -> 'c list
  val fold_left2 :
    f:( 'a -> 'b -> 'c -> 'a) -> init:'a -> 'b list -> 'c list -> 'a
  val fold_right2 :
    f:( 'a -> 'b -> 'c -> 'c) -> 'a list -> 'b list -> init:'c -> 'c
  val for_all : f:( 'a -> bool) -> 'a list -> bool
  val exists : f:( 'a -> bool) -> 'a list -> bool
  val for_all2 : f:( 'a -> 'b -> bool) -> 'a list -> 'b list -> bool
  val exists2 : f:( 'a -> 'b -> bool) -> 'a list -> 'b list -> bool
  val mem : 'a -> set:'a list -> bool
  val memq : 'a -> set:'a list -> bool
  val find : f:( 'a -> bool) -> 'a list -> 'a
  val filter : f:( 'a -> bool) -> 'a list -> 'a list

```

```

val find_all : f:('a -> bool) -> 'a list -> 'a list
val partition : f:('a -> bool) -> 'a list -> 'a list * 'a list
val assoc : 'a -> ('a * 'b) list -> 'b
val assq : 'a -> ('a * 'b) list -> 'b
val mem_assoc : 'a -> map:('a * 'b) list -> bool
val mem_assq : 'a -> map:('a * 'b) list -> bool
val remove_assoc : 'a -> ('a * 'b) list -> ('a * 'b) list
val remove_assq : 'a -> ('a * 'b) list -> ('a * 'b) list
val split : ('a * 'b) list -> 'a list * 'b list
val combine : 'a list -> 'b list -> ('a * 'b) list
val sort : cmp:('a -> 'a -> int) -> 'a list -> 'a list
val stable_sort : cmp:('a -> 'a -> int) -> 'a list -> 'a list
end

```

37.3 Module StdLabels.String

```

module String : sig

  val length : string -> int
  val get : string -> int -> char
  val set : string -> int -> char -> unit
  val create : int -> string
  val make : int -> char -> string
  val copy : string -> string
  val sub : string -> pos:int -> len:int -> string
  val fill : string -> pos:int -> len:int -> char -> unit
  val blit :
    src:string -> src_pos:int -> dst:string -> dst_pos:int -> len:int -> unit
  val concat : sep:string -> string list -> string
  val iter : f:(char -> unit) -> string -> unit
  val escaped : string -> string
  val index : string -> char -> int
  val rindex : string -> char -> int
  val index_from : string -> int -> char -> int
  val rindex_from : string -> int -> char -> int
  val contains : string -> char -> bool
  val contains_from : string -> int -> char -> bool
  val rcontains_from : string -> int -> char -> bool
  val uppercase : string -> string

```

```

val lowercase : string -> string
val capitalize : string -> string
val uncapitalize : string -> string
val unsafe_get : string -> int -> char
val unsafe_set : string -> int -> char -> unit
val unsafe_blit :
  src:string -> src_pos:int -> dst:string -> dst_pos:int -> len:int -> unit
val unsafe_fill : string -> pos:int -> len:int -> char -> unit
end

```

38 Module Stream : Streams and parsers.

```
type 'a t
```

The type of streams holding values of type 'a.

```
exception Failure
```

Raised by parsers when none of the first components of the stream patterns is accepted.

```
exception Error of string
```

Raised by parsers when the first component of a stream pattern is accepted, but one of the following components is rejected.

Stream builders

Warning: these functions create streams with fast access; it is illegal to mix them with streams built with [`<` `>`]; would raise **Failure** when accessing such mixed streams.

```
val from : (int -> 'a option) -> 'a t
```

Stream.from *f* returns a stream built from the function *f*. To create a new stream element, the function *f* is called with the current stream count. The user function *f* must return either **Some** *<value>* for a value or **None** to specify the end of the stream.

```
val of_list : 'a list -> 'a t
```

Return the stream holding the elements of the list in the same order.

```
val of_string : string -> char t
```

Return the stream of the characters of the string parameter.

```
val of_channel : Pervasives.in_channel -> char t
```

Return the stream of the characters read from the input channel.

Stream iterator

```
val iter : ('a -> unit) -> 'a t -> unit
```

`Stream.iter f s` scans the whole stream `s`, applying function `f` in turn to each stream element encountered.

Predefined parsers

`val next : 'a t -> 'a`

Return the first element of the stream and remove it from the stream. Raise `Stream.Failure` if the stream is empty.

`val empty : 'a t -> unit`

Return `()` if the stream is empty, else raise `Stream.Failure`.

Useful functions

`val peek : 'a t -> 'a option`

Return `Some` of "the first element" of the stream, or `None` if the stream is empty.

`val junk : 'a t -> unit`

Remove the first element of the stream, possibly unfreezing it before.

`val count : 'a t -> int`

Return the current count of the stream elements, i.e. the number of the stream elements discarded.

`val npeek : int -> 'a t -> 'a list`

`npeek n` returns the list of the `n` first elements of the stream, or all its remaining elements if less than `n` elements are available.

39 Module String : String operations.

`val length : string -> int`

Return the length (number of characters) of the given string.

`val get : string -> int -> char`

`String.get s n` returns character number `n` in string `s`. The first character is character number 0. The last character is character number `String.length s - 1`. Raise `Invalid_argument` if `n` is outside the range 0 to `(String.length s - 1)`. You can also write `s.[n]` instead of `String.get s n`.

`val set : string -> int -> char -> unit`

`String.set s n c` modifies string `s` in place, replacing the character number `n` by `c`. Raise `Invalid_argument` if `n` is outside the range 0 to `(String.length s - 1)`. You can also write `s.[n] <- c` instead of `String.set s n c`.

`val create : int -> string`

`String.create n` returns a fresh string of length `n`. The string initially contains arbitrary characters. Raise `Invalid_argument` if `n < 0` or `n > Sys.max_string_length`.

`val make : int -> char -> string`
`String.make n c` returns a fresh string of length `n`, filled with the character `c`. Raise `Invalid_argument` if `n < 0` or `n > Sys.max_string_length[41]`.

`val copy : string -> string`
Return a copy of the given string.

`val sub : string -> int -> int -> string`
`String.sub s start len` returns a fresh string of length `len`, containing the characters number `start` to `start + len - 1` of string `s`. Raise `Invalid_argument` if `start` and `len` do not designate a valid substring of `s`; that is, if `start < 0`, or `len < 0`, or `start + len > String.length[39] s`.

`val fill : string -> int -> int -> char -> unit`
`String.fill s start len c` modifies string `s` in place, replacing the characters number `start` to `start + len - 1` by `c`. Raise `Invalid_argument` if `start` and `len` do not designate a valid substring of `s`.

`val blit : string -> int -> string -> int -> int -> unit`
`String.blit src srcoff dst dstoff len` copies `len` characters from string `src`, starting at character number `srcoff`, to string `dst`, starting at character number `dstoff`. It works correctly even if `src` and `dst` are the same string, and the source and destination chunks overlap. Raise `Invalid_argument` if `srcoff` and `len` do not designate a valid substring of `src`, or if `dstoff` and `len` do not designate a valid substring of `dst`.

`val concat : string -> string list -> string`
`String.concat sep sl` concatenates the list of strings `sl`, inserting the separator string `sep` between each.

`val iter : (char -> unit) -> string -> unit`
`String.iter f s` applies function `f` in turn to all the characters of `s`. It is equivalent to `f s.(0); f s.(1); ...; f s.(String.length s - 1); ()`.

`val escaped : string -> string`
Return a copy of the argument, with special characters represented by escape sequences, following the lexical conventions of Objective Caml. If there is no special character in the argument, return the original string itself, not a copy.

`val index : string -> char -> int`
`String.index s c` returns the position of the leftmost occurrence of character `c` in string `s`. Raise `Not_found` if `c` does not occur in `s`.


```

val rindex : string -> char -> int
    String.rindex s c returns the position of the rightmost occurrence of character c in string
    s. Raise Not_found if c does not occur in s.

val index_from : string -> int -> char -> int
    Same as String.index[39], but start searching at the character position given as second
    argument. String.index s c is equivalent to String.index_from s 0 c.

val rindex_from : string -> int -> char -> int
    Same as String.rindex[39], but start searching at the character position given as second
    argument. String.rindex s c is equivalent to String.rindex_from s (String.length s
    - 1) c.

val contains : string -> char -> bool
    String.contains s c tests if character c appears in the string s.

val contains_from : string -> int -> char -> bool
    String.contains_from s start c tests if character c appears in the substring of s starting
    from start to the end of s. Raise Invalid_argument if start is not a valid index of s.

val rcontains_from : string -> int -> char -> bool
    String.rcontains_from s stop c tests if character c appears in the substring of s starting
    from the beginning of s to index stop. Raise Invalid_argument if stop is not a valid index
    of s.

val uppercase : string -> string
    Return a copy of the argument, with all lowercase letters translated to uppercase, including
    accented letters of the ISO Latin-1 (8859-1) character set.

val lowercase : string -> string
    Return a copy of the argument, with all uppercase letters translated to lowercase, including
    accented letters of the ISO Latin-1 (8859-1) character set.

val capitalize : string -> string
    Return a copy of the argument, with the first letter set to uppercase.

val uncapitalize : string -> string
    Return a copy of the argument, with the first letter set to lowercase.

type t = string
    An alias for the type of strings.

val compare : t -> t -> int
    The comparison function for strings, with the same specification as
    Pervasives.compare[28]. Along with the type t, this function compare allows the module
    String to be passed as argument to the functors Set.Make[34.3] and Map.Make[21.3].

```

40 Module StringLabels : String operations.

`val length : string -> int`

Return the length (number of characters) of the given string.

`val get : string -> int -> char`

`String.get s n` returns character number `n` in string `s`. The first character is character number 0. The last character is character number `String.length s - 1`. Raise `Invalid_argument` if `n` is outside the range 0 to `(String.length s - 1)`. You can also write `s.[n]` instead of `String.get s n`.

`val set : string -> int -> char -> unit`

`String.set s n c` modifies string `s` in place, replacing the character number `n` by `c`. Raise `Invalid_argument` if `n` is outside the range 0 to `(String.length s - 1)`. You can also write `s.[n] <- c` instead of `String.set s n c`.

`val create : int -> string`

`String.create n` returns a fresh string of length `n`. The string initially contains arbitrary characters. Raise `Invalid_argument` if `n < 0` or `n > Sys.max_string_length`.

`val make : int -> char -> string`

`String.make n c` returns a fresh string of length `n`, filled with the character `c`. Raise `Invalid_argument` if `n < 0` or `n > Sys.max_string_length`[41].

`val copy : string -> string`

Return a copy of the given string.

`val sub : string -> pos:int -> len:int -> string`

`String.sub s start len` returns a fresh string of length `len`, containing the characters number `start` to `start + len - 1` of string `s`. Raise `Invalid_argument` if `start` and `len` do not designate a valid substring of `s`; that is, if `start < 0`, or `len < 0`, or `start + len > StringLabels.length`[40] `s`.

`val fill : string -> pos:int -> len:int -> char -> unit`

`String.fill s start len c` modifies string `s` in place, replacing the characters number `start` to `start + len - 1` by `c`. Raise `Invalid_argument` if `start` and `len` do not designate a valid substring of `s`.

`val blit :`

`src:string -> src_pos:int -> dst:string -> dst_pos:int -> len:int -> unit`

`String.blit src srcoff dst dstoff len` copies `len` characters from string `src`, starting at character number `srcoff`, to string `dst`, starting at character number `dstoff`. It works correctly even if `src` and `dst` are the same string, and the source and destination chunks overlap. Raise `Invalid_argument` if `srcoff` and `len` do not designate a valid substring of `src`, or if `dstoff` and `len` do not designate a valid substring of `dst`.

val concat : `sep:string -> string list -> string`
String.concat `sep sl` concatenates the list of strings `sl`, inserting the separator string `sep` between each.

val iter : `f:(char -> unit) -> string -> unit`
String.iter `f s` applies function `f` in turn to all the characters of `s`. It is equivalent to `f s.(0); f s.(1); ...; f s.(String.length s - 1); ()`.

val escaped : `string -> string`
Return a copy of the argument, with special characters represented by escape sequences, following the lexical conventions of Objective Caml. If there is no special character in the argument, return the original string itself, not a copy.

val index : `string -> char -> int`
String.index `s c` returns the position of the leftmost occurrence of character `c` in string `s`. Raise `Not_found` if `c` does not occur in `s`.

val rindex : `string -> char -> int`
String.rindex `s c` returns the position of the rightmost occurrence of character `c` in string `s`. Raise `Not_found` if `c` does not occur in `s`.

val index_from : `string -> int -> char -> int`
Same as **StringLabels.index**[40], but start searching at the character position given as second argument. **String.index** `s c` is equivalent to **String.index_from** `s 0 c`.

val rindex_from : `string -> int -> char -> int`
Same as **StringLabels.rindex**[40], but start searching at the character position given as second argument. **String.rindex** `s c` is equivalent to **String.rindex_from** `s (String.length s - 1) c`.

val contains : `string -> char -> bool`
String.contains `s c` tests if character `c` appears in the string `s`.

val contains_from : `string -> int -> char -> bool`
String.contains_from `s start c` tests if character `c` appears in the substring of `s` starting from `start` to the end of `s`. Raise `Invalid_argument` if `start` is not a valid index of `s`.

val rcontains_from : `string -> int -> char -> bool`
String.rcontains_from `s stop c` tests if character `c` appears in the substring of `s` starting from the beginning of `s` to index `stop`. Raise `Invalid_argument` if `stop` is not a valid index of `s`.

val uppercase : `string -> string`
Return a copy of the argument, with all lowercase letters translated to uppercase, including accented letters of the ISO Latin-1 (8859-1) character set.

val lowercase : string -> string

Return a copy of the argument, with all uppercase letters translated to lowercase, including accented letters of the ISO Latin-1 (8859-1) character set.

val capitalize : string -> string

Return a copy of the argument, with the first letter set to uppercase.

val uncapitalize : string -> string

Return a copy of the argument, with the first letter set to lowercase.

41 Module Sys : System interface.

val argv : string array

The command line arguments given to the process. The first element is the command name used to invoke the program. The following elements are the command-line arguments given to the program.

val executable_name : string

The name of the file containing the executable currently running.

val file_exists : string -> bool

Test if a file with the given name exists.

val remove : string -> unit

Remove the given file name from the file system.

val rename : string -> string -> unit

Rename a file. The first argument is the old name and the second is the new name.

val getenv : string -> string

Return the value associated to a variable in the process environment. Raise `Not_found` if the variable is unbound.

val command : string -> int

Execute the given shell command and return its exit code.

val time : unit -> float

Return the processor time, in seconds, used by the program since the beginning of execution.

val chdir : string -> unit

Change the current working directory of the process.

val getcwd : unit -> string

Return the current working directory of the process.

val readdir : string -> string array

Return the names of all files present in the given directory. Names denoting the current directory and the parent directory (".", ".." in Unix) are not returned. Each string in the result is a file name rather than a complete path. There is no guarantee that the name strings in the resulting array will appear in any specific order; they are not, in particular, guaranteed to appear in alphabetical order.

val interactive : bool Pervasives.ref

This reference is initially set to **false** in standalone programs and to **true** if the code is being executed under the interactive toplevel system **ocaml**.

val os_type : string

Operating system currently executing the Caml program. One of

- "Unix" (for all Unix versions, including Linux and Mac OS X),
- "Win32" (for MS-Windows, OCaml compiled with MSVC++ or Mingw),
- "Cygwin" (for MS-Windows, OCaml compiled with Cygwin),
- "MacOS" (for MacOS 9).

val word_size : int

Size of one word on the machine currently executing the Caml program, in bits: 32 or 64.

val max_string_length : int

Maximum length of a string.

val max_array_length : int

Maximum length of an array.

Signal handling

type signal_behavior =

| **Signal_default**
| **Signal_ignore**
| **Signal_handle** of (int -> unit)

What to do when receiving a signal:

- **Signal_default**: take the default behavior (usually: abort the program)
- **Signal_ignore**: ignore the signal
- **Signal_handle f**: call function **f**, giving it the signal number as argument.

val signal : int -> signal_behavior -> signal_behavior

Set the behavior of the system on receipt of a given signal. The first argument is the signal number. Return the behavior previously associated with the signal.

`val set_signal : int -> signal_behavior -> unit`
Same as `Sys.signal`[41] but return value is ignored.

Signal numbers for the standard POSIX signals.

`val sigabrt : int`
Abnormal termination

`val sigalrm : int`
Timeout

`val sigfpe : int`
Arithmetic exception

`val sighup : int`
Hangup on controlling terminal

`val sigill : int`
Invalid hardware instruction

`val sigint : int`
Interactive interrupt (ctrl-C)

`val sigkill : int`
Termination (cannot be ignored)

`val sigpipe : int`
Broken pipe

`val sigquit : int`
Interactive termination

`val sigsegv : int`
Invalid memory reference

`val sigterm : int`
Termination

`val sigusr1 : int`
Application-defined signal 1

`val sigusr2 : int`
Application-defined signal 2

`val sigchld : int`
Child process terminated

```

val sigcont : int
    Continue

val sigstop : int
    Stop

val sigtstp : int
    Interactive stop

val sigttin : int
    Terminal read from background process

val sigttou : int
    Terminal write from background process

val sigvtalrm : int
    Timeout in virtual time

val sigprof : int
    Profiling interrupt

exception Break
    Exception raised on interactive interrupt if Sys.catch_break[41] is on.

val catch_break : bool -> unit
    catch_break governs whether interactive interrupt (ctrl-C) terminates the program or raises
    the Break exception. Call catch_break true to enable raising Break, and catch_break
    false to let the system terminate the program on user interrupt.

val ocaml_version : string
    ocaml_version is the version of Objective Caml. It is a string of the form
    "major.minor[additional-info]" Where major and minor are integers, and
    additional-info is a string that is empty or starts with a '+'.

```

42 Module Weak : Arrays of weak pointers and hash tables of weak pointers.

Low-level functions

```
type 'a t
```

The type of arrays of weak pointers (weak arrays). A weak pointer is a value that the garbage collector may erase at any time. A weak pointer is said to be full if it points to a value, empty if the value was erased by the GC. Note that weak arrays cannot be marshaled using `Pervasives.output_value`[28] or the functions of the `Marshal`[22] module.

```

val create : int -> 'a t
    Weak.create n returns a new weak array of length n. All the pointers are initially empty.
    Raise Invalid_argument if n is negative or greater than Sys.max_array_length[41]-1.

val length : 'a t -> int
    Weak.length ar returns the length (number of elements) of ar.

val set : 'a t -> int -> 'a option -> unit
    Weak.set ar n (Some el) sets the nth cell of ar to be a (full) pointer to el; Weak.set ar
    n None sets the nth cell of ar to empty. Raise Invalid_argument "Weak.set" if n is not in
    the range 0 to Weak.length[42] a - 1.

val get : 'a t -> int -> 'a option
    Weak.get ar n returns None if the nth cell of ar is empty, Some x (where x is the value) if
    it is full. Raise Invalid_argument "Weak.get" if n is not in the range 0 to Weak.length[42]
    a - 1.

val get_copy : 'a t -> int -> 'a option
    Weak.get_copy ar n returns None if the nth cell of ar is empty, Some x (where x is a
    (shallow) copy of the value) if it is full. In addition to pitfalls with mutable values, the
    interesting difference with get is that get_copy does not prevent the incremental GC from
    erasing the value in its current cycle (get may delay the erasure to the next GC cycle).
    Raise Invalid_argument "Weak.get" if n is not in the range 0 to Weak.length[42] a - 1.

val check : 'a t -> int -> bool
    Weak.check ar n returns true if the nth cell of ar is full, false if it is empty. Note that
    even if Weak.check ar n returns true, a subsequent Weak.get[42] ar n can return None.

val fill : 'a t -> int -> int -> 'a option -> unit
    Weak.fill ar ofs len el sets to el all pointers of ar from ofs to ofs + len - 1. Raise
    Invalid_argument "Weak.fill" if ofs and len do not designate a valid subarray of a.

val blit : 'a t -> int -> 'a t -> int -> int -> unit
    Weak.blit ar1 off1 ar2 off2 len copies len weak pointers from ar1 (starting at off1)
    to ar2 (starting at off2). It works correctly even if ar1 and ar2 are the same. Raise
    Invalid_argument "Weak.blit" if off1 and len do not designate a valid subarray of ar1,
    or if off2 and len do not designate a valid subarray of ar2.

```

Weak hash tables

A weak hash table is a hashed set of values. Each value may magically disappear from the set when it is not used by the rest of the program any more. This is normally used to share data structures without inducing memory leaks. Weak hash tables are defined on values from a `Hashtbl.HashedType`[14.1] module; the `equal` relation and `hash` function are taken from that module. We will say that `v` is an instance of `x` if `equal x v` is `true`.

The `equal` relation must be able to work on a shallow copy of the values and give the same result as with the value itself.


```

module type S = sig end
[42.1]
module Make : functor (H : Hashtbl.Hashtype) -> sig end
[42.2]

```

42.1 Module type `Weak.S` : The output signature of the functor `Weak.Make`[42.2].

```

module type S = sig

  type data
    The type of the elements stored in the table.

  type t
    The type of tables that contain elements of type data. Note that weak hash tables cannot be
    marshaled using Pervasives.output_value[28] or the functions of the Marshal[22] module.

  val create : int -> t
    create n creates a new empty weak hash table, of initial size n. The table will grow as
    needed.

  val clear : t -> unit
    Remove all elements from the table.

  val merge : t -> data -> data
    merge t x returns an instance of x found in t if any, or else adds x to t and return x.

  val add : t -> data -> unit
    add t x adds x to t. If there is already an instance of x in t, it is unspecified which one will
    be returned by subsequent calls to find and merge.

  val remove : t -> data -> unit
    remove t x removes from t one instance of x. Does nothing if there is no instance of x in t.

  val find : t -> data -> data
    find t x returns an instance of x found in t. Raise Not_found if there is no such element.

  val find_all : t -> data -> data list
    find_all t x returns a list of all the instances of x found in t.

  val mem : t -> data -> bool
    mem t x returns true if there is at least one instance of x in t, false otherwise.

  val iter : (data -> unit) -> t -> unit
    iter f t calls f on each element of t, in some unspecified order. It is not specified what
    happens if f tries to change t itself.

```

```

val fold : (data -> 'a -> 'a) -> t -> 'a -> 'a
    fold f t init computes (f d1 (... (f dN init))) where d1 ... dN are the elements
    of t in some unspecified order. It is not specified what happens if f tries to change t itself.

val count : t -> int
    Count the number of elements in the table. count t gives the same result as fold (fun _ n
    -> n+1) t 0 but does not delay the deallocation of the dead elements.

val stats : t -> int * int * int * int * int * int
    Return statistics on the table. The numbers are, in order: table length, number of entries,
    sum of bucket lengths, smallest bucket length, median bucket length, biggest bucket length.

end

```

42.2 Module Weak.Make : Functor building an implementation of the weak hash table structure.

```

module Make : sig
    Parameters:
        • H : Hashtbl.HashedType

end

```

43 Module Unix : Interface to the Unix system

Error report

```

type error =
    | E2BIG
        Argument list too long
    | EACCES
        Permission denied
    | EAGAIN
        Resource temporarily unavailable; try again
    | EBADF
        Bad file descriptor
    | EBUSY
        Resource unavailable
    | ECHILD
        No child process

```

EDEADLK	Resource deadlock would occur
EDOM	Domain error for math functions, etc.
EEXIST	File exists
EFAULT	Bad address
EFBIG	File too large
EINTR	Function interrupted by signal
EINVAL	Invalid argument
EIO	Hardware I/O error
EISDIR	Is a directory
EMFILE	Too many open files by the process
EMLINK	Too many links
ENAMETOOLONG	Filename too long
ENFILE	Too many open files in the system
ENODEV	No such device
ENOENT	No such file or directory
ENOEXEC	Not an executable file
ENOLCK	No locks available
ENOMEM	

	Not enough memory
ENOSPC	No space left on device
ENOSYS	Function not supported
ENOTDIR	Not a directory
ENOTEMPTY	Directory not empty
ENOTTY	Inappropriate I/O control operation
ENXIO	No such device or address
EPERM	Operation not permitted
EPIPE	Broken pipe
ERANGE	Result too large
EROFS	Read-only file system
ESPIPE	Invalid seek e.g. on a pipe
ESRCH	No such process
EXDEV	Invalid link
EWOULDBLOCK	Operation would block
EINPROGRESS	Operation now in progress
EALREADY	Operation already in progress
ENOTSOCK	Socket operation on non-socket

EDESTADDRREQ	Destination address required
EMSGSIZE	Message too long
EPROTOTYPE	Protocol wrong type for socket
ENOPROTOOPT	Protocol not available
EPROTONOSUPPORT	Protocol not supported
ESOCKTNOSUPPORT	Socket type not supported
EOPNOTSUPP	Operation not supported on socket
EPFNOSUPPORT	Protocol family not supported
EAFNOSUPPORT	Address family not supported by protocol family
EADDRINUSE	Address already in use
EADDRNOTAVAIL	Can't assign requested address
ENETDOWN	Network is down
ENETUNREACH	Network is unreachable
ENETRESET	Network dropped connection on reset
ECONNABORTED	Software caused connection abort
ECONNRESET	Connection reset by peer
ENOBUFS	No buffer space available
EISCONN	

	Socket is already connected
ENOTCONN	
	Socket is not connected
ESHUTDOWN	
	Can't send after socket shutdown
ETOOMANYREFS	
	Too many references: can't splice
ETIMEDOUT	
	Connection timed out
ECONNREFUSED	
	Connection refused
EHOSTDOWN	
	Host is down
EHOSTUNREACH	
	No route to host
ELOOP	
	Too many levels of symbolic links
EOVERFLOW	
	File size or position not representable
EUNKNOWNERR of int	
	Unknown error

The type of error codes. Errors defined in the POSIX standard and additional errors from UNIX98 and BSD. All other errors are mapped to EUNKNOWNERR.

exception Unix_error of (error * string * string)

Raised by the system calls below when an error is encountered. The first component is the error code; the second component is the function name; the third component is the string parameter to the function, if it has one, or the empty string otherwise.

val error_message : error -> string

Return a string describing the given error code.

val handle_unix_error : ('a -> 'b) -> 'a -> 'b

handle_unix_error f x applies **f** to **x** and returns the result. If the exception **Unix_error** is raised, it prints a message describing the error and exits with code 2.

Access to the process environment

val environment : unit -> string array

Return the process environment, as an array of strings with the format “variable=value”.

```

val getenv : string -> string
    Return the value associated to a variable in the process environment. Raise Not_found if the
    variable is unbound. (This function is identical to Sys.getenv.)

val putenv : string -> string -> unit
    Unix.putenv name value sets the value associated to a variable in the process environment.
    name is the name of the environment variable, and value its new associated value.

    Process handling
type process_status =
    | WEXITED of int
        The process terminated normally by exit; the argument is the return code.
    | WSIGNALED of int
        The process was killed by a signal; the argument is the signal number.
    | WSTOPPED of int
        The process was stopped by a signal; the argument is the signal number.
    The termination status of a process.

type wait_flag =
    | WNOHANG
        do not block if no child has died yet, but immediately return with a pid equal to 0.
    | WUNTRACED
        report also the children that receive stop signals.
    Flags for Unix.waitpid[43].

val execv : string -> string array -> unit
    execv prog args execute the program in file prog, with the arguments args, and the
    current process environment.

val execve : string -> string array -> string array -> unit
    Same as Unix.execv[43], except that the third argument provides the environment to the
    program executed.

val execvp : string -> string array -> unit
    Same as Unix.execv[43] respectively, except that the program is searched in the path.

val execvpe : string -> string array -> string array -> unit
    Same as Unix.execvp[43] respectively, except that the program is searched in the path.

val fork : unit -> int
    Fork a new process. The returned integer is 0 for the child process, the pid of the child
    process for the parent process.

```

val wait : unit -> int * process_status

Wait until one of the children processes die, and return its pid and termination status.

val waitpid : wait_flag list -> int -> int * process_status

Same as `Unix.wait[43]`, but waits for the process whose pid is given. A pid of -1 means wait for any child. A pid of 0 means wait for any child in the same process group as the current process. Negative pid arguments represent process groups. The list of options indicates whether `waitpid` should return immediately without waiting, or also report stopped children.

val system : string -> process_status

Execute the given command, wait until it terminates, and return its termination status. The string is interpreted by the shell `/bin/sh` and therefore can contain redirections, quotes, variables, etc. The result `WEXITED 127` indicates that the shell couldn't be executed.

val getpid : unit -> int

Return the pid of the process.

val getppid : unit -> int

Return the pid of the parent process.

val nice : int -> int

Change the process priority. The integer argument is added to the “nice” value. (Higher values of the “nice” value mean lower priorities.) Return the new nice value.

Basic file input/output

type file_descr

The abstract type of file descriptors.

val stdin : file_descr

File descriptor for standard input.

val stdout : file_descr

File descriptor for standard output.

val stderr : file_descr

File descriptor for standard standard error.

type open_flag =

| O_RDONLY

Open for reading

| O_WRONLY

Open for writing

| O_RDWR


```

        Open for reading and writing
| O_NONBLOCK
        Open in non-blocking mode
| O_APPEND
        Open for append
| O_CREAT
        Create if nonexistent
| O_TRUNC
        Truncate to 0 length if existing
| O_EXCL
        Fail if existing
| O_NOCTTY
        Don't make this dev a controlling tty
| O_DSYNC
        Writes complete as 'Synchronised I/O data integrity completion'
| O_SYNC
        Writes complete as 'Synchronised I/O file integrity completion'
| O_RSYNC
        Reads complete as writes (depending on O_SYNC/O_DSYNC)
        The flags to Unix.openfile[43].

type file_perm = int
    The type of file access rights.

val openfile : string -> open_flag list -> file_perm -> file_descr
    Open the named file with the given flags. Third argument is the permissions to give to the
    file if it is created. Return a file descriptor on the named file.

val close : file_descr -> unit
    Close a file descriptor.

val read : file_descr -> string -> int -> int -> int
    read fd buff ofs len reads len characters from descriptor fd, storing them in string
    buff, starting at position ofs in string buff. Return the number of characters actually read.

val write : file_descr -> string -> int -> int -> int
    write fd buff ofs len writes len characters to descriptor fd, taking them from string
    buff, starting at position ofs in string buff. Return the number of characters actually
    written.

```

Interfacing with the standard input/output library

```
val in_channel_of_descr : file_descr -> Pervasives.in_channel
```

Create an input channel reading from the given descriptor. The channel is initially in binary mode; use `set_binary_mode_in ic false` if text mode is desired.

```
val out_channel_of_descr : file_descr -> Pervasives.out_channel
```

Create an output channel writing on the given descriptor. The channel is initially in binary mode; use `set_binary_mode_out oc false` if text mode is desired.

```
val descr_of_in_channel : Pervasives.in_channel -> file_descr
```

Return the descriptor corresponding to an input channel.

```
val descr_of_out_channel : Pervasives.out_channel -> file_descr
```

Return the descriptor corresponding to an output channel.

Seeking and truncating

```
type seek_command =
```

```
| SEEK_SET
```

indicates positions relative to the beginning of the file

```
| SEEK_CUR
```

indicates positions relative to the current position

```
| SEEK_END
```

indicates positions relative to the end of the file

Positioning modes for `Unix.lseek`[43].

```
val lseek : file_descr -> int -> seek_command -> int
```

Set the current position for a file descriptor

```
val truncate : string -> int -> unit
```

Truncates the named file to the given size.

```
val ftruncate : file_descr -> int -> unit
```

Truncates the file corresponding to the given descriptor to the given size.

File statistics

```
type file_kind =
```

```
| S_REG
```

Regular file

```
| S_DIR
```

Directory

```
| S_CHR
```

Character device

```

| S_BLK
    Block device

| S_LNK
    Symbolic link

| S_FIFO
    Named pipe

| S SOCK
    Socket

type stats = {
    st_dev : int ;
        Device number

    st_ino : int ;
        Inode number

    st_kind : file_kind ;
        Kind of the file

    st_perm : file_perm ;
        Access rights

    st_nlink : int ;
        Number of links

    st_uid : int ;
        User id of the owner

    st_gid : int ;
        Group ID of the file's group

    st_rdev : int ;
        Device minor number

    st_size : int ;
        Size in bytes

    st_atime : float ;
        Last access time

    st_mtime : float ;
        Last modification time

    st_ctime : float ;
        Last status change time
}

```

The informations returned by the `Unix.stat`^[43] calls.

```

val stat : string -> stats
    Return the informations for the named file.

val lstat : string -> stats
    Same as Unix.stat[43], but in case the file is a symbolic link, return the informations for
    the link itself.

val fstat : file_descr -> stats
    Return the informations for the file associated with the given descriptor.

File operations on large files
module LargeFile : sig end
[43.1]
Operations on file names
val unlink : string -> unit
    Removes the named file

val rename : string -> string -> unit
    rename old new changes the name of a file from old to new.

val link : string -> string -> unit
    link source dest creates a hard link named dest to the file named source.

File permissions and ownership
type access_permission =
| R_OK
    Read permission
| W_OK
    Write permission
| X_OK
    Execution permission
| F_OK
    File exists
    Flags for the Unix.access[43] call.

val chmod : string -> file_perm -> unit
    Change the permissions of the named file.

val fchmod : file_descr -> file_perm -> unit
    Change the permissions of an opened file.

val chown : string -> int -> int -> unit

```

Change the owner uid and owner gid of the named file.

```
val fchown : file_descr -> int -> int -> unit
```

Change the owner uid and owner gid of an opened file.

```
val umask : int -> int
```

Set the process's file mode creation mask, and return the previous mask.

```
val access : string -> access_permission list -> unit
```

Check that the process has the given permissions over the named file. Raise `Unix_error` otherwise.

Operations on file descriptors

```
val dup : file_descr -> file_descr
```

Return a new file descriptor referencing the same file as the given descriptor.

```
val dup2 : file_descr -> file_descr -> unit
```

`dup2 fd1 fd2` duplicates `fd1` to `fd2`, closing `fd2` if already opened.

```
val set_nonblock : file_descr -> unit
```

Set the “non-blocking” flag on the given descriptor. When the non-blocking flag is set, reading on a descriptor on which there is temporarily no data available raises the `EAGAIN` or `EWOULDBLOCK` error instead of blocking; writing on a descriptor on which there is temporarily no room for writing also raises `EAGAIN` or `EWOULDBLOCK`.

```
val clear_nonblock : file_descr -> unit
```

Clear the “non-blocking” flag on the given descriptor. See `Unix.set_nonblock[43]`.

```
val set_close_on_exec : file_descr -> unit
```

Set the “close-on-exec” flag on the given descriptor. A descriptor with the close-on-exec flag is automatically closed when the current process starts another program with one of the `exec` functions.

```
val clear_close_on_exec : file_descr -> unit
```

Clear the “close-on-exec” flag on the given descriptor. See `Unix.set_close_on_exec[43]`.

Directories

```
val mkdir : string -> file_perm -> unit
```

Create a directory with the given permissions.

```
val rmdir : string -> unit
```

Remove an empty directory.

```
val chdir : string -> unit
```

Change the process working directory.

```

val getcwd : unit -> string
    Return the name of the current working directory.

val chroot : string -> unit
    Change the process root directory.

type dir_handle
    The type of descriptors over opened directories.

val opendir : string -> dir_handle
    Open a descriptor on a directory

val readdir : dir_handle -> string
    Return the next entry in a directory.
    Raises End_of_file when the end of the directory has been reached.

val rewinddir : dir_handle -> unit
    Reposition the descriptor to the beginning of the directory

val closedir : dir_handle -> unit
    Close a directory descriptor.

Pipes and redirections

val pipe : unit -> file_descr * file_descr
    Create a pipe. The first component of the result is opened for reading, that's the exit to the
    pipe. The second component is opened for writing, that's the entrance to the pipe.

val mkfifo : string -> file_perm -> unit
    Create a named pipe with the given permissions.

High-level process and redirection management

val create_process :
    string ->
    string array -> file_descr -> file_descr -> file_descr -> int
    create_process prog args new_stdin new_stdout new_stderr forks a new process that
    executes the program in file prog, with arguments args. The pid of the new process is
    returned immediately; the new process executes concurrently with the current process. The
    standard input and outputs of the new process are connected to the descriptors new_stdin,
    new_stdout and new_stderr. Passing e.g. stdout for new_stdout prevents the redirection
    and causes the new process to have the same standard output as the current process. The
    executable file prog is searched in the path. The new process has the same environment as
    the current process.

```

```

val create_process_env :
  string ->
string array ->
string array -> file_descr -> file_descr -> file_descr -> int
  create_process_env prog args env new_stdin new_stdout new_stderr works as
  Unix.create_process[43], except that the extra argument env specifies the environment
  passed to the program.

val open_process_in : string -> Pervasives.in_channel
  High-level pipe and process management. This function runs the given command in parallel
  with the program. The standard output of the command is redirected to a pipe, which can
  be read via the returned input channel. The command is interpreted by the shell /bin/sh
  (cf. system).

val open_process_out : string -> Pervasives.out_channel
  Same as Unix.open_process_in[43], but redirect the standard input of the command to a
  pipe. Data written to the returned output channel is sent to the standard input of the
  command. Warning: writes on output channels are buffered, hence be careful to call
  Pervasives.flush[28] at the right times to ensure correct synchronization.

val open_process : string -> Pervasives.in_channel * Pervasives.out_channel
  Same as Unix.open_process_out[43], but redirects both the standard input and standard
  output of the command to pipes connected to the two returned channels. The input channel
  is connected to the output of the command, and the output channel to the input of the
  command.

val open_process_full :
  string ->
string array ->
Pervasives.in_channel * Pervasives.out_channel * Pervasives.in_channel
  Similar to Unix.open_process[43], but the second argument specifies the environment
  passed to the command. The result is a triple of channels connected respectively to the
  standard output, standard input, and standard error of the command.

val close_process_in : Pervasives.in_channel -> process_status
  Close channels opened by Unix.open_process_in[43], wait for the associated command to
  terminate, and return its termination status.

val close_process_out : Pervasives.out_channel -> process_status
  Close channels opened by Unix.open_process_out[43], wait for the associated command to
  terminate, and return its termination status.

val close_process :
  Pervasives.in_channel * Pervasives.out_channel -> process_status

```

Close channels opened by `Unix.open_process`[43], wait for the associated command to terminate, and return its termination status.

```
val close_process_full :
```

```
  Pervasives.in_channel * Pervasives.out_channel * Pervasives.in_channel ->
```

```
process_status
```

Close channels opened by `Unix.open_process_full`[43], wait for the associated command to terminate, and return its termination status.

Symbolic links

```
val symlink : string -> string -> unit
```

`symlink source dest` creates the file `dest` as a symbolic link to the file `source`.

```
val readlink : string -> string
```

Read the contents of a link.

Polling

```
val select :
```

```
  file_descr list ->
```

```
file_descr list ->
```

```
file_descr list ->
```

```
float -> file_descr list * file_descr list * file_descr list
```

Wait until some input/output operations become possible on some channels. The three list arguments are, respectively, a set of descriptors to check for reading (first argument), for writing (second argument), or for exceptional conditions (third argument). The fourth argument is the maximal timeout, in seconds; a negative fourth argument means no timeout (unbounded wait). The result is composed of three sets of descriptors: those ready for reading (first component), ready for writing (second component), and over which an exceptional condition is pending (third component).

Locking

```
type lock_command =
```

```
  | F_ULOCK
```

Unlock a region

```
  | F_LOCK
```

Lock a region for writing, and block if already locked

```
  | F_TLOCK
```

Lock a region for writing, or fail if already locked

```
  | F_TEST
```

Test a region for other process locks

```
  | F_RLOCK
```

Lock a region for reading, and block if already locked

| F_TRLOCK

Lock a region for reading, or fail if already locked

Commands for `Unix.lockf`[43].

```
val lockf : file_descr -> lock_command -> int -> unit
```

`lockf fd cmd size` puts a lock on a region of the file opened as `fd`. The region starts at the current read/write position for `fd` (as set by `Unix.lseek`[43]), and extends `size` bytes forward if `size` is positive, `size` bytes backwards if `size` is negative, or to the end of the file if `size` is zero. A write lock (set with `F_LOCK` or `F_TLOCK`) prevents any other process from acquiring a read or write lock on the region. A read lock (set with `F_RLOCK` or `F_TRLOCK`) prevents any other process from acquiring a write lock on the region, but lets other processes acquire read locks on it.

Signals Note: installation of signal handlers is performed via the functions `Sys.signal`[41] and `Sys.set_signal`[41].

```
val kill : int -> int -> unit
```

`kill pid sig` sends signal number `sig` to the process with id `pid`.

```
type sigprocmask_command =  
  | SIG_SETMASK  
  | SIG_BLOCK  
  | SIG_UNBLOCK
```

```
val sigprocmask : sigprocmask_command -> int list -> int list
```

`sigprocmask cmd sigs` changes the set of blocked signals. If `cmd` is `SIG_SETMASK`, blocked signals are set to those in the list `sigs`. If `cmd` is `SIG_BLOCK`, the signals in `sigs` are added to the set of blocked signals. If `cmd` is `SIG_UNBLOCK`, the signals in `sigs` are removed from the set of blocked signals. `sigprocmask` returns the set of previously blocked signals.

```
val sigpending : unit -> int list
```

Return the set of blocked signals that are currently pending.

```
val sigsuspend : int list -> unit
```

`sigsuspend sigs` atomically sets the blocked signals to `sig` and waits for a non-ignored, non-blocked signal to be delivered. On return, the blocked signals are reset to their initial value.

```
val pause : unit -> unit
```

Wait until a non-ignored, non-blocked signal is delivered.

Time functions

```
type process_times = {  
  tms_utime : float ;
```

User time for the process

```
  tms_stime : float ;
```

```

        System time for the process
tms_cstime : float ;
        User time for the children processes
tms_cutime : float ;
        System time for the children processes
}
    The execution times (CPU times) of a process.

```

```

type tm = {
    tm_sec : int ;
        Seconds 0..59
    tm_min : int ;
        Minutes 0..59
    tm_hour : int ;
        Hours 0..23
    tm_mday : int ;
        Day of month 1..31
    tm_mon : int ;
        Month of year 0..11
    tm_year : int ;
        Year - 1900
    tm_wday : int ;
        Day of week (Sunday is 0)
    tm_yday : int ;
        Day of year 0..365
    tm_isdst : bool ;
        Daylight time savings in effect
}

```

The type representing wallclock time and calendar date.

```

val time : unit -> float
    Return the current time since 00:00:00 GMT, Jan. 1, 1970, in seconds.

val gettimeofday : unit -> float
    Same as Unix.time[43], but with resolution better than 1 second.

val gmtime : float -> tm

```

Convert a time in seconds, as returned by `Unix.time`[43], into a date and a time. Assumes UTC (Coordinated Universal Time), also known as GMT.

`val localtime : float -> tm`

Convert a time in seconds, as returned by `Unix.time`[43], into a date and a time. Assumes the local time zone.

`val mktime : tm -> float * tm`

Convert a date and time, specified by the `tm` argument, into a time in seconds, as returned by `Unix.time`[43]. Also return a normalized copy of the given `tm` record, with the `tm_wday`, `tm_yday`, and `tm_isdst` fields recomputed from the other fields. The `tm` argument is interpreted in the local time zone.

`val alarm : int -> int`

Schedule a `SIGALRM` signal after the given number of seconds.

`val sleep : int -> unit`

Stop execution for the given number of seconds.

`val times : unit -> process_times`

Return the execution times of the process.

`val utimes : string -> float -> float -> unit`

Set the last access time (second arg) and last modification time (third arg) for a file. Times are expressed in seconds from 00:00:00 GMT, Jan. 1, 1970.

`type interval_timer =`

`| ITIMER_REAL`

decrements in real time, and sends the signal `SIGALRM` when expired.

`| ITIMER_VIRTUAL`

decrements in process virtual time, and sends `SIGVTALRM` when expired.

`| ITIMER_PROF`

(for profiling) decrements both when the process is running and when the system is running on behalf of the process; it sends `SIGPROF` when expired.

The three kinds of interval timers.

`type interval_timer_status = {`

`it_interval : float ;`

Period

`it_value : float ;`

Current value of the timer

`}`

The type describing the status of an interval timer

```
val getitimer : interval_timer -> interval_timer_status
```

Return the current status of the given interval timer.

```
val setitimer :
```

```
    interval_timer ->
```

```
interval_timer_status -> interval_timer_status
```

`setitimer t s` sets the interval timer `t` and returns its previous status. The `s` argument is interpreted as follows: `s.it_value`, if nonzero, is the time to the next timer expiration; `s.it_interval`, if nonzero, specifies a value to be used in reloading `it_value` when the timer expires. Setting `s.it_value` to zero disable the timer. Setting `s.it_interval` to zero causes the timer to be disabled after its next expiration.

User id, group id

```
val getuid : unit -> int
```

Return the user id of the user executing the process.

```
val geteuid : unit -> int
```

Return the effective user id under which the process runs.

```
val setuid : int -> unit
```

Set the real user id and effective user id for the process.

```
val getgid : unit -> int
```

Return the group id of the user executing the process.

```
val getegid : unit -> int
```

Return the effective group id under which the process runs.

```
val setgid : int -> unit
```

Set the real group id and effective group id for the process.

```
val getgroups : unit -> int array
```

Return the list of groups to which the user executing the process belongs.

```
type passwd_entry = {  
    pw_name : string ;  
    pw_passwd : string ;  
    pw_uid : int ;  
    pw_gid : int ;  
    pw_gecos : string ;  
    pw_dir : string ;  
    pw_shell : string ;  
}
```

Structure of entries in the `passwd` database.

```
type group_entry = {  
  gr_name : string ;  
  gr_passwd : string ;  
  gr_gid : int ;  
  gr_mem : string array ;  
}
```

Structure of entries in the `groups` database.

```
val getlogin : unit -> string
```

Return the login name of the user executing the process.

```
val getpwnam : string -> passwd_entry
```

Find an entry in `passwd` with the given name, or raise `Not_found`.

```
val getgrnam : string -> group_entry
```

Find an entry in `group` with the given name, or raise `Not_found`.

```
val getpwuid : int -> passwd_entry
```

Find an entry in `passwd` with the given user id, or raise `Not_found`.

```
val getgrgid : int -> group_entry
```

Find an entry in `group` with the given group id, or raise `Not_found`.

Internet addresses

```
type inet_addr
```

The abstract type of Internet addresses.

```
val inet_addr_of_string : string -> inet_addr
```

Conversions between string with the format `XXX.YYY.ZZZ.TTT` and Internet addresses.

`inet_addr_of_string` raises `Failure` when given a string that does not match this format.

```
val string_of_inet_addr : inet_addr -> string
```

See `Unix.inet_addr_of_string`[43].

```
val inet_addr_any : inet_addr
```

A special Internet address, for use only with `bind`, representing all the Internet addresses that the host machine possesses.

Sockets

```
type socket_domain =  
| PF_UNIX
```

Unix domain

```

| PF_INET
    Internet domain
    The type of socket domains.

type socket_type =
| SOCK_STREAM
    Stream socket

| SOCK_DGRAM
    Datagram socket

| SOCK_RAW
    Raw socket

| SOCK_SEQPACKET
    Sequenced packets socket
    The type of socket kinds, specifying the semantics of communications.

type sockaddr =
| ADDR_UNIX of string
| ADDR_INET of (inet_addr * int)
    The type of socket addresses. ADDR_UNIX name is a socket address in the Unix domain;
    name is a file name in the file system. ADDR_INET(addr,port) is a socket address in
    the Internet domain; addr is the Internet address of the machine, and port is the port
    number.

val socket : socket_domain -> socket_type -> int -> file_descr
    Create a new socket in the given domain, and with the given kind. The third argument is
    the protocol type; 0 selects the default protocol for that kind of sockets.

val socketpair :
    socket_domain ->
socket_type -> int -> file_descr * file_descr
    Create a pair of unnamed sockets, connected together.

val accept : file_descr -> file_descr * sockaddr
    Accept connections on the given socket. The returned descriptor is a socket connected to the
    client; the returned address is the address of the connecting client.

val bind : file_descr -> sockaddr -> unit
    Bind a socket to an address.

val connect : file_descr -> sockaddr -> unit
    Connect a socket to an address.

val listen : file_descr -> int -> unit

```

Set up a socket for receiving connection requests. The integer argument is the maximal number of pending requests.

```
type shutdown_command =
  | SHUTDOWN_RECEIVE
      Close for receiving
  | SHUTDOWN_SEND
      Close for sending
  | SHUTDOWN_ALL
      Close both
  The type of commands for shutdown.

val shutdown : file_descr -> shutdown_command -> unit
  Shutdown a socket connection. SHUTDOWN_SEND as second argument causes reads on the
  other end of the connection to return an end-of-file condition. SHUTDOWN_RECEIVE causes
  writes on the other end of the connection to return a closed pipe condition (SIGPIPE signal).

val getsockname : file_descr -> sockaddr
  Return the address of the given socket.

val getpeername : file_descr -> sockaddr
  Return the address of the host connected to the given socket.

type msg_flag =
  | MSG_OOB
  | MSG_DONTROUTE
  | MSG_PEEK
  The flags for Unix.recv[43], Unix.recvfrom[43], Unix.send[43] and Unix.sendto[43].

val recv : file_descr -> string -> int -> int -> msg_flag list -> int
  Receive data from a connected socket.

val recvfrom :
  file_descr ->
  string -> int -> int -> msg_flag list -> int * sockaddr
  Receive data from an unconnected socket.

val send : file_descr -> string -> int -> int -> msg_flag list -> int
  Send data over a connected socket.

val sendto :
  file_descr ->
  string -> int -> int -> msg_flag list -> sockaddr -> int
  Send data over an unconnected socket.
```

Socket options

```

type socket_bool_option =
  | SO_DEBUG
      Record debugging information
  | SO_BROADCAST
      Permit sending of broadcast messages
  | SO_REUSEADDR
      Allow reuse of local addresses for bind
  | SO_KEEPAIVE
      Keep connection active
  | SO_DONTROUTE
      Bypass the standard routing algorithms
  | SO_OOBINLINE
      Leave out-of-band data in line
  | SO_ACCEPTCONN
      Report whether socket listening is enabled

```

The socket options that can be consulted with `Unix.getsockopt[43]` and modified with `Unix.setsockopt[43]`. These options have a boolean (`true/false`) value.

```

type socket_int_option =
  | SO_SNDBUF
      Size of send buffer
  | SO_RCVBUF
      Size of received buffer
  | SO_ERROR
      Report the error status and clear it
  | SO_TYPE
      Report the socket type
  | SO_RCVLOWAT
      Minimum number of bytes to process for input operations
  | SO_SNDLOWAT
      Minimum number of bytes to process for output operations

```

The socket options that can be consulted with `Unix.getsockopt_int[43]` and modified with `Unix.setsockopt_int[43]`. These options have an integer value.

```

type socket_optint_option =
  | SO_LINGER

```


Whether to linger on closed connections that have data present, and for how long (in seconds)

The socket options that can be consulted with `Unix.getsockopt_optint`[43] and modified with `Unix.setsockopt_optint`[43]. These options have a value of type `int option`, with `None` meaning “disabled”.

```
type socket_float_option =  
  | SO_RCVTIMEO
```

Timeout for input operations

```
  | SO_SNDTIMEO
```

Timeout for output operations

The socket options that can be consulted with `Unix.getsockopt_float`[43] and modified with `Unix.setsockopt_float`[43]. These options have a floating-point value representing a time in seconds. The value 0 means infinite timeout.

```
val getsockopt : file_descr -> socket_bool_option -> bool
```

Return the current status of a boolean-valued option in the given socket.

```
val setsockopt : file_descr -> socket_bool_option -> bool -> unit
```

Set or clear a boolean-valued option in the given socket.

```
val getsockopt_int : file_descr -> socket_int_option -> int
```

Same as `Unix.getsockopt`[43] for an integer-valued socket option.

```
val setsockopt_int : file_descr -> socket_int_option -> int -> unit
```

Same as `Unix.setsockopt`[43] for an integer-valued socket option.

```
val getsockopt_optint : file_descr -> socket_optint_option -> int option
```

Same as `Unix.getsockopt`[43] for a socket option whose value is an `int option`.

```
val setsockopt_optint :
```

```
  file_descr -> socket_optint_option -> int option -> unit
```

Same as `Unix.setsockopt`[43] for a socket option whose value is an `int option`.

```
val getsockopt_float : file_descr -> socket_float_option -> float
```

Same as `Unix.getsockopt`[43] for a socket option whose value is a floating-point number.

```
val setsockopt_float : file_descr -> socket_float_option -> float -> unit
```

Same as `Unix.setsockopt`[43] for a socket option whose value is a floating-point number.

High-level network connection functions

```
val open_connection :
```

```
  sockaddr -> Pervasives.in_channel * Pervasives.out_channel
```

Connect to a server at the given address. Return a pair of buffered channels connected to the server. Remember to call `Pervasives.flush`[28] on the output channel at the right times to ensure correct synchronization.

```
val shutdown_connection : Pervasives.in_channel -> unit
```

“Shut down” a connection established with `Unix.open_connection`[43]; that is, transmit an end-of-file condition to the server reading on the other side of the connection.

```
val establish_server :
```

```
(Pervasives.in_channel -> Pervasives.out_channel -> unit) ->
```

```
sockaddr -> unit
```

Establish a server on the given address. The function given as first argument is called for each connection with two buffered channels connected to the client. A new process is created for each connection. The function `Unix.establish_server`[43] never returns normally.

Host and protocol databases

```
type host_entry = {  
  h_name : string ;  
  h_aliases : string array ;  
  h_addrtype : socket_domain ;  
  h_addr_list : inet_addr array ;  
}
```

Structure of entries in the `hosts` database.

```
type protocol_entry = {  
  p_name : string ;  
  p_aliases : string array ;  
  p_proto : int ;  
}
```

Structure of entries in the `protocols` database.

```
type service_entry = {  
  s_name : string ;  
  s_aliases : string array ;  
  s_port : int ;  
  s_proto : string ;  
}
```

Structure of entries in the `services` database.

```
val gethostname : unit -> string
```

Return the name of the local host.

```
val gethostbyname : string -> host_entry
```

Find an entry in `hosts` with the given name, or raise `Not_found`.

```
val gethostbyaddr : inet_addr -> host_entry
```

Find an entry in `hosts` with the given address, or raise `Not_found`.

```
val getprotobyname : string -> protocol_entry
```

Find an entry in `protocols` with the given name, or raise `Not_found`.

```
val getprotobynumber : int -> protocol_entry
```

Find an entry in `protocols` with the given protocol number, or raise `Not_found`.

```
val getservbyname : string -> string -> service_entry
```

Find an entry in `services` with the given name, or raise `Not_found`.

```
val getservbyport : int -> string -> service_entry
```

Find an entry in `services` with the given service number, or raise `Not_found`.

Terminal interface

The following functions implement the POSIX standard terminal interface. They provide control over asynchronous communication ports and pseudo-terminals. Refer to the `termios` man page for a complete description.

```
type terminal_io = {
```

```
  mutable c_ignbrk : bool ;
```

Ignore the break condition.

```
  mutable c_brkint : bool ;
```

Signal interrupt on break condition.

```
  mutable c_ignpar : bool ;
```

Ignore characters with parity errors.

```
  mutable c_parmrk : bool ;
```

Mark parity errors.

```
  mutable c_inpck : bool ;
```

Enable parity check on input.

```
  mutable c_istrip : bool ;
```

Strip 8th bit on input characters.

```
  mutable c_inlcr : bool ;
```

Map NL to CR on input.

```
  mutable c_igncr : bool ;
```

Ignore CR on input.

```
  mutable c_icrnl : bool ;
```

Map CR to NL on input.

```
  mutable c_ixon : bool ;
```

Recognize XON/XOFF characters on input.

```

mutable c_ixon : bool ;
    Emit XON/XOFF chars to control input flow.

mutable c_opost : bool ;
    Enable output processing.

mutable c_obaud : int ;
    Output baud rate (0 means close connection).

mutable c_ibaud : int ;
    Input baud rate.

mutable c_csize : int ;
    Number of bits per character (5-8).

mutable c_cstopb : int ;
    Number of stop bits (1-2).

mutable c_cread : bool ;
    Reception is enabled.

mutable c_parenb : bool ;
    Enable parity generation and detection.

mutable c_parodd : bool ;
    Specify odd parity instead of even.

mutable c_hupcl : bool ;
    Hang up on last close.

mutable c_clocal : bool ;
    Ignore modem status lines.

mutable c_isig : bool ;
    Generate signal on INTR, QUIT, SUSP.

mutable c_icanon : bool ;
    Enable canonical processing (line buffering and editing)

mutable c_noflsh : bool ;
    Disable flush after INTR, QUIT, SUSP.

mutable c_echo : bool ;
    Echo input characters.

mutable c_echoe : bool ;
    Echo ERASE (to erase previous character).

mutable c_echok : bool ;
    Echo KILL (to erase the current line).

mutable c_echonl : bool ;

```

```

        Echo NL even if c_echo is not set.
mutable c_vintr : char ;
        Interrupt character (usually ctrl-C).
mutable c_vquit : char ;
        Quit character (usually ctrl-\\).
mutable c_verase : char ;
        Erase character (usually DEL or ctrl-H).
mutable c_vkill : char ;
        Kill line character (usually ctrl-U).
mutable c_veof : char ;
        End-of-file character (usually ctrl-D).
mutable c_veol : char ;
        Alternate end-of-line char. (usually none).
mutable c_vmin : int ;
        Minimum number of characters to read before the read request is satisfied.
mutable c_vtime : int ;
        Maximum read wait (in 0.1s units).
mutable c_vstart : char ;
        Start character (usually ctrl-Q).
mutable c_vstop : char ;
        Stop character (usually ctrl-S).
}
val tcgetattr : file_descr -> terminal_io
        Return the status of the terminal referred to by the given file descriptor.

type setattr_when =
| TCSANOW
| TCSADRAIN
| TCSAFLUSH
val tcsetattr : file_descr -> setattr_when -> terminal_io -> unit
        Set the status of the terminal referred to by the given file descriptor. The second argument
        indicates when the status change takes place: immediately (TCSANOW), when all pending
        output has been transmitted (TCSADRAIN), or after flushing all input that has been received
        but not read (TCSAFLUSH). TCSADRAIN is recommended when changing the output
        parameters; TCSAFLUSH, when changing the input parameters.

val tcsendbreak : file_descr -> int -> unit

```

Send a break condition on the given file descriptor. The second argument is the duration of the break, in 0.1s units; 0 means standard duration (0.25s).

```
val tcdrain : file_descr -> unit
```

Waits until all output written on the given file descriptor has been transmitted.

```
type flush_queue =  
  | TCIFLUSH  
  | TCOFLUSH  
  | TCIOFLUSH
```

```
val tcflush : file_descr -> flush_queue -> unit
```

Discard data written on the given file descriptor but not yet transmitted, or data received but not yet read, depending on the second argument: **TCIFLUSH** flushes data received but not read, **TCOFLUSH** flushes data written but not transmitted, and **TCIOFLUSH** flushes both.

```
type flow_action =  
  | TCOOFF  
  | TCOON  
  | TCIOFF  
  | TCION
```

```
val tcflow : file_descr -> flow_action -> unit
```

Suspend or restart reception or transmission of data on the given file descriptor, depending on the second argument: **TCOOFF** suspends output, **TCOON** restarts output, **TCIOFF** transmits a STOP character to suspend input, and **TCION** transmits a START character to restart input.

```
val setsid : unit -> int
```

Put the calling process in a new session and detach it from its controlling terminal.

43.1 Module `Unix.LargeFile` : File operations on large files.

```
module LargeFile : sig
```

This sub-module provides 64-bit variants of the functions `Unix.lseek`[43] (for positioning a file descriptor), `Unix.truncate`[43] and `Unix.ftruncate`[43] (for changing the size of a file), and `Unix.stat`[43], `Unix.lstat`[43] and `Unix.fstat`[43] (for obtaining information on files). These alternate functions represent positions and sizes by 64-bit integers (type `int64`) instead of regular integers (type `int`), thus allowing operating on files whose sizes are greater than `max_int`.

```
val lseek : Unix.file_descr -> int64 -> Unix.seek_command -> int64
```

```
val truncate : string -> int64 -> unit
```

```
val ftruncate : Unix.file_descr -> int64 -> unit
```

```
type stats = {  
  st_dev : int ;
```

Device number

```

    st_ino : int ;
        Inode number
    st_kind : Unix.file_kind ;
        Kind of the file
    st_perm : Unix.file_perm ;
        Access rights
    st_nlink : int ;
        Number of links
    st_uid : int ;
        User id of the owner
    st_gid : int ;
        Group ID of the file's group
    st_rdev : int ;
        Device minor number
    st_size : int64 ;
        Size in bytes
    st_atime : float ;
        Last access time
    st_mtime : float ;
        Last modification time
    st_ctime : float ;
        Last status change time
}
val stat : string -> stats
val lstat : string -> stats
val fstat : Unix.file_descr -> stats
end

```

44 Module Str : Regular expressions and high-level string processing

Regular expressions

```
type regexp
```

The type of compiled regular expressions.

```
val regexp : string -> regexp
```

Compile a regular expression. The syntax for regular expressions is the same as in Gnu Emacs. The special characters are `$^.*+?[]`. The following constructs are recognized:

- `.` matches any character except newline
- `*` (postfix) matches the previous expression zero, one or several times
- `+` (postfix) matches the previous expression one or several times
- `?` (postfix) matches the previous expression once or not at all
- `[...]` character set; ranges are denoted with `-`, as in `[a-z]`; an initial `^`, as in `[^0-9]`, complements the set
- `^` matches at beginning of line
- `$` matches at end of line
- `\|` (infix) alternative between two expressions
- `\(...\)` grouping and naming of the enclosed expression
- `\1` the text matched by the first `\(...\)` expression (`\2` for the second expression, and so on up to `\9`)
- `\b` matches word boundaries
- `\` quotes special characters.

`val regexp_case_fold : string -> regexp`

Same as `regexp`, but the compiled expression will match text in a case-insensitive way: uppercase and lowercase letters will be considered equivalent.

`val quote : string -> string`

`Str.quote s` returns a regexp string that matches exactly `s` and nothing else.

`val regexp_string : string -> regexp`

`Str.regexp_string s` returns a regular expression that matches exactly `s` and nothing else.

`val regexp_string_case_fold : string -> regexp`

`Str.regexp_string_case_fold` is similar to `Str.regexp_string`[\[44\]](#), but the regexp matches in a case-insensitive way.

String matching and searching

`val string_match : regexp -> string -> int -> bool`

`string_match r s start` tests whether the characters in `s` starting at position `start` match the regular expression `r`. The first character of a string has position 0, as usual.

`val search_forward : regexp -> string -> int -> int`

`search_forward r s start` searches the string `s` for a substring matching the regular expression `r`. The search starts at position `start` and proceeds towards the end of the string. Return the position of the first character of the matched substring, or raise `Not_found` if no substring matches.


```
val search_backward : regexp -> string -> int -> int
```

Same as `Str.search_forward[44]`, but the search proceeds towards the beginning of the string.

```
val string_partial_match : regexp -> string -> int -> bool
```

Similar to `Str.string_match[44]`, but succeeds whenever the argument string is a prefix of a string that matches. This includes the case of a true complete match.

```
val matched_string : string -> string
```

`matched_string s` returns the substring of `s` that was matched by the latest `Str.string_match[44]`, `Str.search_forward[44]` or `Str.search_backward[44]`. The user must make sure that the parameter `s` is the same string that was passed to the matching or searching function.

```
val match_beginning : unit -> int
```

`match_beginning()` returns the position of the first character of the substring that was matched by `Str.string_match[44]`, `Str.search_forward[44]` or `Str.search_backward[44]`.

```
val match_end : unit -> int
```

`match_end()` returns the position of the character following the last character of the substring that was matched by `string_match`, `search_forward` or `search_backward`.

```
val matched_group : int -> string -> string
```

`matched_group n s` returns the substring of `s` that was matched by the `n`th group `\(...\)` of the regular expression during the latest `Str.string_match[44]`, `Str.search_forward[44]` or `Str.search_backward[44]`. The user must make sure that the parameter `s` is the same string that was passed to the matching or searching function. `matched_group n s` raises `Not_found` if the `n`th group of the regular expression was not matched. This can happen with groups inside alternatives `|`, options `?` or repetitions `*`. For instance, the empty string will match `\(a\)*`, but `matched_group 1 ""` will raise `Not_found` because the first group itself was not matched.

```
val group_beginning : int -> int
```

`group_beginning n` returns the position of the first character of the substring that was matched by the `n`th group of the regular expression.

Raises

- `Not_found` if the `n`th group of the regular expression was not matched.
- `Invalid_argument` if there are fewer than `n` groups in the regular expression.

```
val group_end : int -> int
```

`group_end n` returns the position of the character following the last character of substring that was matched by the `n`th group of the regular expression.

Raises

- `Not_found` if the `nth` group of the regular expression was not matched.
- `Invalid_argument` if there are fewer than `n` groups in the regular expression.

Replacement

`val global_replace : regexp -> string -> string -> string`

`global_replace regexp templ s` returns a string identical to `s`, except that all substrings of `s` that match `regexp` have been replaced by `templ`. The replacement template `templ` can contain `\1`, `\2`, etc; these sequences will be replaced by the text matched by the corresponding group in the regular expression. `\0` stands for the text matched by the whole regular expression.

`val replace_first : regexp -> string -> string -> string`

Same as `Str.global_replace`[44], except that only the first substring matching the regular expression is replaced.

`val global_substitute : regexp -> (string -> string) -> string -> string`

`global_substitute regexp subst s` returns a string identical to `s`, except that all substrings of `s` that match `regexp` have been replaced by the result of function `subst`. The function `subst` is called once for each matching substring, and receives `s` (the whole text) as argument.

`val substitute_first : regexp -> (string -> string) -> string -> string`

Same as `Str.global_substitute`[44], except that only the first substring matching the regular expression is replaced.

`val replace_matched : string -> string -> string`

`replace_matched repl s` returns the replacement text `repl` in which `\1`, `\2`, etc. have been replaced by the text matched by the corresponding groups in the most recent matching operation. `s` must be the same string that was matched during this matching operation.

Splitting

`val split : regexp -> string -> string list`

`split r s` splits `s` into substrings, taking as delimiters the substrings that match `r`, and returns the list of substrings. For instance, `split (regexp "[\t]+") s` splits `s` into blank-separated words. An occurrence of the delimiter at the beginning and at the end of the string is ignored.

`val bounded_split : regexp -> string -> int -> string list`

Same as `Str.split`[44], but splits into at most `n` substrings, where `n` is the extra integer parameter.

`val split_delim : regexp -> string -> string list`

Same as `Str.split`[44] but occurrences of the delimiter at the beginning and at the end of the string are recognized and returned as empty strings in the result. For instance, `split_delim (regexp " ") " abc " returns [""; "abc"; ""], while split with the same arguments returns ["abc"].`

```

val bounded_split_delim : regexp -> string -> int -> string list
    Same as Str.bounded_split[44], but occurrences of the delimiter at the beginning and at
    the end of the string are recognized and returned as empty strings in the result.

type split_result =
  | Text of string
  | Delim of string
val full_split : regexp -> string -> split_result list
    Same as Str.split_delim[44], but returns the delimiters as well as the substrings contained
    between delimiters. The former are tagged Delim in the result list; the latter are tagged
    Text. For instance, full_split (regexp "[{}]" ) "{ab}" returns [Delim "{"; Text
    "ab"; Delim "}"].

val bounded_full_split : regexp -> string -> int -> split_result list
    Same as Str.bounded_split_delim[44], but returns the delimiters as well as the substrings
    contained between delimiters. The former are tagged Delim in the result list; the latter are
    tagged Text.

    Extracting substrings
val string_before : string -> int -> string
    string_before s n returns the substring of all characters of s that precede position n
    (excluding the character at position n).

val string_after : string -> int -> string
    string_after s n returns the substring of all characters of s that follow position n
    (including the character at position n).

val first_chars : string -> int -> string
    first_chars s n returns the first n characters of s. This is the same function as
    Str.string_before[44].

val last_chars : string -> int -> string
    last_chars s n returns the last n characters of s.

```

45 Module Bigarray : Large, multi-dimensional, numerical arrays.

This module implements multi-dimensional arrays of integers and floating-point numbers, thereafter referred to as “big arrays”. The implementation allows efficient sharing of large numerical arrays between Caml code and C or Fortran numerical libraries.

Concerning the naming conventions, users of this module are encouraged to do `open Bigarray` in their source, then refer to array types and operations via short dot notation, e.g. `Array1.t` or `Array2.sub`.

Big arrays support all the Caml ad-hoc polymorphic operations:

- comparisons (`=`, `<>`, `<=`, etc, as well as `Pervasives.compare`[28]);
- hashing (module `Hash`);
- and structured input-output (`Pervasives.output_value`[28] and `Pervasives.input_value`[28], as well as the functions from the `Marshal`[22] module).

Element kinds

Big arrays can contain elements of the following kinds:

- IEEE single precision (32 bits) floating-point numbers (`Bigarray.float32_elt`[45]),
- IEEE double precision (64 bits) floating-point numbers (`Bigarray.float64_elt`[45]),
- IEEE single precision (2 * 32 bits) floating-point complex numbers (`Bigarray.complex32_elt`[45]),
- IEEE double precision (2 * 64 bits) floating-point complex numbers (`Bigarray.complex64_elt`[45]),
- 8-bit integers (signed or unsigned) (`Bigarray.int8_signed_elt`[45] or `Bigarray.int8_unsigned_elt`[45]),
- 16-bit integers (signed or unsigned) (`Bigarray.int16_signed_elt`[45] or `Bigarray.int16_unsigned_elt`[45]),
- Caml integers (signed, 31 bits on 32-bit architectures, 63 bits on 64-bit architectures) (`Bigarray.int_elt`[45]),
- 32-bit signed integer (`Bigarray.int32_elt`[45]),
- 64-bit signed integers (`Bigarray.int64_elt`[45]),
- platform-native signed integers (32 bits on 32-bit architectures, 64 bits on 64-bit architectures) (`Bigarray.nativeint_elt`[45]).

Each element kind is represented at the type level by one of the abstract types defined below.

```

type float32_elt
type float64_elt
type complex32_elt
type complex64_elt
type int8_signed_elt
type int8_unsigned_elt
type int16_signed_elt
type int16_unsigned_elt
type int_elt
type int32_elt
type int64_elt
type nativeint_elt
type ('a, 'b) kind
```

To each element kind is associated a Caml type, which is the type of Caml values that can be stored in the big array or read back from it. This type is not necessarily the same as the type of the array elements proper: for instance, a big array whose elements are of kind `float32_elt` contains 32-bit single precision floats, but reading or writing one of its elements from Caml uses the Caml type `float`, which is 64-bit double precision floats.

The abstract type `('a, 'b) kind` captures this association of a Caml type `'a` for values read or written in the big array, and of an element kind `'b` which represents the actual contents of the big array. The following predefined values of type `kind` list all possible associations of Caml types with element kinds:

```
val float32 : (float, float32_elt) kind
    See Bigarray.char[45].

val float64 : (float, float64_elt) kind
    See Bigarray.char[45].

val complex32 : (Complex.t, complex32_elt) kind
    See Bigarray.char[45].

val complex64 : (Complex.t, complex64_elt) kind
    See Bigarray.char[45].

val int8_signed : (int, int8_signed_elt) kind
    See Bigarray.char[45].

val int8_unsigned : (int, int8_unsigned_elt) kind
    See Bigarray.char[45].

val int16_signed : (int, int16_signed_elt) kind
    See Bigarray.char[45].

val int16_unsigned : (int, int16_unsigned_elt) kind
    See Bigarray.char[45].

val int : (int, int_elt) kind
    See Bigarray.char[45].

val int32 : (int32, int32_elt) kind
    See Bigarray.char[45].

val int64 : (int64, int64_elt) kind
    See Bigarray.char[45].

val nativeint : (nativeint, nativeint_elt) kind
    See Bigarray.char[45].
```

```
val char : (char, int8_unsigned_elt) kind
```

As shown by the types of the values above, big arrays of kind `float32_elt` and `float64_elt` are accessed using the Caml type `float`. Big arrays of complex kinds `complex32_elt`, `complex64_elt` are accessed with the Caml type `Complex.t`[8]. Big arrays of integer kinds are accessed using the smallest Caml integer type large enough to represent the array elements: `int` for 8- and 16-bit integer bigarrays, as well as Caml-integer bigarrays; `int32` for 32-bit integer bigarrays; `int64` for 64-bit integer bigarrays; and `nativeint` for platform-native integer bigarrays. Finally, big arrays of kind `int8_unsigned_elt` can also be accessed as arrays of characters instead of arrays of small integers, by using the kind value `char` instead of `int8_unsigned`.

Array layouts

```
type c_layout
```

See `Bigarray.fortran_layout`[45].

```
type fortran_layout
```

To facilitate interoperability with existing C and Fortran code, this library supports two different memory layouts for big arrays, one compatible with the C conventions, the other compatible with the Fortran conventions.

In the C-style layout, array indices start at 0, and multi-dimensional arrays are laid out in row-major format. That is, for a two-dimensional array, all elements of row 0 are contiguous in memory, followed by all elements of row 1, etc. In other terms, the array elements at (x, y) and $(x, y+1)$ are adjacent in memory.

In the Fortran-style layout, array indices start at 1, and multi-dimensional arrays are laid out in column-major format. That is, for a two-dimensional array, all elements of column 0 are contiguous in memory, followed by all elements of column 1, etc. In other terms, the array elements at (x, y) and $(x+1, y)$ are adjacent in memory.

Each layout style is identified at the type level by the abstract types `Bigarray.c_layout`[45] and `fortran_layout` respectively.

```
type 'a layout
```

The type `'a layout` represents one of the two supported memory layouts: C-style if `'a` is `Bigarray.c_layout`[45], Fortran-style if `'a` is `Bigarray.fortran_layout`[45].

Supported layouts

The abstract values `c_layout` and `fortran_layout` represent the two supported layouts at the level of values.

```
val c_layout : c_layout layout
```

```
val fortran_layout : fortran_layout layout
```

Generic arrays (of arbitrarily many dimensions)

```
module Genarray : sig end
```

[45.1]

One-dimensional arrays

```
module Array1 : sig end
```

[45.2]

Two-dimensional arrays

```
module Array2 : sig end
```

[45.3]

Three-dimensional arrays

```
module Array3 : sig end
```

[45.4]

Coercions between generic big arrays and fixed-dimension big arrays

```
val genarray_of_array1 : ('a, 'b, 'c) Array1.t -> ('a, 'b, 'c) Genarray.t
```

Return the generic big array corresponding to the given one-dimensional big array.

```
val genarray_of_array2 : ('a, 'b, 'c) Array2.t -> ('a, 'b, 'c) Genarray.t
```

Return the generic big array corresponding to the given two-dimensional big array.

```
val genarray_of_array3 : ('a, 'b, 'c) Array3.t -> ('a, 'b, 'c) Genarray.t
```

Return the generic big array corresponding to the given three-dimensional big array.

```
val array1_of_genarray : ('a, 'b, 'c) Genarray.t -> ('a, 'b, 'c) Array1.t
```

Return the one-dimensional big array corresponding to the given generic big array. Raise `Invalid_arg` if the generic big array does not have exactly one dimension.

```
val array2_of_genarray : ('a, 'b, 'c) Genarray.t -> ('a, 'b, 'c) Array2.t
```

Return the two-dimensional big array corresponding to the given generic big array. Raise `Invalid_arg` if the generic big array does not have exactly two dimensions.

```
val array3_of_genarray : ('a, 'b, 'c) Genarray.t -> ('a, 'b, 'c) Array3.t
```

Return the three-dimensional big array corresponding to the given generic big array. Raise `Invalid_arg` if the generic big array does not have exactly three dimensions.

Re-shaping big arrays

```
val reshape : ('a, 'b, 'c) Genarray.t ->
```

```
int array -> ('a, 'b, 'c) Genarray.t
```

`reshape b [|d1;...;dN|]` converts the big array `b` to a N-dimensional array of dimensions `d1...dN`. The returned array and the original array `b` share their data and have the same layout. For instance, assuming that `b` is a one-dimensional array of dimension 12, `reshape b [|3;4|]` returns a two-dimensional array `b'` of dimensions 3 and 4. If `b` has C layout, the element `(x,y)` of `b'` corresponds to the element `x * 3 + y` of `b`. If `b` has Fortran layout, the element `(x,y)` of `b'` corresponds to the element `x + (y - 1) * 4` of `b`. The returned big array must have exactly the same number of elements as the original big array `b`. That is, the product of the dimensions of `b` must be equal to `i1 * ... * iN`. Otherwise, `Invalid_arg` is raised.

```
val reshape_1 : ('a, 'b, 'c) Genarray.t -> int -> ('a, 'b, 'c) Array1.t
```

Specialized version of `Bigarray.reshape`[45] for reshaping to one-dimensional arrays.

```
val reshape_2 :
  ('a, 'b, 'c) Genarray.t ->
  int -> int -> ('a, 'b, 'c) Array2.t
```

Specialized version of `Bigarray.reshape`[45] for reshaping to two-dimensional arrays.

```
val reshape_3 :
  ('a, 'b, 'c) Genarray.t ->
  int -> int -> int -> ('a, 'b, 'c) Array3.t
```

Specialized version of `Bigarray.reshape`[45] for reshaping to three-dimensional arrays.

45.1 Module `Bigarray.Genarray`

```
module Genarray : sig
```

```
type ('a, 'b, 'c) t
```

The type `Genarray.t` is the type of big arrays with variable numbers of dimensions. Any number of dimensions between 1 and 16 is supported.

The three type parameters to `Genarray.t` identify the array element kind and layout, as follows:

- the first parameter, `'a`, is the Caml type for accessing array elements (`float`, `int`, `int32`, `int64`, `nativeint`);
- the second parameter, `'b`, is the actual kind of array elements (`float32_elt`, `float64_elt`, `int8_signed_elt`, `int8_unsigned_elt`, etc);
- the third parameter, `'c`, identifies the array layout (`c_layout` or `fortran_layout`).

For instance, `(float, float32_elt, fortran_layout) Genarray.t` is the type of generic big arrays containing 32-bit floats in Fortran layout; reads and writes in this array use the Caml type `float`.

```
val create :
  ('a, 'b) Bigarray.kind ->
  'c Bigarray.layout -> int array -> ('a, 'b, 'c) t
```

`Genarray.create kind layout dimensions` returns a new big array whose element kind is determined by the parameter `kind` (one of `float32`, `float64`, `int8_signed`, etc) and whose layout is determined by the parameter `layout` (one of `c_layout` or `fortran_layout`). The `dimensions` parameter is an array of integers that indicate the size of the big array in each dimension. The length of `dimensions` determines the number of dimensions of the bigarray.

For instance, `Genarray.create int32 c_layout [|4;6;8|]` returns a fresh big array of 32-bit integers, in C layout, having three dimensions, the three dimensions being 4, 6 and 8 respectively.

Big arrays returned by `Genarray.create` are not initialized: the initial values of array elements is unspecified.

`Genarray.create` raises `Invalid_arg` if the number of dimensions is not in the range 1 to 16 inclusive, or if one of the dimensions is negative.

`val num_dims : ('a, 'b, 'c) t -> int`

Return the number of dimensions of the given big array.

`val dims : ('a, 'b, 'c) t -> int array`

`Genarray.dims a` returns all dimensions of the big array `a`, as an array of integers of length `Genarray.num_dims a`.

`val nth_dim : ('a, 'b, 'c) t -> int -> int`

`Genarray.nth_dim a n` returns the `n`-th dimension of the big array `a`. The first dimension corresponds to `n = 0`; the second dimension corresponds to `n = 1`; the last dimension, to `n = Genarray.num_dims a - 1`. Raise `Invalid_arg` if `n` is less than 0 or greater or equal than `Genarray.num_dims a`.

`val kind : ('a, 'b, 'c) t -> ('a, 'b) Bigarray.kind`

Return the kind of the given big array.

`val layout : ('a, 'b, 'c) t -> 'c Bigarray.layout`

Return the layout of the given big array.

`val get : ('a, 'b, 'c) t -> int array -> 'a`

Read an element of a generic big array. `Genarray.get a [|i1; ...; iN|]` returns the element of `a` whose coordinates are `i1` in the first dimension, `i2` in the second dimension, ..., `iN` in the `N`-th dimension.

If `a` has C layout, the coordinates must be greater or equal than 0 and strictly less than the corresponding dimensions of `a`. If `a` has Fortran layout, the coordinates must be greater or equal than 1 and less or equal than the corresponding dimensions of `a`. Raise `Invalid_arg` if the array `a` does not have exactly `N` dimensions, or if the coordinates are outside the array bounds.

If `N > 3`, alternate syntax is provided: you can write `a.{i1, i2, ..., iN}` instead of `Genarray.get a [|i1; ...; iN|]`. (The syntax `a.{...}` with one, two or three coordinates is reserved for accessing one-, two- and three-dimensional arrays as described below.)

`val set : ('a, 'b, 'c) t -> int array -> 'a -> unit`

Assign an element of a generic big array. `Genarray.set a [|i1; ...; iN|] v` stores the value `v` in the element of `a` whose coordinates are `i1` in the first dimension, `i2` in the second dimension, ..., `iN` in the `N`-th dimension.

The array `a` must have exactly `N` dimensions, and all coordinates must lie inside the array bounds, as described for `Genarray.get`; otherwise, `Invalid_arg` is raised.

If `N > 3`, alternate syntax is provided: you can write `a.{i1, i2, ..., iN} <- v` instead of `Genarray.set a [|i1; ...; iN|] v`. (The syntax `a.{...} <- v` with one, two or three coordinates is reserved for updating one-, two- and three-dimensional arrays as described below.)

```

val sub_left :
  ('a, 'b, Bigarray.c_layout) t ->
  int -> int -> ('a, 'b, Bigarray.c_layout) t

```

Extract a sub-array of the given big array by restricting the first (left-most) dimension. `Genarray.sub_left a ofs len` returns a big array with the same number of dimensions as `a`, and the same dimensions as `a`, except the first dimension, which corresponds to the interval `[ofs ... ofs + len - 1]` of the first dimension of `a`. No copying of elements is involved: the sub-array and the original array share the same storage space. In other terms, the element at coordinates `[|i1; ...; iN|]` of the sub-array is identical to the element at coordinates `[|i1+ofs; ...; iN|]` of the original array `a`.

`Genarray.sub_left` applies only to big arrays in C layout. Raise `Invalid_arg` if `ofs` and `len` do not designate a valid sub-array of `a`, that is, if `ofs < 0`, or `len < 0`, or `ofs + len > Genarray.nth_dim a 0`.

```

val sub_right :
  ('a, 'b, Bigarray.fortran_layout) t ->
  int -> int -> ('a, 'b, Bigarray.fortran_layout) t

```

Extract a sub-array of the given big array by restricting the last (right-most) dimension. `Genarray.sub_right a ofs len` returns a big array with the same number of dimensions as `a`, and the same dimensions as `a`, except the last dimension, which corresponds to the interval `[ofs ... ofs + len - 1]` of the last dimension of `a`. No copying of elements is involved: the sub-array and the original array share the same storage space. In other terms, the element at coordinates `[|i1; ...; iN|]` of the sub-array is identical to the element at coordinates `[|i1; ...; iN+ofs|]` of the original array `a`.

`Genarray.sub_right` applies only to big arrays in Fortran layout. Raise `Invalid_arg` if `ofs` and `len` do not designate a valid sub-array of `a`, that is, if `ofs < 1`, or `len < 0`, or `ofs + len > Genarray.nth_dim a (Genarray.num_dims a - 1)`.

```

val slice_left :
  ('a, 'b, Bigarray.c_layout) t ->
  int array -> ('a, 'b, Bigarray.c_layout) t

```

Extract a sub-array of lower dimension from the given big array by fixing one or several of the first (left-most) coordinates. `Genarray.slice_left a [|i1; ... ; iM|]` returns the “slice” of `a` obtained by setting the first `M` coordinates to `i1, ..., iM`. If `a` has `N` dimensions, the slice has dimension `N - M`, and the element at coordinates `[|j1; ...; j(N-M)|]` in the slice is identical to the element at coordinates `[|i1; ...; iM; j1; ...; j(N-M)|]` in the original array `a`. No copying of elements is involved: the slice and the original array share the same storage space.

`Genarray.slice_left` applies only to big arrays in C layout. Raise `Invalid_arg` if `M >= N`, or if `[|i1; ... ; iM|]` is outside the bounds of `a`.

```

val slice_right :
  ('a, 'b, Bigarray.fortran_layout) t ->
  int array -> ('a, 'b, Bigarray.fortran_layout) t

```

Extract a sub-array of lower dimension from the given big array by fixing one or several of the last (right-most) coordinates. `Genarray.slice_right a [|i1; ... ; iM|]` returns the “slice” of `a` obtained by setting the last `M` coordinates to `i1, ..., iM`. If `a` has `N` dimensions, the slice has dimension `N - M`, and the element at coordinates `[|j1; ... ; j(N-M)|]` in the slice is identical to the element at coordinates `[|j1; ... ; j(N-M); i1; ... ; iM|]` in the original array `a`. No copying of elements is involved: the slice and the original array share the same storage space.

`Genarray.slice_right` applies only to big arrays in Fortran layout. Raise `Invalid_arg` if `M >= N`, or if `[|i1; ... ; iM|]` is outside the bounds of `a`.

```
val blit : ('a, 'b, 'c) t -> ('a, 'b, 'c) t -> unit
```

Copy all elements of a big array in another big array. `Genarray.blit src dst` copies all elements of `src` into `dst`. Both arrays `src` and `dst` must have the same number of dimensions and equal dimensions. Copying a sub-array of `src` to a sub-array of `dst` can be achieved by applying `Genarray.blit` to sub-array or slices of `src` and `dst`.

```
val fill : ('a, 'b, 'c) t -> 'a -> unit
```

Set all elements of a big array to a given value. `Genarray.fill a v` stores the value `v` in all elements of the big array `a`. Setting only some elements of `a` to `v` can be achieved by applying `Genarray.fill` to a sub-array or a slice of `a`.

```
val map_file :
```

```
    Unix.file_descr ->
```

```
    ('a, 'b) Bigarray.kind ->
```

```
    'c Bigarray.layout -> bool -> int array -> ('a, 'b, 'c) t
```

Memory mapping of a file as a big array. `Genarray.map_file fd kind layout shared dims` returns a big array of kind `kind`, layout `layout`, and dimensions as specified in `dims`. The data contained in this big array are the contents of the file referred to by the file descriptor `fd` (as opened previously with `Unix.openfile`, for example). If `shared` is `true`, all modifications performed on the array are reflected in the file. This requires that `fd` be opened with write permissions. If `shared` is `false`, modifications performed on the array are done in memory only, using copy-on-write of the modified pages; the underlying file is not affected.

`Genarray.map_file` is much more efficient than reading the whole file in a big array, modifying that big array, and writing it afterwards.

To adjust automatically the dimensions of the big array to the actual size of the file, the major dimension (that is, the first dimension for an array with C layout, and the last dimension for an array with Fortran layout) can be given as `-1`. `Genarray.map_file` then determines the major dimension from the size of the file. The file must contain an integral number of sub-arrays as determined by the non-major dimensions, otherwise `Failure` is raised.

If all dimensions of the big array are given, the file size is matched against the size of the big array. If the file is larger than the big array, only the initial portion of the file is mapped to the big array. If the file is smaller than the big array, the file is automatically grown to the size of the big array. This requires write permissions on `fd`.

end

45.2 Module `Bigarray.Array1` : One-dimensional arrays.

module `Array1` : sig

The `Array1` structure provides operations similar to those of `Bigarray.Genarray`[45.1], but specialized to the case of one-dimensional arrays. (The `Array2` and `Array3` structures below provide operations specialized for two- and three-dimensional arrays.) Statically knowing the number of dimensions of the array allows faster operations, and more precise static type-checking.

type ('a, 'b, 'c) t

The type of one-dimensional big arrays whose elements have Caml type 'a, representation kind 'b, and memory layout 'c.

val create :

('a, 'b) Bigarray.kind ->

'c Bigarray.layout -> int -> ('a, 'b, 'c) t

`Array1.create` kind layout dim returns a new bigarray of one dimension, whose size is dim. kind and layout determine the array element kind and the array layout as described for `Genarray.create`.

val dim : ('a, 'b, 'c) t -> int

Return the size (dimension) of the given one-dimensional big array.

val kind : ('a, 'b, 'c) t -> ('a, 'b) Bigarray.kind

Return the kind of the given big array.

val layout : ('a, 'b, 'c) t -> 'c Bigarray.layout

Return the layout of the given big array.

val get : ('a, 'b, 'c) t -> int -> 'a

`Array1.get` a x, or alternatively `a.{x}`, returns the element of a at index x. x must be greater or equal than 0 and strictly less than `Array1.dim a` if a has C layout. If a has Fortran layout, x must be greater or equal than 1 and less or equal than `Array1.dim a`. Otherwise, `Invalid_arg` is raised.

val set : ('a, 'b, 'c) t -> int -> 'a -> unit

`Array1.set` a x v, also written `a.{x} <- v`, stores the value v at index x in a. x must be inside the bounds of a as described in `Bigarray.Array1.get`[45.2]; otherwise, `Invalid_arg` is raised.

val sub : ('a, 'b, 'c) t ->

int -> int -> ('a, 'b, 'c) t

Extract a sub-array of the given one-dimensional big array. See `Genarray.sub_left` for more details.

```

val blit : ('a, 'b, 'c) t -> ('a, 'b, 'c) t -> unit
    Copy the first big array to the second big array. See Genarray.blit for more details.

val fill : ('a, 'b, 'c) t -> 'a -> unit
    Fill the given big array with the given value. See Genarray.fill for more details.

val of_array :
    ('a, 'b) Bigarray.kind ->
    'c Bigarray.layout -> 'a array -> ('a, 'b, 'c) t
    Build a one-dimensional big array initialized from the given array.

val map_file :
    Unix.file_descr ->
    ('a, 'b) Bigarray.kind ->
    'c Bigarray.layout -> bool -> int -> ('a, 'b, 'c) t
    Memory mapping of a file as a one-dimensional big array. See
    Bigarray.Genarray.map_file[45.1] for more details.

end

```

45.3 Module `Bigarray.Array2` : Two-dimensional arrays.

`module Array2 : sig`

The `Array2` structure provides operations similar to those of `Bigarray.Genarray`[45.1], but specialized to the case of two-dimensional arrays.

```

type ('a, 'b, 'c) t
    The type of two-dimensional big arrays whose elements have Caml type 'a, representation
    kind 'b, and memory layout 'c.

val create :
    ('a, 'b) Bigarray.kind ->
    'c Bigarray.layout -> int -> int -> ('a, 'b, 'c) t
    Array2.create kind layout dim1 dim2 returns a new bigarray of two dimension, whose
    size is dim1 in the first dimension and dim2 in the second dimension. kind and layout
    determine the array element kind and the array layout as described for
    Bigarray.Genarray.create[45.1].

val dim1 : ('a, 'b, 'c) t -> int
    Return the first dimension of the given two-dimensional big array.

val dim2 : ('a, 'b, 'c) t -> int
    Return the second dimension of the given two-dimensional big array.

val kind : ('a, 'b, 'c) t -> ('a, 'b) Bigarray.kind

```

Return the kind of the given big array.

```
val layout : ('a, 'b, 'c) t -> 'c Bigarray.layout
```

Return the layout of the given big array.

```
val get : ('a, 'b, 'c) t -> int -> int -> 'a
```

`Array2.get a x y`, also written `a.{x,y}`, returns the element of `a` at coordinates `(x, y)`. `x` and `y` must be within the bounds of `a`, as described for `Bigarray.Genarray.get`[45.1]; otherwise, `Invalid_arg` is raised.

```
val set : ('a, 'b, 'c) t -> int -> int -> 'a -> unit
```

`Array2.set a x y v`, or alternatively `a.{x,y} <- v`, stores the value `v` at coordinates `(x, y)` in `a`. `x` and `y` must be within the bounds of `a`, as described for `Bigarray.Genarray.set`[45.1]; otherwise, `Invalid_arg` is raised.

```
val sub_left :
```

```
('a, 'b, Bigarray.c_layout) t ->
```

```
int -> int -> ('a, 'b, Bigarray.c_layout) t
```

Extract a two-dimensional sub-array of the given two-dimensional big array by restricting the first dimension. See `Bigarray.Genarray.sub_left`[45.1] for more details.

`Array2.sub_left` applies only to arrays with C layout.

```
val sub_right :
```

```
('a, 'b, Bigarray.fortran_layout) t ->
```

```
int -> int -> ('a, 'b, Bigarray.fortran_layout) t
```

Extract a two-dimensional sub-array of the given two-dimensional big array by restricting the second dimension. See `Bigarray.Genarray.sub_right`[45.1] for more details.

`Array2.sub_right` applies only to arrays with Fortran layout.

```
val slice_left :
```

```
('a, 'b, Bigarray.c_layout) t ->
```

```
int -> ('a, 'b, Bigarray.c_layout) Bigarray.Array1.t
```

Extract a row (one-dimensional slice) of the given two-dimensional big array. The integer parameter is the index of the row to extract. See `Bigarray.Genarray.slice_left`[45.1] for more details. `Array2.slice_left` applies only to arrays with C layout.

```
val slice_right :
```

```
('a, 'b, Bigarray.fortran_layout) t ->
```

```
int -> ('a, 'b, Bigarray.fortran_layout) Bigarray.Array1.t
```

Extract a column (one-dimensional slice) of the given two-dimensional big array. The integer parameter is the index of the column to extract. See `Bigarray.Genarray.slice_right`[45.1] for more details. `Array2.slice_right` applies only to arrays with Fortran layout.

```
val blit : ('a, 'b, 'c) t -> ('a, 'b, 'c) t -> unit
```

Copy the first big array to the second big array. See `Bigarray.Genarray.blit`[45.1] for more details.

```

val fill : ('a, 'b, 'c) t -> 'a -> unit
    Fill the given big array with the given value. See Bigarray.Genarray.fill[45.1] for more
    details.

val of_array :
    ('a, 'b) Bigarray.kind ->
    'c Bigarray.layout -> 'a array array -> ('a, 'b, 'c) t
    Build a two-dimensional big array initialized from the given array of arrays.

val map_file :
    Unix.file_descr ->
    ('a, 'b) Bigarray.kind ->
    'c Bigarray.layout -> bool -> int -> int -> ('a, 'b, 'c) t
    Memory mapping of a file as a two-dimensional big array. See
    Bigarray.Genarray.map_file[45.1] for more details.

end

```

45.4 Module `Bigarray.Array3` : Three-dimensional arrays.

module `Array3` : sig

The `Array3` structure provides operations similar to those of `Bigarray.Genarray`[45.1], but specialized to the case of three-dimensional arrays.

```

type ('a, 'b, 'c) t

```

The type of three-dimensional big arrays whose elements have Caml type `'a`, representation kind `'b`, and memory layout `'c`.

```

val create :

```

```

    ('a, 'b) Bigarray.kind ->

```

```

    'c Bigarray.layout -> int -> int -> int -> ('a, 'b, 'c) t

```

`Array3.create kind layout dim1 dim2 dim3` returns a new bigarray of three dimension, whose size is `dim1` in the first dimension, `dim2` in the second dimension, and `dim3` in the third. `kind` and `layout` determine the array element kind and the array layout as described for `Bigarray.Genarray.create`[45.1].

```

val dim1 : ('a, 'b, 'c) t -> int

```

Return the first dimension of the given three-dimensional big array.

```

val dim2 : ('a, 'b, 'c) t -> int

```

Return the second dimension of the given three-dimensional big array.

```

val dim3 : ('a, 'b, 'c) t -> int

```

Return the third dimension of the given three-dimensional big array.

```

val kind : ('a, 'b, 'c) t -> ('a, 'b) Bigarray.kind
    Return the kind of the given big array.

val layout : ('a, 'b, 'c) t -> 'c Bigarray.layout
    Return the layout of the given big array.

val get : ('a, 'b, 'c) t -> int -> int -> int -> 'a
    Array3.get a x y z, also written a.{x,y,z}, returns the element of a at coordinates (x, y, z). x, y and z must be within the bounds of a, as described for Bigarray.Genarray.get[45.1]; otherwise, Invalid_arg is raised.

val set : ('a, 'b, 'c) t -> int -> int -> int -> 'a -> unit
    Array3.set a x y v, or alternatively a.{x,y,z} <- v, stores the value v at coordinates (x, y, z) in a. x, y and z must be within the bounds of a, as described for Bigarray.Genarray.set[45.1]; otherwise, Invalid_arg is raised.

val sub_left :
    ('a, 'b, Bigarray.c_layout) t ->
    int -> int -> ('a, 'b, Bigarray.c_layout) t
    Extract a three-dimensional sub-array of the given three-dimensional big array by restricting the first dimension. See Bigarray.Genarray.sub_left[45.1] for more details.
    Array3.sub_left applies only to arrays with C layout.

val sub_right :
    ('a, 'b, Bigarray.fortran_layout) t ->
    int -> int -> ('a, 'b, Bigarray.fortran_layout) t
    Extract a three-dimensional sub-array of the given three-dimensional big array by restricting the second dimension. See Bigarray.Genarray.sub_right[45.1] for more details.
    Array3.sub_right applies only to arrays with Fortran layout.

val slice_left_1 :
    ('a, 'b, Bigarray.c_layout) t ->
    int -> int -> ('a, 'b, Bigarray.c_layout) Bigarray.Array1.t
    Extract a one-dimensional slice of the given three-dimensional big array by fixing the first two coordinates. The integer parameters are the coordinates of the slice to extract. See Bigarray.Genarray.slice_left[45.1] for more details. Array3.slice_left_1 applies only to arrays with C layout.

val slice_right_1 :
    ('a, 'b, Bigarray.fortran_layout) t ->
    int -> int -> ('a, 'b, Bigarray.fortran_layout) Bigarray.Array1.t
    Extract a one-dimensional slice of the given three-dimensional big array by fixing the last two coordinates. The integer parameters are the coordinates of the slice to extract. See Bigarray.Genarray.slice_right[45.1] for more details. Array3.slice_right_1 applies only to arrays with Fortran layout.

```



```

val slice_left_2 :
  ('a, 'b, Bigarray.c_layout) t ->
int -> ('a, 'b, Bigarray.c_layout) Bigarray.Array2.t
  Extract a two-dimensional slice of the given three-dimensional big array by fixing the first
  coordinate. The integer parameter is the first coordinate of the slice to extract. See
  Bigarray.Genarray.slice_left[45.1] for more details. Array3.slice_left_2 applies only
  to arrays with C layout.

val slice_right_2 :
  ('a, 'b, Bigarray.fortran_layout) t ->
int -> ('a, 'b, Bigarray.fortran_layout) Bigarray.Array2.t
  Extract a two-dimensional slice of the given three-dimensional big array by fixing the last
  coordinate. The integer parameter is the coordinate of the slice to extract. See
  Bigarray.Genarray.slice_right[45.1] for more details. Array3.slice_right_2 applies
  only to arrays with Fortran layout.

val blit : ('a, 'b, 'c) t -> ('a, 'b, 'c) t -> unit
  Copy the first big array to the second big array. See Bigarray.Genarray.blit[45.1] for
  more details.

val fill : ('a, 'b, 'c) t -> 'a -> unit
  Fill the given big array with the given value. See Bigarray.Genarray.fill[45.1] for more
  details.

val of_array :
  ('a, 'b) Bigarray.kind ->
  'c Bigarray.layout -> 'a array array array -> ('a, 'b, 'c) t
  Build a three-dimensional big array initialized from the given array of arrays of arrays.

val map_file :
  Unix.file_descr ->
  ('a, 'b) Bigarray.kind ->
  'c Bigarray.layout ->
  bool -> int -> int -> int -> ('a, 'b, 'c) t
  Memory mapping of a file as a three-dimensional big array. See
  Bigarray.Genarray.map_file[45.1] for more details.

end

```

46 Module Num : Operation on arbitrary-precision numbers.

Numbers (type `num`) are arbitrary-precision rational numbers, plus the special elements `1/0` (infinity) and `0/0` (undefined).

```
type num =
```

```
| Int of int
| Big_int of Big_int.big_int
| Ratio of Ratio.ratio
```

The type of numbers.

Arithmetic operations

```
val (+/) : num -> num -> num
    Same as Num.add_num[46].
```

```
val add_num : num -> num -> num
    Addition
```

```
val minus_num : num -> num
    Unary negation.
```

```
val (-/) : num -> num -> num
    Same as Num.sub_num[46].
```

```
val sub_num : num -> num -> num
    Subtraction
```

```
val (*/) : num -> num -> num
    Same as Num.mult_num[46].
```

```
val mult_num : num -> num -> num
    Multiplication
```

```
val square_num : num -> num
    Squaring
```

```
val (//) : num -> num -> num
    Same as Num.div_num[46].
```

```
val div_num : num -> num -> num
    Division
```

```
val quo_num : num -> num -> num
    Euclidean division: quotient.
```

```
val mod_num : num -> num -> num
    Euclidean division: remainder.
```

```
val (**/) : num -> num -> num
    Same as Num.power_num[46].
```

```
val power_num : num -> num -> num
```

Exponentiation

```
val abs_num : num -> num
```

Absolute value.

```
val succ_num : num -> num
```

succ *n* is *n*+1

```
val pred_num : num -> num
```

pred *n* is *n*-1

```
val incr_num : num Pervasives.ref -> unit
```

incr *r* is *r*:=!*r*+1, where *r* is a reference to a number.

```
val decr_num : num Pervasives.ref -> unit
```

decr *r* is *r*:=!*r*-1, where *r* is a reference to a number.

```
val is_integer_num : num -> bool
```

Test if a number is an integer

The four following functions approximate a number by an integer :

```
val integer_num : num -> num
```

integer_num *n* returns the integer closest to *n*. In case of ties, rounds towards zero.

```
val floor_num : num -> num
```

floor_num *n* returns the largest integer smaller or equal to *n*.

```
val round_num : num -> num
```

round_num *n* returns the integer closest to *n*. In case of ties, rounds off zero.

```
val ceiling_num : num -> num
```

ceiling_num *n* returns the smallest integer bigger or equal to *n*.

```
val sign_num : num -> int
```

Return -1, 0 or 1 according to the sign of the argument.

Comparisons between numbers

```
val (=/) : num -> num -> bool
```

```
val (</) : num -> num -> bool
```

```
val (>/) : num -> num -> bool
```

```
val (<=/) : num -> num -> bool
```

```
val (>=/) : num -> num -> bool
```

```
val (<>/) : num -> num -> bool
```

```

val eq_num : num -> num -> bool
val lt_num : num -> num -> bool
val le_num : num -> num -> bool
val gt_num : num -> num -> bool
val ge_num : num -> num -> bool
val compare_num : num -> num -> int
    Return -1, 0 or 1 if the first argument is less than, equal to, or greater than the second
    argument.

val max_num : num -> num -> num
    Return the greater of the two arguments.

val min_num : num -> num -> num
    Return the smaller of the two arguments.

Coercions with strings
val string_of_num : num -> string
    Convert a number to a string, using fractional notation.

val approx_num_fix : int -> num -> string
    See Num.approx_num_exp[46].

val approx_num_exp : int -> num -> string
    Approximate a number by a decimal. The first argument is the required precision. The
    second argument is the number to approximate. Num.approx_num_fix[46] uses decimal
    notation; the first argument is the number of digits after the decimal point. approx_num_exp
    uses scientific (exponential) notation; the first argument is the number of digits in the
    mantissa.

val num_of_string : string -> num
    Convert a string to a number.

Coercions between numerical types
val int_of_num : num -> int
val num_of_int : int -> num
val nat_of_num : num -> Nat.nat
val num_of_nat : Nat.nat -> num
val num_of_big_int : Big_int.big_int -> num
val big_int_of_num : num -> Big_int.big_int
val ratio_of_num : num -> Ratio.ratio
val num_of_ratio : Ratio.ratio -> num
val float_of_num : num -> float

```