

CREF(I)

CREF(I)

NAME

`cref` - make cross reference listing

SYNOPSIS

`cref [-acilostux123] name ...`

DESCRIPTION

Cref makes a cross reference listing of program files in assembler or C format. The files named as arguments in the command line are searched for symbols in the appropriate syntax. The output report is in four columns:

(1)	(2)	(3)	(4)
symbol	file	see below	text as it appears in file

Cref may use either an *ignore* file or an *only* file. If the `-i` option is given, the next argument is taken to be an *ignore* file; if the `-o` option is given, the next argument is taken to be an *only* file. *Ignore* and *only* files are lists of symbols separated by new lines. All symbols in an *ignore* file are ignored in columns (1) and (3) of the output. If an *only* file is given, only symbols in that file appear in column (1). At most one of `-i` and `-o` may be used. The default setting is `-i`. Assembler predefined symbols or C keywords are ignored. The `-s` option causes current symbols to be put in column 3. In the assembler, the current symbol is the most recent name symbol; in C, it is the current function name. The `-l` option causes the line number within the file to be put in column 3. The `-t` option causes the next available argument to be used as the name of the intermediate temporary file (instead of `/tmp/crt??`). The file is created and is not removed at the end of the process. The format of the output under this option is not as above.

Options:

- a** assembler format (default)
- c** C format input
- i** use *ignore* file (see above)
- l** put line number in col. 3 (instead of current symbol)
- o** use *only* file (see above)
- s** current symbol in col. 3 (default)
- t** user supplied temporary file
- u** print only symbols that occur exactly once
- x** print only C external symbols
- 1** sort output on column 1 (default)
- 2** sort output on column 2
- 3** sort output on column 3

FILES

<code>/tmp/crt??</code>	temporaries
<code>/usr/lib/aign</code>	default assembler <i>ignore</i> file
<code>/usr/lib/cign</code>	default C <i>ignore</i> file
<code>/usr/bin/crpost</code>	post processor
<code>/usr/bin/upost</code>	post processor for <code>-u</code> option
<code>/bin/sort</code>	used to sort temporaries

SEE ALSO

`as` (I), `cc` (I)